



BE SURE. BUILD SURE.

Page 1/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **Konudur 160 PL-XL - Komponente A**

Article number: 911

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Epoxy sealing

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +48612864565

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



GHS07 GHS09

##### Signal word

Warning

(Contd. on page 2)

IE



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

**Trade name Konudur 160 PL-XL - Komponente A**

(Contd. of page 1)

- **Hazard-determining components of labelling:** Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight < 700  
1,6-hexene-diglycidylether  
2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700  
maleic anhydride  
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
- **Hazard statements**  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves / eye protection / face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.
- **Additional information:** To avoid risks to human health and the environment, comply with the instructions for use.  
Contains epoxy constituents. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 1675-54-3 EINECS: 216-823-5	bis[4-(2,3-epoxypropoxy)phenyl]propane Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	70-100%
CAS: 16096-31-4 EINECS: 240-260-4	1,6-hexene-diglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥10-<25%
CAS: 9003-36-5 NLP: 500-006-8	2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥10-<25%

(Contd. on page 3)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

**Trade name Konudur 160 PL-XL - Komponente A**

(Contd. of page 2)

CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	≥0.1-<0.5%
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.1-<0.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Seek medical treatment.
- **After swallowing** Rinse out mouth and then drink plenty of water. Seek medical treatment.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:**

No special measures required.

#### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Not required.

· **6.2 Environmental precautions:**

Prevent material from reaching sewage system, holes and cellars.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **6.4 Reference to other sections**

See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

**Trade name Konudur 160 PL-XL - Komponente A**

See Section 13 for information on disposal.

(Contd. of page 3)

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
*Store in cool, dry place in tightly closed containers.  
Open and handle container with care.*
- **Information about protection against explosions and fires:** *No special measures required.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep container tightly sealed.*
- **7.3 Specific end use(s)** *No further relevant information available.*

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical systems:** *No further data; see item 7.*
- **Components with critical values that require monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

#### · DNELs

##### **16096-31-4 1,6-hexene-diglycidylether**

Dermal DNEL 2.8 mg/kg bw/day (ArL)

Inhalative DNEL 4.9 mg/m<sup>3</sup> (ArL)

##### **68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs**

Oral DNEL 1 mg/kg bw/Tag (ArL)

Dermal DNEL 1.7 mg/kg bw/day (ArL)

Inhalative DNEL 0.98 mg/m<sup>3</sup> (ArL)

#### · PNECs

##### **16096-31-4 1,6-hexene-diglycidylether**

PNEC 0.0115 mg/l (Fresh water)

0.00115 mg/l (Mew)

PNEC 0.223 mg/kg dwt (Bod)

0.0283 mg/kg dwt (Sediment)

(Contd. on page 5)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

**Trade name Konudur 160 PL-XL - Komponente A**

(Contd. of page 4)

	0.283 mg/kg dwt (Fresh water sediment)
<b>68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs</b>	
PNEC	0.00072 mg/l (Mew)
	0.0072 mg/l (Suw)
PNEC	80.12 mg/kg dwt (Bod)
	6.677 mg/kg dwt (Sediment)
	66.77 mg/kg dwt (Fresh water sediment)

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**
  - Keep away from foodstuffs, beverages and food.
  - Instantly remove any soiled and impregnated garments.
  - Wash hands during breaks and at the end of the work.
  - Avoid contact with the eyes and skin.
- **Protection of hands:**
  - Protective gloves.
  - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
  - After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves**
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
  - The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
  - Safety glasses
  - Tightly sealed safety glasses.
- **Body protection:**
  - Protective work clothing.

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
  - Form:** Fluid
  - Colour:** According to product specification
  - Smell:** Characteristic
- **Change in condition**
  - Melting point/freezing point:** Not determined
  - Initial boiling point and boiling range:** 200 °C

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

Trade name Konudur 160 PL-XL - Komponente A

(Contd. of page 5)

· <b>Flash point:</b>	141 °C
· <b>Ignition temperature:</b>	184 °C
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive.
· <b>Steam pressure at 20 °C:</b>	0.1 hPa
· <b>Density at 20 °C</b>	1.17 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	
· <b>Thermal decomposition / conditions to be avoided:</b>	No decomposition if used according to specifications.
· <b>10.3 Possibility of hazardous reactions</b>	No dangerous reactions known
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.
· <b>10.6 Hazardous decomposition products:</b>	No dangerous decomposition products known

### SECTION 11: Toxicological information

· <b>11.1 Information on toxicological effects</b>	
· <b>Acute toxicity</b>	Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

**16096-31-4 1,6-hexene-diglycidylether**

Oral	LD50	>8500 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>4900 mg/kg (rat)
--------	------	-------------------

**9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700**

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

**13463-67-7 titanium dioxide**

Oral	LD50	>10000 mg/kg (rat)
------	------	--------------------

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

**Trade name Konudur 160 PL-XL - Komponente A**

(Contd. of page 6)

Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)
<b>68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs</b>		
Oral	LD50	17100 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

#### **1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane**

IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)

#### **16096-31-4 1,6-hexene-diglycidylether**

LC50/96h	30 mg/l (Leucidus idus)
EC50/48h	47 mg/l (Daphnia magna)

#### **9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700**

LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

#### **68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs**

EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>5000 mg/l (Oncorhynchus mykiss)
	1800 mg/l (Lepomis macrochirus)
EC50	>100 mg/l (BEL)
NOEC	500 mg/l (Pseudokirchneriella subcapitata)

#### · 12.2 Persistence and degradability

No further relevant information available.

(Contd. on page 8)

IE



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

**Trade name Konudur 160 PL-XL - Komponente A**

(Contd. of page 7)

- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **Ecotoxicological effects:**
- **Remark:** *Toxic for fish*
- **Additional ecological information:**
- **General notes:** *Toxic for aquatic organisms  
Also poisonous for fish and plankton in water bodies.  
Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Other adverse effects** *No further relevant information available.*

#### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11	waste paint and varnish containing organic solvents or other dangerous substances

- **Uncleaned packagings:**
- **Recommendation:** *Dispose of packaging according to regulations on the disposal of packagings.  
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

#### SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** *UN3082*
- **14.2 UN proper shipping name**
- **ADR, IATA** *ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)*
- **IMDG** *ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivates), MARINE POLLUTANT*

(Contd. on page 9)





BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

**Trade name Konudur 160 PL-XL - Komponente A**

(Contd. of page 8)

· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR</b>	
· <b>Class</b>	9 (M6) Miscellaneous dangerous substances and articles.
· <b>Label</b>	9
· <b>IMDG, IATA</b>	
· <b>Class</b>	9 Miscellaneous dangerous substances and articles.
· <b>Label</b>	9
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	III
· <b>14.5 Environmental hazards:</b>	Product contains environmentally hazardous substances: epoxide derivates
· <b>Marine pollutant:</b>	Yes Symbol (fish and tree)
· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>Special marking (IATA):</b>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Miscellaneous dangerous substances and articles.
· <b>Kemler Number:</b>	90
· <b>EMS Number:</b>	F-A, S-F
· <b>Stowage Category</b>	A
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	(-)
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

Trade name Konudur 160 PL-XL - Komponente A

(Contd. of page 9)

- **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases** H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.

(Contd. on page 11)

IE



BE SURE. BUILD SURE.

Page 11/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2021

Version number 6

Revision: 15.10.2021

**Trade name Konudur 160 PL-XL - Komponente A**

(Contd. of page 10)

*H411 Toxic to aquatic life with long lasting effects.*

*H412 Harmful to aquatic life with long lasting effects.*

· **Department issuing data specification sheet:**

· **Abbreviations and acronyms:**

*Environment protection department.*

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*DNEL: Derived No-Effect Level (REACH)*

*PNEC: Predicted No-Effect Concentration (REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Carc. 2: Carcinogenicity – Category 2*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

· **\* Data compared to the previous version altered.**

IE