



BE SURE. BUILD SURE.

Page 1/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Konudur 170 TR-NA - Komponente B

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy resin

Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8

D-46238 Bottrop

Tel.: +49(0)2041-101-0

Fax.: +49(0)2041-101-400

E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG

Hagackerstr. 10

CH-8953 Dietikon

Tel.: +44-7400510

Fax : +44-7400533

Informing department:

msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05 GHS07

(Contd. on page 2)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:**
 - Isophorone diamine
 - Polyoxypropylene triamine
 - Polyoxypropylenediamine
 - Polymer with amino-functional groups
 - Hydrocarbons, C9-unsaturated, polymerised
 - 2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid
- **Hazard statements**
 - H302 Harmful if swallowed.
 - H314 Causes severe skin burns and eye damage.
 - H317 May cause an allergic skin reaction.
 - H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
 - P260 Do not breathe dusts or mists.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P310 Immediately call a POISON CENTER/doctor.
 - P321 Specific treatment (see on this label).
 - P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 2855-13-2	Isophoron Diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1030 mg/kg	10-30%
CAS: 39423-51-3	Polyoxypropylene triamine Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312	≥10-<25%
CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine Skin Corr. 1B, H314; Aquatic Chronic 3, H412	≥10-<25%
EC number: 949-140-2	Polymer with amino-functional groups Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	≥3-<10%

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

CAS: 71302-83-5 EC number: 701-299-7	Hydrocarbons, C9-unsaturated, polymerised Asp. Tox. 1, H304; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	(Contd. of page 2) ≥2.5-<5%
EC number: 701-443-9	Phenol, mono- and distyrolised Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1A, H317	≥0.25-<1%

Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur.
If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water.
Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** No special measures required.

(Contd. on page 4)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 3)

- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** None.
- **Storage class** 8A

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 4)

· DNELs

CAS: 2855-13-2 Isophoron Diamine

Oral DNEL 0.526 mg/kg bw/Tag (ArL)

Inhalative DNEL 20.1 mg/m³ (ArL)

CAS: 39423-51-3 Polyoxypropylene triamine

Inhalative DNEL 14 mg/m³ (ArL)

CAS: 9046-10-0 Polyoxypropylenediamine

Oral DNEL 0.04 mg/kg bw/Tag (ArL)

Dermal DNEL 2.5 mg/kg bw/day (ArL)

· PNECs

CAS: 2855-13-2 Isophoron Diamine

PNEC 0.006 mg/l (Mew)

0.06 mg/l (Freshwater)

PNEC 0.578 mg/kg dwt (Sediment)

5.784 mg/kg dwt (Fresh water sediment)

CAS: 39423-51-3 Polyoxypropylene triamine

PNEC 10 mg/l (Sewage Treatment Plant)

0.00044 mg/l (Mew)

0.0044 mg/l (Freshwater)

PNEC 0.002 mg/kg dwt (Bod)

0.002 mg/kg dwt (Sediment)

0.02 mg/kg dwt (Fresh water sediment)

CAS: 9046-10-0 Polyoxypropylenediamine

PNEC 7.5 mg/l (Sewage Treatment Plant)

0.015 mg/l (Fresh water)

PNEC 0.0176 mg/kg dwt (Bod)

0.125 mg/kg dwt (Sediment)

0.132 mg/kg dwt (Fresh water sediment)

· Additional information:

The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

· Breathing equipment:

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

· **Hand protection**

· **Material of gloves**

· **Penetration time of glove material**

· **Eye/face protection**

· **Body protection:**

(Contd. of page 5)

expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

Tight-fitting safety goggles.

Safety goggles.

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

Whitish

· **Smell:**

Characteristic

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/13

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 6)

· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	Not determined
· Flash point:	>150 °C
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C	1.2 g/cm ³

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
--------------------------	--

(Contd. on page 8)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 7)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values that are relevant for classification:**

CAS: 2855-13-2 Isophoron Diamine

Oral	LD50	1030 mg/kg (ATE)
		1030 mg/kg (rat)
Dermal	NOAEL	250 mg/kg (rat)
	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)
		1840 mg/kg (rabbit)

CAS: 39423-51-3 Polyoxypropylene triamine

Oral	LD50	550 mg/kg (rat)
Dermal	LD50	>1000 mg/kg (rat)

CAS: 9046-10-0 Polyoxypropylenediamine

Oral	LD50	2855 mg/kg (Rat)
		2885 mg/kg (rat)
Dermal	LD50	2980 mg/kg (Kan)
		2980 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 8)

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 2855-13-2 Isophoron Diamine

LC50/96h	110 mg/l (fish)
	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (daphnia)
	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus)
	3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)
	>50 mg/l (algae)

CAS: 39423-51-3 Polyoxypropylene triamine

LC50/96h	>100 mg/l (Oncorhynchus mykiss)
EC50/48h	13 mg/l (Daphnia magna)
ErC50/72h	4.4 mg/l (algae)

CAS: 9046-10-0 Polyoxypropylenediamine

EC50/72h	15 mg/l (algae)
LC50/96h	>15 mg/l (fish)
EC50/48h	80 mg/l (daphnia)

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· PBT:

Not applicable.

· vPvB:

Not applicable.

· 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 9)

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Waste disposal key number:** 55352
 Bez.: aliphatische Amine
 Entsorgungshinweise:
 Sonderabfallverbrennung

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP6	Acute Toxicity
HP8	Corrosive
HP13	Sensitising
HP14	Ecotoxic

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN2735

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA** AMINES, LIQUID, CORROSIVE, N.O.S.
 (Polyoxypropylenediamine, ISOPHORONEDIAMINE)

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class** 8 (C7) Corrosive substances.

· **Label** 8

· **IMDG, IATA**

· **Class** 8 Corrosive substances.

· **Label** 8

(Contd. on page 11)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 10)

· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Segregation groups · Stowage Category · Segregation Code	Warning: Corrosive substances. 80 F-A, S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE, ISOPHORONEDIAMINE), 8, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** No further relevant information available.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 12)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 11)

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

19.10.2021

· **Version number of previous version:**

30

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.07.2025

Version number 31 (replaces version 30)

Revision: 12.07.2025

Trade name Konudur 170 TR-NA - Komponente B

(Contd. of page 12)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the
previous version altered.**

IE