

Page 1/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 33 (replaces version 32) Revision: 11.04.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name Konudur 250 OM-PL Sommerharz - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Synthetic resin Polyurethane

• 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

msds@mc-bauchemie.de

1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

· 2.2 Label elements

· Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

GHS05

· Signal word Danger

· Hazard-determining

components of labelling:
Silicic acid, sodium salt
Hazard statements
H315 Causes skin irritation.

H318 Causes serious eye damage.

(Contd. on page 2)



Page 2/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 11.04.2025 Printing date 11.04.2025 Version number 33 (replaces version 32)

#### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 1) P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

Take off contaminated clothing and wash it

P362+P364 before reuse.

If skin irritation occurs: Get medical advice/

attention.

· 2.3 Other hazards

· Precautionary statements

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture consisting of the following components.

P332+P313

· Dangerous components:		
CAS: 1344-09-8	Silicic acid, sodium salt	30-60%
	Eye Dam. 1, H318; Skin Irrit. 2, H315	
CAS: 107-21-1	Ethanediol	<10%
EINECS: 203-473-3	STOT RE 2, H373; Acute Tox. 4, H302	
Reg.nr.: 01-2119456816-28	·	

· Additional information For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

· General information Remove, decontaminate and dispose of soiled, soaked clothing

and shoes immediately.

Remove person to fresh air, keep warm, allow to rest; if breathing · After inhalation

is difficult, seek medical attention.

· After skin contact In case of contact with skin, preferably wash with polyethylene

glycol-based cleaner or clean with plenty of warm water and soap.

Consult a doctor in case of skin reactions.

· After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at

least 10 minutes) with water that is as lukewarm as possible.

Consult an ophthalmologist.

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

· 4.2 Most important symptoms and effects, both acute and

delayed Information for the doctor: The product irritates the respiratory tract

and is a potential trigger for skin and respiratory sensitisation.

(Contd. on page 3)



Page 3/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 11.04.2025 Printing date 11.04.2025 Version number 33 (replaces version 32)

#### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 2)

Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.

· 4.3 Indication of any immediate medical attention and special treatment needed No information available.

# SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· 5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment:

No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures

Not required.

· 6.2 Environmental precautions:

· 6.3 Methods and material for

Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Ensure adequate ventilation.

Dilute with much water.

containment and cleaning up: Dispose of the material collected according to regulations.

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas.

Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being

exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. (Contd. on page 4)



Page 4/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 33 (replaces version 32) Revision: 11.04.2025

#### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 3)

The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing

immediately.

· Information about protection

against explosions and fires: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any

incompatibilities Keep container dry and tightly closed. Further information on the

storage conditions that must be observed for quality assurance

reasons can be found in our technical data sheet.

· Storage

· Requirements to be met by

**storerooms and containers:** Store only in the original container.

· Further information about

storage conditions: None.
Storage class 10

• 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

<ul> <li>Components with critical values that require monitoring at the workplace</li> </ul>	· Components with	critical values	that require	monitoring	at the work	place:
--	-------------------	-----------------	--------------	------------	-------------	--------

#### CAS: 107-21-1 Ethanediol

OEL (Ireland) Short-term value: 104 mg/m³, 40 ppm

Long-term value: 52 mg/m³, 20 ppm

Skin, IOELV

IOELV (European Union) Short-term value: 104 mg/m³, 40 ppm

Long-term value: 52 mg/m³, 20 ppm

Skin

#### · DNELs

## CAS: 1344-09-8 Silicic acid, sodium salt

Oral DNEL 0.8 mg/kg bw/Tag (ArL)
Dermal DNEL 1.59 mg/kg bw/day (ArL)
Inhalative DNEL 5.61 mg/m³ (ArL)

#### CAS: 107-21-1 Ethanediol

Dermal DNEL 106 mg/kg bw/day (ArL)
Inhalative DNEL 35 mg/m³ (ArL)

(Contd. on page 5)



Page 5/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 33 (replaces version 32) Revision: 11.04.2025

### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 4)

· PNECs

CAS: 1344-09-8 Silicic acid, sodium salt

PNEC 348 mg/l (Kla)

1 mg/l (Mew)

7.5 mg/l (Freshwater)

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash bands before breaks and at the end of we

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

· Breathing equipment: Respiratory protection required at insufficiently ventilated

workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-

term work.

If applicable, further recommendations for respiratory protection

can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic

bronchitis), handling of the product is not recommended.

Hand protection Suitable materials for protective gloves; EN 374:

Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).

Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC

definition): butyl rubber.

In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes

according to EN374).

The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multilayer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide sufficient protection for short periods of wear.

For solvent-free products:

Example:

Polychloroprene - CR: thickness  $\geq 0.5$ mm; breakthrough time

*≥*480min.

(Contd. on page 6)



Page 6/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 33 (replaces version 32) Revision: 11.04.2025

### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 5)

Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time

>480min.

Butyl rubber - IIR: thickness  $\geq$ 0.5mm; breakthrough time  $\geq$ 480min. Fluoro rubber - FKM: thickness  $\geq$ 0.4mm; breakthrough time

≥480min

Recommendation: Dispose of contaminated gloves.

• Material of gloves Polychloroprene - CR

Nitrile rubber - NBR Butyl rubber - IIR Fluoro rubber - FKM

Penetration time of glove

material

Polychloroprene - CR: thickness ≥0.5mm; breakthrough time

×480min.

Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time

≥480min.

Butyl rubber - IIR: thickness  $\ge$ 0.5mm; breakthrough time  $\ge$ 480min. Fluoro rubber - FKM: Thickness  $\ge$ 0.4mm; Breakthrough time

*≥*480min.

· Eye/face protection

· Body protection:

Safety goggles with side protection in accordance with EN 166.

Use chemical-resistant protective clothing.

In case of hypersensitivity of the skin, handling the product is not

recommended.

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Whitish

Smell: Weak, characteristicMelting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range 100 °C (CAS: 7732-18-5 Water)

· Flash point: 111 °C

· **pH** Not determined.

· Viscosity:

Kinematic viscositydynamic:Not determined.Not determined.

Solubility

• Water: Fully miscible

• Steam pressure at 20 °C: 23 hPa (CAS: 7732-18-5 Water)

· Density and/or relative density

Density at 20 °C 1.5 g/cm<sup>3</sup>

· 9.2 Other information

· Appearance:

· Form: Fluid

(Contd. on page 7)



Page 7/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 33 (replaces version 32) Revision: 11.04.2025

#### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 6)

Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes · Explosives Void Flammable gases Void Void · Aerosols Void · Oxidising gases · Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

Self-heating substances and mixtures
Substances and mixtures, which emit
flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

# SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

**conditions to be avoided:** No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

## **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)



Page 8/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 33 (replaces version 32) Revision: 11.04.2025 Printing date 11.04.2025

#### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 7)

· LD/LC5	· LD/LC50 values that are relevant for classification:		
CAS: 1344-09-8 Silicic acid, sodium salt			
Oral	LD50	3400 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rat)	
CAS: 10	CAS: 107-21-1 Ethanediol		
Oral	LD50	4000 mg/kg (rat)	
	LDL0	1600 mg/kg (Workers)	
Dermal	LD50	>3500 mg/kg (mouse)	
		10600 mg/kg (rabbit)	

· Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin

sensitisation Based on available data, the classification criteria are not met. · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

### · 12.1 Toxicity

		icity:

# CAS: 1344-09-8 Silicic acid, sodium salt

EC50/72h >345.4 mg/l (Desmodesmus subspicatus)

LC50/96h 1108 mg/l (Danio rerio)

260 mg/l (Oncorhynchus mykiss)

>100 mg/l (fish)

EC50 >100 mg/l (Bak)

> >100 mg/l (algae) >100 mg/l (Daphnien)

>100 mg/l (Daphnia magna)

EC50/48h | 1700 mg/l (Daphnia magna)

#### CAS: 107-21-1 Ethanediol

LC50/96h | 72860 mg/l (Pimephales promelas)

EC50/48h >100 mg/l (Daphnia magna)

(Contd. on page 9)



Page 9/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 33 (replaces version 32) Revision: 11.04.2025

#### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 8)

EC50/96h | 6500-13000 mg/l (Selenastrum capricornutum)

NOEC 8590 mg/l (Ceriodaphnia dubia) 15380 mg/l (Pimephales promelas)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

## **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· European waste catalogue		
06 00 00	WASTES FROM INORGANIC CHEMICAL PROCESSES	
06 02 00	wastes from the MFSU of bases	
06 02 99	wastes not otherwise specified	
HP4	Irritant - skin irritation and eye damage	

· Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

# SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

(Contd. on page 10)



Page 10/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 33 (replaces version 32) Revision: 11.04.2025

#### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 9)

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· **ADR, IMDG, IATA** Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to

**IMO instruments** Not applicable.

· UN "Model Regulation": Void

# **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/ legislation specific for the

**substance or mixture** No further relevant information available.

· REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)



Page 11/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 33 (replaces version 32) Revision: 11.04.2025

#### Trade name Konudur 250 OM-PL Sommerharz - Komponente A

(Contd. of page 10)

· Relevant phrases H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H373 May cause damage to organs through prolonged or repeated

exposure.

· Department issuing data

**specification sheet:** Environment protection department.

· Date of previous version: 13.10.2021

· Version number of previous

version:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par

route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

\* Data compared to the previous version altered.

ΙE