



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet **according to Regulation (EC) No 1907/2006, Article 31**

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· **Trade name** MC-CarboSolid 1000 - Komponente A

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Epoxy sealing

1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· **Informing department:**

msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1A H360F May damage fertility.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS07 GHS08

· **Signal word**

Danger

(Contd. on page 2)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 1)

- **Hazard-determining components of labelling:** Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane
Oxirane, mono((C12-14-alkyloxy)methyl)derivatives
4,4'-Methylenediphenyldiglycidyl ether
1,6-bis(2,3-epoxypropoxy)hexane
- **Hazard statements** H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H360F May damage fertility.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P405 Store locked up.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%
CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥2.5-<10%
CAS: 68609-97-2 EINECS: 271-846-8	Oxirane, mono((C12-14-alkyloxy)methyl)derivatives Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<2.5%
CAS: 933999-84-9	1,6-bis(2,3-epoxypropoxy)hexane Repr. 1A, H360F; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<1.5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/11

Safety data sheet **according to Regulation (EC) No 1907/2006, Article 31**

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Collect mechanically.
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for information on disposal.

IE

(Contd. on page 4)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BgBau technical data sheet and practical guide for handling epoxy resins.

· Information about protection against explosions and fires:

Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by storerooms and containers:

No special requirements.

· Further information about storage conditions:

None.

· Storage class

6.1C

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

Dermal DNEL 0.75 mg/kg bw/day (ArL)

Inhalative DNEL 0.49 mg/m³ (ArL)

· PNECs

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

PNEC 0.00072 mg/l (Mew)

0.0072 mg/l (Freshwater)

PNEC 80.12 mg/kg dwt (Bod)

6.677 mg/kg dwt (Sediment)

66.77 mg/kg dwt (Fresh water sediment)

(Contd. on page 5)



BE SURE. BUILD SURE.

Page 5/11

Safety data sheet **according to Regulation (EC) No 1907/2006, Article 31**

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 4)

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.
- **Breathing equipment:** If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.
- **Hand protection** Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves** You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material".
The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.
Nitrile rubber
Recommended material thickness: ≥ 0.4 mm
- **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.
The following applies to all other gloves:
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.
Nitrile rubber
Material thickness: ≥ 0.40 mm
Penetration time: ≥ 480 min
Butyl rubber:
Material thickness: ≥ 0.5 mm
Penetration time: ≥ 480 min
- **Eye/face protection** Tight-fitting safety goggles.
Safety goggles.
- **Body protection:** Protective clothing
Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons,

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 5)

overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:	Grey
· Smell:	Characteristic
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	2230 °C (CAS: 14808-60-7 Quartz sand)
· Flash point:	151 °C
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity at 20 °C	5000 s (ISO 6 mm)
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 1732 °C:	13.5 hPa (CAS: 14808-60-7 Quartz sand)
· Density and/or relative density	
· Density	Not determined

· 9.2 Other information

· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 6)

· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

Oral	LD50	11400 mg/kg (rat)
Dermal	LD50	23000 mg/kg (rabbit)
		>2000 mg/kg (rat)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

Oral	LD50	17100 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility.

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 7)

- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane

LC50/96h >100 mg/l (Daphnia magna)

EC50/96h >100 mg/l (Leucidus idus)

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

LC50/72h >11 mg/l (algae)

IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (Oncorhynchus mykiss)

1.3 mg/l (fish)

EC50/48h 2.1 mg/l (daphnia)

1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

EbC50/72h 843 mg/l (Pseudokirchneriella subcapitata)

LC50/96h >5000 mg/l (Oncorhynchus mykiss)

1800 mg/l (Lepomis macrochirus)

EC50 >100 mg/l (BEL)

NOEC 500 mg/l (Pseudokirchneriella subcapitata)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 9)



BE SURE. BUILD SURE.

Page 9/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 8)

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
HP10	Toxic for reproduction
HP14	Ecotoxic

· Uncleaned packagings:

· Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA

Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA

Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class

Void

· 14.4 Packing group

· ADR, IMDG, IATA

Void

· 14.5 Environmental hazards:

· Marine pollutant:

No

· 14.6 Special precautions for user

Not applicable.

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

(Contd. on page 10)

IE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 9)

· **UN "Model Regulation":** Void

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**

No further relevant information available.

· **REGULATION (EC) No 1907/2006 ANNEX XVII**

Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360F May damage fertility.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

19.10.2021

· **Version number of previous version:**

42

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 30.08.2025

Version number 43 (replaces version 42)

Revision: 30.08.2025

Trade name MC-CarboSolid 1000 - Komponente A

(Contd. of page 10)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 1A: Reproductive toxicity – Category 1A

Repr. 1B: Reproductive toxicity – Category 1B

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the
previous version altered.

IE