

Page 1/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name MC-CarboSolid 1000 BC - Komponente A

462 · Article number:

· 1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Layer to promote adhesion

Epoxy resin

· 1.3 Details of the supplier of the safety data sheet

MC-Bauchemie Müller GmbH & Co. KG Manufacturer/Supplier:

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

· 1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360F May damage fertility.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure.

Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP

regulation.

(Contd. on page 2)



Page 2/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

· Hazard pictograms

(Contd. of page 1)

· Signal word Danger

· Hazard-determining

components of labelling: 4,4'-Methylenediphenyldiglycidyl ether

Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

Quartz sand

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}

methyl)oxirane

· Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H360F May damage fertility.

H372 Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements P260 Do not breathe dust/fume/gas/mist/vapours/

spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/

spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

EUH211 Warning! Hazardous respirable droplets may be formed

when sprayed. Do not breathe spray or mist.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

(Contd. on page 3)



Page 3/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

(Co	ontd. of page 2
nents:	
4,4'-Methylenediphenyldiglycidyl ether	30-60%
Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
Quartz sand	10-30%
STOT RE 1, H372	
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<25%
Oxirane, mono((C12-14-alkyloxy)methyl)derivatives	≥1-<10%
Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	
Titanium dioxide	≥1-<5%
Carc. 2, H351	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	≥1-<1.5%
	A,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Quartz sand STOT RE 1, H372 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317 Titanium dioxide Carc. 2, H351 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

• After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or

mixture No further relevant information available.

(Contd. on page 4)



Page 4/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: No special measures required.

· 6.3 Methods and material for

containment and cleaning up: Collect mechanically.

Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy

resins.

Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: None.

(Contd. on page 5)



Page 5/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 12.04.2025 Printing date 12.04.2025 Version number 53 (replaces version 52)

Trade name MC-CarboSolid 1000 BC - Komponente A

(Contd. of page 4)

· Storage class

6.1C

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 14808-60-7 Quartz sand

OEL (Ireland) Long-term value: 0.1 mg/m3

BOELV (European Union) Long-term value: 0.1* mg/m3

*respirable fraction

DNELs

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

DNEL 0.75 mg/kg bw/day (ArL)

Inhalative DNEL 0.49 mg/m³ (ArL)

PNECs

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

PNEC 0.00072 mg/l (Mew)

0.0072 mg/l (Freshwater)

PNEC 80.12 mg/kg dwt (Bod)

6.677 mg/kg dwt (Sediment)

66.77 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed. Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

If workplace limit values cannot be complied with by ventilation · Breathing equipment:

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/ white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

Selection of the glove material on consideration of the penetration · Hand protection

times, rates of diffusion and the degradation

· Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material".

(Contd. on page 6)



Page 6/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

(Contd. of page 5)

The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

Safe

Safety goggles.
Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Eye/face protection

· Body protection:

· Colour: According to product specification

Smell: CharacteristicMelting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range >140 °C
• Flash point: >100 °C
• Auto-ignition temperature: 184 °C

· **pH** Not determined.

· Viscosity:

· Kinematic viscosity
· dynamic:

Not determined.

Not determined.

(Contd. on page 7)



Page 7/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

(Contd. of page 6)

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0.1 hPa

Density and/or relative density

· Density at 20 °C 2.19 g/cm³

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

Information with regard to physical hazard

classes

Void · Explosives Void · Flammable gases · Aerosols Void · Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void

Pyrophoric solids
Self-heating substances and mixtures

Substances and mixtures, which emit flammable gases in contact with water Void
Oxidising liquids Void

Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

Void

 Void
 Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

Void

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

(Contd. on page 8)



Page 8/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

(Contd. of page 7)

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

	· LD/LC50 values that are relevant for classification: CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether		
	Oral	LD50	11400 mg/kg (rat)
	Dermal	LD50	23000 mg/kg (rabbit)
			>2000 mg/kg (rat)
	040 000		

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane

	Oral	LD50	>2000 mg/kg (rat)
	Dermal	LD50	>2000 mg/kg (rabbit)
	CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives		
	Oral	LD50	17100 mg/kg (rat)
	CAS: 13463-67-7 Titanium dioxide		
	Oral	LD50	>5000 mg/kg (rat)
	Dermal	LD50	>10000 mg/kg (rabbit)
	Inhalative	LC50/4 h	>6.8 mg/l (rat)
CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane			

Oral	LD50	8030 mg/kg (rat)
Dermal	LD50	4248 mg/kg (rabbit)

Primary irritant effect:

Skin corrosion/irritation Causes skin irritation.
 Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

• Germ cell mutagenicity
• Carcinogenicity

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Reproductive toxicity May damage fertility.

• STOT-single exposure
• STOT-repeated exposure

Based on available data, the classification criteria are not met.

Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)



Page 9/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

(Contd. of page 8)

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

· 12.1 Toxicity

Λα	uatic	to	vic	itur.
Ay	uauc	(U)	(/C	ıιy.

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

LC50/72h >11 mg/l (algae) IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (Oncorhynchus mykiss)

1.3 mg/l (fish)

EC50/48h | 2.1 mg/l (daphnia)

1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]
bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]
bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)
oxirane

LC50/96h >100 mg/l (Daphnia magna) EC50/96h >100 mg/l (Leucidus idus)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

EbC50/72h 843 mg/l (Pseudokirchneriella subcapitata)

LC50/96h >5000 mg/l (Oncorhynchus mykiss)

1800 mg/l (Lepomis macrochirus)

EC50 >100 mg/l (BEL)

NOEC 500 mg/l (Pseudokirchneriella subcapitata)

CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

LC50/96h | 55 mg/l (Cyp)

EC50/48h 473 mg/l (Daphnia magna)

ErC50/72h | 255 mg/l (Scenedesmus subspicatus)

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

(Contd. on page 10)



Page 10/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 12.04.2025 Printing date 12.04.2025 Version number 53 (replaces version 52)

Trade name MC-CarboSolid 1000 BC - Komponente A

(Contd. of page 9)

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

European waste catalogue 08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products) 08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances HP4 Irritant - skin irritation and eye damage HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

· Uncleaned packagings:

Sensitising

Ecotoxic

HP13

HP14

Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR, IATA	ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (Epoxide resin)
IMDG	ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (Epoxide resin
	MARINE POLLUTANT
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances an
	articlés.
Label	9

(Contd. on page 11)



Page 11/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

	(Contd. of page
· IMDG, IATA · Class	9 Miscellaneous dangerous substances an articles.
· Label	9
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR): · Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances ar articles.
· Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
· 14.7 Maritime transport in bulk accordi IMO instruments	ing to Not applicable.
Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN 9, III

- IE



Page 12/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

(Contd. of page 11)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.

H360F May damage fertility.

H372 Causes damage to organs through prolonged or repeated

exposure.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing data

specification sheet: Environment protection department.

(Contd. on page 13)



Page 13/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 53 (replaces version 52) Revision: 12.04.2025

Trade name MC-CarboSolid 1000 BC - Komponente A

(Contd. of page 12)

· Date of previous version: 13.10.2021

· Version number of previous

version:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity - Category 2 Repr. 1B: Reproductive toxicity - Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

* * Data compared to the previous version altered.