

Page 1/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.12.2024 Version number 30 (replaces version 29) Revision: 09.12.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name MC-CarboSolid 1209 TX - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Epoxy coating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

#### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS07 GHS09

· Signal word Warning

(Contd. on page 2)





# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 30 (replaces version 29) Revision: 09.12.2024 Printing date 09.12.2024

#### Trade name MC-CarboSolid 1209 TX - Komponente A

(Contd. of page 1)

Hazard-determining

components of labelling: epoxide derivates

> Reaction mass of 2.2'-[methylenebis(4.1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane

(1:2)

· Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Avoid breathing dust/fume/gas/mist/vapours/ · Precautionary statements P261

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/ P332+P313

attention.

P333+P313 If skin irritation or rash occurs: Get medical

advice/attention.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture consisting of the following components.

CAS: 1675-54-3	epoxide derivates	30-60%
EINECS: 216-823-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	
CAS: 9003-36-5 EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	≥10-<259
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	



Page 3/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.12.2024 Version number 30 (replaces version 29) Revision: 09.12.2024

#### Trade name MC-CarboSolid 1209 TX - Komponente A

(Contd. of page 2)

CAS: 933999-84-9

Reaction products of hexane-1,6-diol with 2-(chloromethyl) ≥2.5-<10% oxirane (1:2)

Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;
Aquatic Chronic 3, H412

Additional information For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

• After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

• After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

### SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures \( \)

Not required.

6.2 Environmental

precautions:

Inform respective authorities in case product reaches water or

sewage system.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

(Contd. on page 4)



Page 4/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 09.12.2024 Printing date 09.12.2024 Version number 30 (replaces version 29)

Ensure adequate ventilation.

Trade name MC-CarboSolid 1209 TX - Komponente A

(Contd. of page 3)

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe

handling

Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy

resins.

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

·Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: None. · Storage class 10

#### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering

controls No further data; see section 7.

(Contd. on page 5)



Page 5/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 09.12.2024 Printing date 09.12.2024 Version number 30 (replaces version 29)

Trade name MC-CarboSolid 1209 TX - Komponente A

(Contd. of page 4)

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/ white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

· Hand protection Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

· Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

· Eye/face protection

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

Safety goggles. · Body protection: Protective clothing

> Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.



Page 6/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.12.2024 Version number 30 (replaces version 29) Revision: 09.12.2024

Trade name MC-CarboSolid 1209 TX - Komponente A

(Contd. of page 5)

#### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: White

Smell: CharacteristicMelting point/freezing point: Not determined

· Boiling point or initial boiling point and

>200 °C (CAS: 1675-54-3 bis[4-(2,3-

epoxypropoxy)phenyl]propane)

· Flash point: 151 °C

• Auto-ignition temperature: 460 °C (CAS: 9003-36-5 2,2'-[methylenebis(p-

phenyleneoxymethylene)]bisoxirane polymers

and homologues, molecular weight < 700)

Not determined.

Viscosity:

· pH

Kinematic viscositydynamic:Not determined.Not determined.

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure: Not determined.

· Density and/or relative density

· **Density** Not determined

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

Information with regard to physical hazard

classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit

flammable gases in contact with water Void
Oxidising liquids Void

· Oxidising solids Void

(Contd. on page 7)



Page 7/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.12.2024 Version number 30 (replaces version 29) Revision: 09.12.2024

#### Trade name MC-CarboSolid 1209 TX - Komponente A

(Contd. of page 6)

· Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

#### SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

**conditions to be avoided:** No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

#### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

CAS: 1675-54-3 epoxide derivates

Dermal | LD50 | 23000 mg/kg (rabbit)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rabbit)

Primary irritant effect:

Skin corrosion/irritation
 Serious eye damage/irritation
 Causes skin irritation.
 Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

(Contd. on page 8)



Page 8/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.12.2024 Version number 30 (replaces version 29) Revision: 09.12.2024

#### Trade name MC-CarboSolid 1209 TX - Komponente A

(Contd. of page 7)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 1675-54-3 epoxide derivates

IC50 >42.6 mg/l (Bak)

LC50/96h | 2 mg/l (Oncorhynchus mykiss) EC50/48h | 1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-

[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

LC50/96h >100 mg/l (Daphnia magna) EC50/96h >100 mg/l (Leucidus idus)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Remark: Toxic for fish

· Additional ecological information:

· General notes: Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

# SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

(Contd. on page 9)





# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.12.2024 Version number 30 (replaces version 29) Revision: 09.12.2024

### Trade name MC-CarboSolid 1209 TX - Komponente A

	(Contd. of page 8)		
· European	· European waste catalogue		
17 00 00	CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)		
17 09 00	other construction and demolition wastes		
17 09 03*	other construction and demolition wastes (including mixed wastes) containing hazardous substances		
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED		
15 01 00	packaging (including separately collected municipal packaging waste)		
15 01 01	paper and cardboard packaging		
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED		
15 01 00	packaging (including separately collected municipal packaging waste)		
15 01 02	plastic packaging		
HP4	Irritant - skin irritation and eye damage		
HP13	Sensitising		
HP14	Ecotoxic		

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR, IATA	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)
IMDG	ENVIRONMENTALLY `HAZARDOÚ, SUBSTANCE, LIQUID, N.O.S. (epoxide derivates, MARINE POLLUTANT
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances an articles.
Label	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances an articles.
Label	9





# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.12.2024 Version number 30 (replaces version 29) Revision: 09.12.2024

#### Trade name MC-CarboSolid 1209 TX - Komponente A

	(Contd. of page
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accordi IMO instruments	<b>ng to</b> Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
Transport category Tunnel restriction code	3 (-)
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDI DERIVATES), 9, III

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

(Contd. on page 11)



Page 11/12

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 09.12.2024 Printing date 09.12.2024 Version number 30 (replaces version 29)

#### Trade name MC-CarboSolid 1209 TX - Komponente A

(Contd. of page 10)

· Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H315 Causes skin irritation.

> H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Toxic to aquatic life with long lasting effects. H411 H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· Department issuing data

specification sheet: Environment protection department.

· Date of previous version: 19.10.2021

· Version number of previous

version:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 12)



Page 12/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.12.2024 Version number 30 (replaces version 29) Revision: 09.12.2024

#### Trade name MC-CarboSolid 1209 TX - Komponente A

(Contd. of page 11)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 3

\* Data compared to the previous version altered.

- IE