

Page 1/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

undertaking	
· 1.1 Product identifier	
· Trade name	MC-Color Flair vision - Komponente B
 Article number: 1.2 Relevant identified uses of the substance or mixture 	3911
and uses advised against • Application of the substance	No further relevant information available.
/ the mixture	Coating compound/ Surface coating/ paint Hardening agent/ Curing agent
· 1.3 Details of the supplier of	the safety data sheet
Manufacturer/Supplier:	MC-Bauchemie Müller GmbH & Co. KG
	Am Kruppwald 1-8
	D-46238 Bottrop Tel.: +49(0)2041-101-0
	Fax.: +49(0)2041-101-400
	E-Mail: info@mc-bauchemie.de
	MC-Bauchemie AG
	Hagackerstr. 10
	CH-8953 Dietikon
	Tel.: +44-7400510 Fax : +44-7400533
· Informing department:	msds@mc-bauchemie.de
1.4 Emergency telephone number:	Tel.: +49 / (0)700 24112112 (MCR)
number.	Tel.: +1 872 5888271 (MCR)
SECTION 2: Hazards ide	entification
 2.1 Classification of the subs Classification according to F 	
-	ful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.	
Skin Sens. 1 H317 May cause an allergic skin reaction.	
STOT SE 3 H335 May cause respiratory irritation.	
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.	
:	
· 2.2 Label elements	
• Labelling according to	10 The product is allocation and labelled according to the CL
Regulation (EC) No 12/2/200	18 The product is classified and labelled according to the CLF regulation.

· Hazard pictograms





Page 2/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 1)
Warning
Hydrophiles, aliphatisches Polyisocyanat
Hexamethylen-1,6-diisocyanat Homopolymer
hexamethylene diisocyanate
H332 Harmful if inhaled.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
EUH204 Contains isocyanates. May produce an allergic reaction.
sessment
Not applicable.
Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description:	Mixture consisting of the following components.	
· Dangerous components:		
CAS: 160994-68-3	Hydrophiles, aliphatisches Polyisocyanat Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204	50-70%
CAS: 3779-63-3 EINECS: 223-242-0	Hexamethylen-1,6-diisocyanat Homopolymer Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	<i>≥</i> 1-<5%
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37- 0000	hexamethylene diisocyanate Acute Tox. 2, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C \geq 0.5 % Skin Sens. 1; H317: C \geq 0.5 %	<0.1%
Additional information	For the wording of the listed hazard phrases refer to section	on 16.

(Contd. on page 3)



Page 3/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 2)

SECTION 4: First aid measures

General information	Remove soiled, soaked clothing immediately.
After inhalation	Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
After skin contact	In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
After eye contact	Rinse the eyes with open eyelids for a sufficiently long time (a least 10 minutes) with water that is as lukewarm as possible Consult an ophthalmologist.
After swallowing	Do NOT induce vomiting. Rinse mouth with water. Medica attention required.
4.2 Most important sympa and effects, both acute and	
delayed	Advice for the doctor: Elementary aid, decontamination

symptomatic treatment. • **4.3 Indication of any** immediate medical attention and special treatment needed Therapeutic measures: No information available.

SECTION 5: Firefighting measures

 5.1 Extinguishing media Suitable extinguishing agent 	s CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
 5.2 Special hazards arising from the substance or 	
mixture	No further relevant information available.
 5.3 Advice for firefighters Protective equipment: 	No special measures required.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and 	
emergency procedures 6.2 Environmental	Not required.
precautions:	Inform respective authorities in case product reaches water or sewage system.
[.] 6.3 Methods and material for	
containment and cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
· 6.4 Reference to other	
sections	See Section 7 for information on safe handling
	See Section 8 for information on personal protection equipment. (Contd. on page 4)



Page 4/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

Trade name MC-Color Flair vision - Komponente B

See Section 13 for information on disposal.

(Contd. of page 3)

SECTION 7: Handling and storage

• 7.1 Precautions for safe	
handling	Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application. For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored. At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people. For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours. Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.
 Information about protection against explosions and fires: 	Keep ignition sources away - do not smoke. Protect from heat. Do not store near heat sources.
 7.2 Conditions for safe storage, including any incompatibilities Storage Requirements to be met by storerooms and containers: 	Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet. Keep tightly closed in original packaging. Ventilate storage rooms
	well. Carefully close opened containers and store upright to prevent any leakage.
· Information about storage in	Storage temperature >5°C and <30°C
• Further information about	May be stored together with hazardous substances of other classes up to 200 kg.
 Storage conditions: Storage class 7.3 Specific end use(s) 	Keep container tightly closed in a well-ventilated place. 10 No further relevant information available.

(Contd. on page 5)



Page 5/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 4)

IF

equipment ready. Do not inhale gases/vapours/aerosols. Avoid contact with eyes skin. Do not store food in the work area. Wash hands before breaks at the end of work.Breathing equipment:Respiratory protection required at insufficiently ventila workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for st term work. If applicable, further recommendations for respiratory protec can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.	SECT	ION 8: Exposure	e controls/personal protection
Components with critical values that require monitoring at the workplace: CAS: 822-06-0 hexamethylene diisocyanate OEL (Ireland) Long-term value: 0.005 ppm as -NCO, Sens DNELs CAS: 822-06-0 hexamethylene diisocyanate Inhalative DNEL 0.5 mg/m³ (ArL) PNECs CAS: 822-06-0 hexamethylene diisocyanate PNEC 100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater) PNEC 8 884 mg/kg dwt (Bod) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as bases 8.2 Exposure controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and Do not smoke, eat or drink while working. Have eye w equipment: Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fresh air mask contor in the end of work. Breathing equipment: Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fres	· 8.1 Co	ntrol parameters	
OEL (Ireland) Long-term value: 0.005 ppm as -NCO, Sens DNELs CAS: 822-06-0 hexamethylene diisocyanate Inhalative DNEL Inhalative DNEL OPNEC CAS: 822-06-0 hexamethylene diisocyanate PNEC 100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater) PNEC 8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures Do not smoke, eat or drink while working. Have eye w equipment ready. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventilit workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (ENS29) are recommended for si term work. Hand protection Hand protection Attibule materials for protective gloves; EN 374: Butyl rubber - I/R: thickness $\geq 0.5mm; break$	Сотро	onents with critical	values that require monitoring at the workplace:
as -ÑCO, Sens DNELs CAS: 822-06-0 hexamethylene diisocyanate Inhalative DNEL 0.5 mg/m³ (ArL) PNECS CAS: 822-06-0 hexamethylene diisocyanate PNECS CAS: 822-06-0 hexamethylene diisocyanate PNEC 100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Kreshwater) PNEC 8884 mg/kg dwt (Bod) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as be 8.2 Exposure controls No further data; see section 7. Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures bo not smoke, eat or drink while working. Have eye w equipment ready. Do not smoke, eat or drink while working. Have eye w explaiment: Breathing equipment: Do not store food in the work area. Wash hands before breaks at the end of work. Breationy protection required at insufficiently ventilat workiplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for st term work. H	CAS: 8	22-06-0 hexamethy	lene diisocyanate
DNELs CAS: 822-06-0 hexamethylene diisocyanate Inhalative DNEL DNECs CAS: 822-06-0 hexamethylene diisocyanate PNEC 100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater) PNEC 8884 mg/kg dwt (Bod) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as base 8.2 Exposure controls Appropriate engineering controls Individual protection measures, such as personal protective equipment General protective and hygienic measures Do not smoke, eat or drink while working. Have eye w equipment ready. Do not stroke food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventila workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for sl term work. H applicable, further recommendations for respiratory protect can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chrhr bronchitis),	OEL (Ir		
CAS: 822-06-0 hexamethylene diisocyanate Inhalative DNEL 0.5 mg/m³ (ArL) PNECS CAS: 822-06-0 hexamethylene diisocyanate PNEC 100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater) PNEC 8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Bod) 4455 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as back as the engineering controls Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures Do not smoke, eat or drink while working. Have eye wequipment ready. Do not store food in the work area. Wash hands before breaks at the end of work. Respiratory protection required at insufficiently ventilit workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (ENS29) are recommended for si term work. Hand protection Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.4mm; breakthrough time ≥480min. Fluoronubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480min. Recommendation: Dispose of contaminated gloves.		as -NCO, Se	ns
Inhalative DNEL 0.5 mg/m³ (ArL) PNECs CAS: 822-06-0 hexamethylene diisocyanate PNEC 100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.0199 mg/l (Freshwater) 0.199 mg/l (Freshwater) PNEC 884 mg/kg dwt (Bod) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as base 8.2 Exposure controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and Do not smoke, eat or drink while working. Have eye w hygienic measures Do not smoke, eat or drink while working. Have eye w equipment ready. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventilit workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (ENS29) are recommended for si term work. Hand protection Suitable materials for protective gloves; EN 374: Hand protection Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. A80 min. Hand protect			
PNECs CAS: 822-06-0 hexamethylene diisocyanate PNEC 100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater) 8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as be 8.2 Exposure controls Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures Do not smoke, eat or drink while working. Have eye w equipment ready. Do not inhale gases/vapours/aerosols. Avoid contact with eyes skin. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for st term work. I			-
CAS: 822-06-0 hexamethylene diisocyanate PNEC 100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater) PNEC 8884 mg/kg dwt (Bod) 44555 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as bases 8.2 Exposure controls Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures Do not smoke, eat or drink while working. Have eye w equipment ready. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventila workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for st term work. If applicable, further recommendations for respiratory protect can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. <td>Inhalati</td> <td>ive DNEL 0.5 mg/m</td> <td>³ (ArL)</td>	Inhalati	ive DNEL 0.5 mg/m	³ (ArL)
PNEC 100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater) PNEC 8884 mg/kg dwt (Bod) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as base as the sequence of the	PNECs	;	
0.0199 mg/l (Mew) 0.199 mg/l (Freshwater) PNEC 8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as bases 8.2 Exposure controls Appropriate engineering controls Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and bo not smoke, eat or drink while working. Have eye we equipment ready. Do not store food in the work area. Wash hands before breaks at the end of work. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for si term work. Hand protection Suitable materials for protective gloves; EN 374: Buty inbber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Auditi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Auditi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min.		-	•
0.199 mg/l (Freshwater) PNEC 8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as bases 8.2 Exposure controls Appropriate engineering Appropriate engineering No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures Do not smoke, eat or drink while working. Have eye wequipment ready. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for siterr work. Hand protection Suitable materials for protective gloves; EN 374: Hand protection Suitable materials for protective gloves; EN 374: Butj! rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.	PNEC	100 mg/l (Sewage T	reatment Plant)
PNEC 8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as bases 8.2 Exposure controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and Do not smoke, eat or drink while working. Have eye wequipment ready. Do not inhale gases/vapours/aerosols. Avoid contact with eyes skin. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for st term work. Hand protection Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.		,	
4455 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as bases 8.2 Exposure controls Appropriate engineering controls Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures Do not smoke, eat or drink while working. Have eye we equipment ready. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventilat workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for st term work. Hand protection Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.4mm; breakthrough time ≥480 min. Autil-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.		•	,
44551 mg/kg dwt (Fresh water sediment) Additional information: The lists that were valid during the compilation were used as backers. 8.2 Exposure controls Appropriate engineering controls Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures Do not smoke, eat or drink while working. Have eye we equipment ready. Do not inhale gases/vapours/aerosols. Avoid contact with eyes skin. Breathing equipment: Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for st term work. Hand protection Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.	PNEC		
Additional information: The lists that were valid during the compilation were used as back appropriate engineering controls 8.2 Exposure controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures bygienic measures Do not smoke, eat or drink while working. Have eye we equipment ready. Do not inhale gases/vapours/aerosols. Avoid contact with eyes skin. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for sl term work. Hand protection If applicable, further recommendations for respiratory protection be found in the appendix. Hand protection Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. ≥480 min. Addition: Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min.			
 8.2 Exposure controls Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures Do not smoke, eat or drink while working. Have eye w <pre>equipment ready.</pre> Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventila <pre>workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for sf term work. Hand protection Hand protection Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.</pre>			· · · · · · · · · · · · · · · · · · ·
hygienic measuresDo not smoke, eat or drink while working. Have eye wequipment ready. Do not inhale gases/vapours/aerosols. Avoid contact with eyes skin. Do not store food in the work area. Wash hands before breaks at the end of work.Breathing equipment:Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for sh term work. If applicable, further recommendations for respiratory protect can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			sures, such as personal protective equipment
hygienic measuresDo not smoke, eat or drink while working. Have eye wequipment ready. Do not inhale gases/vapours/aerosols. Avoid contact with eyes skin. Do not store food in the work area. Wash hands before breaks at the end of work.Breathing equipment:Respiratory protection required at insufficiently ventile workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for sh term work. If applicable, further recommendations for respiratory protect can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			sures, such as personal protective equipment
Do not inhale gases/vapours/aerosols. Avoid contact with eyes skin. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventila workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for shterm work. If applicable, further recommendations for respiratory protect can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. Algomin. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.	hygien	ic measures	Do not smoke, eat or drink while working. Have eye wa
skin. Do not store food in the work area. Wash hands before breaks at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventila workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for sh term work. If applicable, further recommendations for respiratory protection be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480 min. Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480 min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			
at the end of work. Breathing equipment: Respiratory protection required at insufficiently ventilation workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for shifter work. If applicable, further recommendations for respiratory protection be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480m Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			
Breathing equipment: Respiratory protection required at insufficiently ventila workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for shterm work. If applicable, further recommendations for respiratory protection Hand protection Hand protection Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480m Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			Do not store food in the work area. Wash hands before breaks a
 workplaces and when working with splashes. Fresh air mask combination filters A2-P2 (EN529) are recommended for sh term work. If applicable, further recommendations for respiratory protection Hand protection Hand protection Hand protection With the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480m Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves. 	Broath	ina oquinmont:	
combination filters A2-P2 (EN529) are recommended for sh term work.If applicable, further recommendations for respiratory protect can be found in the appendix.In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended.Hand protectionHand protectionSuitable materials for protective gloves; EN 374: 	Diedill	ing equipment.	
If applicable, further recommendations for respiratory protect can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended.Hand protectionSuitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480n Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			combination filters A2-P2 (EN529) are recommended for sho
can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480n Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			
In case of hypersensitivity of the respiratory tract (asthma, chr bronchitis), handling of the product is not recommended.Hand protectionSuitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480n Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			
Hand protectionbronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480n Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			In case of hypersensitivity of the respiratory tract (asthma, chroi
Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480n Fluororubber - FKM: thickness ≥0.4mm; breakthrough t ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			bronchitis), handling of the product is not recommended.
Fluororubber - FKM: thickness ≥0.4mm; breakthrough t ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.	· Hand protection		
Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.			Fluororubber - FKM: thickness ≥0.4mm; breakthrough tin
			Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min.
(Contd. on pa			Recommendation: Dispose of contaminated gloves. (Contd. on page



Page 6/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 30 (replaces version 29) Revis

Revision: 15.04.2025

Trade name MC-Color Flair vision - Komponente B

• Material of gloves	(Contd. of page 5) The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
 Penetration time of glove 	
material	Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min.
	Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min.
 Eye/face protection 	Wear safety goggles/face protection.
 Body protection: 	Wear suitable protective clothing when working.
	In case of hypersensitivity of the skin, handling of the product is not recommended.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chen	nical properties
General Information	
· Colour:	Colourless
· Smell:	Characteristic
 Melting point/freezing point: 	Not determined
Boiling point or initial boiling point and	
boiling range	175 °C (CAS: 111109-77-4
3 3 3	Dipropylenglykoldimethylether)
· Flash point:	70 °C
· рН	Not applicable.
pii	Not determined.
Viecesity	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
· dynamic at 20 °C:	2000 mPas
· Solubility	
· Water:	Partly miscible
· Steam pressure at 20 °C:	0 hPa (CAS: 111109-77-4
•	Dipropylenglykoldimethylether)
 Density and/or relative density 	
· Density at 20 °C	1.1 g/cm³
•	
• 9.2 Other information	
· Appearance:	
Form:	Fluid
· Important information on protection of hea	lth
and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
Explosive properties.	Froduct is not explosive.
 Information with regard to physical haza 	nrd
classes	
·Explosives	Void
· Flammable gases	Void
	(Contd. on page 7



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

Page 7/11

Trade name MC-Color Flair vision - Komponente B

		(Contd. of page
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity		
 10.1 Reactivity 10.2 Chemical stability 	No further relevant information available.	
• Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.	
 10.3 Possibility of hazardous reactions 	Reacts with amines	
10.4 Conditions to avoid	No further relevant information available.	
 10.5 Incompatible materials: 10.6 Hazardous 	No further relevant information available.	
decomposition products:	No dangerous decomposition products known	

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Harmful if inhaled.

Oral	LD50	lydrophiles, aliphatisches Polyisocyanat >2000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50/4 h	0.39 mg/l (rat)	
CAS: 822	-06-0 hexa	amethylene diisocyanate	
Oral	LD50	38 mg/kg (rat)	
Inhalative	LC50/4 h	0.39 mg/l (rat)	



Page 8/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

Trade name MC-Color Flair vision - Komponente B

· Serious eve damage/irritatio	(Contd. of page 7) n Based on available data, the classification criteria are not met.
· Respiratory or skin	
sensitisation	May cause an allergic skin reaction.
· Germ cell mutagenicity	Based on available data, the classification criteria are not met.
· Carcinogenicity	Based on available data, the classification criteria are not met.
· Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
11.2 Information on other ha	zards
· Endocrine disrupting proper	ties
None of the ingredients is lister	d.

SECTION 12: Ecological information

· 12.1 Toxicity

· 12.1 TOXIC	•	
· Aquatic to	xicity:	
CAS: 1609	94-68-3 Hydrophile	s, aliphatisches Polyisocyanat
LC50/96h 28.3 mg/l (Danio rei		rio)
EC50 >10000 mg/l (BEL)		
EC50/48h >100 mg/l (Daphnia		a magna)
ErC50/72h >100 mg/l (Scenede		•
· 12.2 Persis	stence and	<i>,</i>
degradabi	lity	No further relevant information available.
· 12.3 Bioac	cumulative	
potential		No further relevant information available.
· 12.4 Mobil	ity in soil	No further relevant information available.
[.] 12.5 Resul	ts of PBT and vPvE	3 assessment
· PBT:		Not applicable.
· vPvB:		Not applicable.
· 12.6 Endo	crine disrupting	
properties		The product does not contain substances with endocrine disrupting properties.
· 12.7 Other	adverse effects	
· Remark:		Harmful to fish
· Additional	ecological informa	ation:
· General no	-	Harmful to aquatic organisms
		Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
		IE (Contd. on page 9)

(Contd. on page 9)



Page 9/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

Trade name MC-Color Flair vision - Komponente B

(Contd. of page 8)

SECTION 13: Disposal considerations

· 13.1 Wast · Recomme	te treatment methods endation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.		
· European	waste catalogue		
17 00 00	CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)		
17 09 00	other construction and demolition wastes		
17 09 03*	tother construction and demolition wastes (including mixed wastes) containing hazardous substances		
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED		
15 01 00	packaging (including separately collected municipal packaging waste)		
15 01 01	paper and cardboard packaging		
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED		
15 01 00	packaging (including separately collected municipal packaging waste)		
15 01 02	plastic packaging		
HP4	Irritant - skin irritation and eye damage		
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity		
HP13	Sensitising		
HP14	Ecotoxic		
· Uncleane	d packagings:		

Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	



Page 10/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

Trade name MC-Color Flair vision - Komponente B

		(Contd. of page 9)
 14.5 Environmental hazards: Marine pollutant: 	No	
• 14.6 Special precautions for user	Not applicable.	
 14.7 Maritime transport in bulk accordia IMO instruments 	ng to Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/	
legislation specific for the substance or mixture	No further relevant information available.
· REGULATION (EC) No 1907/2006 ANNEX XVII	Conditions of restriction: 3, 74
DIRECTIVE 2011/65/EU on the electrical and electronic equ	e restriction of the use of certain hazardous substances in ipment – Annex II
None of the ingredients is liste	d.
· REGULATION (EU) 2019/114	8
Annex I - RESTRICTED EXPL	LOSIVES PRECURSORS (Upper limit value for the purpose of
licensing under Article 5(3))	
None of the ingredients is liste	d.
· Annex II - REPORTABLE EX	PLOSIVES PRECURSORS
None of the ingredients is liste	d.
· Regulation (EC) No 273/2004	on drug precursors
None of the ingredients is liste	d.
 Regulation (EC) No 111/2005 Community and third countr 	i laying down rules for the monitoring of trade between the ries in drug precursors
None of the ingredients is liste	d.
 15.2 Chemical safety assessment: 	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant	phrases
------------	---------

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.

(Contd. on page 11)

⁻ IF



Page 11/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 30 (replaces version 29)

Revision: 15.04.2025

Trade name MC-Color Flair vision - Komponente B

		(Contd. of page 2	
	H332	Harmful if inhaled.	
	H334	May cause allergy or asthma symptoms or breathin difficulties if inhaled.	
	H335	May cause respiratory irritation.	
	H412	Harmful to aquatic life with long lasting effects.	
	EUH20	4 Contains isocyanates. May produce an allergic reaction.	
Department issuing data			
specification sheet:	Environment protection department.		
Date of previous version:	19.10.2021		
Version number of previous			
version:	29		
Abbreviations and acronyms:	S: RID: Règlement international concernant le transport des marchandise dangereuses par chemin de fer (Regulations Concerning the Internation Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses p route (European Agreement Concerning the International Carriage of Dangerou		
	IATA: Inte GHS: Glo	road) ternational Maritime Code for Dangerous Goods ernational Air Transport Association bally Harmonised System of Classification and Labelling of Chemicals European Inventory of Existing Commercial Chemical Substances	
	ELINCS: CAS: Che	European List of Notified Chemical Substances emical Abstracts Service (division of the American Chemical Society) erived No-Effect Level (REACH)	
		redicted No-Effect Concentration (REACH)	
		thal concentration, 50 percent	
		thal dose, 50 percent	
		sistent, Bioaccumulative and Toxic	
		y Persistent and very Bioaccumulative x. 2: Acute toxicity – Category 2	
		x. 4: Acute toxicity – Category 4	
		2: Skin corrosion/irritation – Category 2	
		2: Serious eye damage/eye irritation – Category 2	
		ns. 1: Respiratory sensitisation – Category 1	
		s. 1: Skin sensitisation – Category 1	
		: 3: Specific target organ toxicity (single exposure) – Category 3 Chronic 3: Hazardous to the aquatic environment - long-term aqua	
* Data compared to the		Category 3	