

Page 1/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name MC-Color Flair vision T - Komponente B

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Coating compound/ Surface coating/ paint

Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

> Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

msds@mc-bauchemie.de

1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Warning

Hazard-determining

components of labelling: Aliphatisches Polyisocyanat

(Contd. on page 2)



Page 2/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

#### Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 1)

Hydrophiles, aliphatisches Polyisocyanat

hexamethylene diisocyanate

· Hazard statements H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

• **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P304+P340 IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell. P403+P233 Store in a well-ventilated place. Keep container tightly

closed.

P405 Store locked up.

· Additional information: EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before

industrial or professional use.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:		
CAS: 28182-81-2	Aliphatisches Polyisocyanat	30-60%
	Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	
CAS: 666723-27-9	Hydrophiles, aliphatisches Polyisocyanat	≥10-<20%
	Acute Tox. 3, H331; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37- 0000	hexamethylene diisocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.5%
· Additional information	For the wording of the listed hazard phrases refer to s	ection 16.

### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

General information Remove soiled, soaked clothing immediately.

• After inhalation Remove person to fresh air, keep warm, allow to rest; if breathing

is difficult, seek medical attention.

(Contd. on page 3)



Page 3/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 12.04.2025 Printing date 12.04.2025 Version number 38 (replaces version 37)

#### Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 2)

In case of contact with skin, wash carefully with plenty of soap and · After skin contact

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at

least 10 minutes) with water that is as lukewarm as possible.

Consult an ophthalmologist.

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

· 4.3 Indication of any

immediate medical attention

and special treatment needed Therapeutic measures: No information available.

# **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

· Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with

water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures

Not required.

· 6.2 Environmental

precautions: Inform respective authorities in case product reaches water or

sewage system.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

(Contd. on page 4)



Page 4/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 12.04.2025 Printing date 12.04.2025 Version number 38 (replaces version 37)

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 3)

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas.

Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being

exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing

immediately.

· Information about protection

against explosions and fires: Keep ignition sources away - do not smoke.

Protect from heat.

Do not store near heat sources.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance

reasons can be found in our technical data sheet.

· Storage

Requirements to be met by

storerooms and containers: Keep tightly closed in original packaging. Ventilate storage rooms

well. Carefully close opened containers and store upright to

prevent any leakage.

Storage temperature >5°C and <30°C

· Information about storage in

one common storage facility: May be stored together with hazardous substances of other

classes up to 200 kg.

· Further information about

storage conditions:

Keep container tightly closed in a well-ventilated place.

· Storage class

· 7.3 Specific end use(s)

No further relevant information available.



Page 5/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 38 (replaces version 37) Revision: 12.04.2025 Printing date 12.04.2025

Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 4)

8.1 Control	parameters	
Componen	ts with critical values that require monitoring at the workplace:	
CAS: 822-0	6-0 hexamethylene diisocyanate	
OEL (Irelan	d) Long-term value: 0.005 ppm as -NCO, Sens	
DNELs		
CAS: 28182	2-81-2 Aliphatisches Polyisocyanat	
Inhalative [	DNEL   0.5 mg/m³ (Workers) (long term local)	
	1 mg/m³ (kei) (acute local eff)	
CAS: 822-06-0 hexamethylene diisocyanate		
Inhalative [	DNEL 0.5 mg/m³ (ArL)	
PNECs		
CAS: 28182	2-81-2 Aliphatisches Polyisocyanat	
PNEC aqua	12.7 μg/l (Daphnia magna) (marine)	
PNEC	38.28 mg/l (kei) (STP)	
CAS: 822-0	6-0 hexamethylene diisocyanate	
PNEC	100 mg/l (Sewage Treatment Plant)	
	0.0199 mg/l (Mew)	
	0.199 mg/l (Freshwater)	
PNEC	8884 mg/kg dwt (Bod)	
	4455 mg/kg dwt (Marine water sediment)	

· Additional information:

The lists that were valid during the compilation were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering

controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

44551 mg/kg dwt (Fresh water sediment)

· General protective and

hygienic measures

Do not smoke, eat or drink while working. Have eye wash

equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Do not store food in the work area. Wash hands before breaks and

at the end of work.

· Breathing equipment: Respiratory protection required at insufficiently ventilated

workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-

term work.

If applicable, further recommendations for respiratory protection

can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic

bronchitis), handling of the product is not recommended.

(Contd. on page 6)



Page 6/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 12.04.2025 Printing date 12.04.2025 Version number 38 (replaces version 37)

#### Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 5)

· Hand protection Suitable materials for protective gloves; EN 374:

> Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluororubber - FKM: thickness ≥0.4mm; breakthrough time

≥480min.

Multi-layer glove - PE/EVAL/PE; Breakthrough time >480 min.

Recommendation: Dispose of contaminated gloves.

· Material of gloves The selection of the suitable gloves does not only depend on the

material, but also on further marks of quality and varies from

manufacturer to manufacturer.

· Penetration time of glove

material

Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time

Multi-layer glove - PE/EVAL/PE; Breakthrough time >480 min.

· Eye/face protection

Wear safety goggles/face protection.

· Body protection: Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not

recommended.

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Colourless · Smell: Characteristic • Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

175 °C boiling range · Flash point: 70 °C · pH at 20 °C

· Viscosity:

· Kinematic viscosity Not determined. · dynamic at 20 °C: 2000 mPas

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure: Not determined.

· Density and/or relative density

 Density at 20 °C 1.1 g/cm<sup>3</sup>

· 9.2 Other information

· Appearance:

Fluid · Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive.

(Contd. on page 7)



Page 7/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

#### Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 6)

· Information with regard to physical haz classes	ard
· Explosives	Void
· Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

## **SECTION 10: Stability and reactivity**

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions Reacts with amines

• **10.4 Conditions to avoid** No further relevant information available. **10.5 Incompatible materials:** No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

# **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Harmful if inhaled.

· LD/LC50 values that are relevant for classification:

### CAS: 28182-81-2 Aliphatisches Polyisocyanat

 Oral
 LD50
 >2500 mg/kg (rat) (OECD 423)

 Dermal
 LD50
 >2000 mg/kg (rat) (OECD 402)

Inhalative LC50/4 h 1.5 mg/l (rat)

(Contd. on page 8)



Page 8/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

#### Trade name MC-Color Flair vision T - Komponente B

	·	4 .1			_
(	COL	ıια.	OI	page	1

	CAS: 666723-27-9 Hydrophiles, aliphatisches Polyisocyanat				
	Oral	LD50	>5000 mg/kg (rat)		
	Dermal	LD50	>2000 mg/kg (rat)		
	Inhalative	LC50/4 h	0.5 mg/l (rat)		
Γ	CAS: 822-06-0 hexamethylene diisocyanate				
Γ	Oral	LD50	738 mg/kg (rat)		
	Inhalative	LC50/4 h	0.39 mg/l (rat)		

· Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met. • Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

**sensitisation** May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

· 12.1 Toxicity

Δα	uat	ic 1	hov	ic	itv:
лu	uaı	16 1	UA	16	LV.

### CAS: 28182-81-2 Aliphatisches Polyisocyanat

ErC10/72h 370 mg/l (Desmodesmus subspicatus) (EU C.3) ErC50/72h >1000 mg/l (Desmodesmus subspicatus) (EU C.3)

#### CAS: 666723-27-9 Hydrophiles, aliphatisches Polyisocyanat

LC50/96h | 35.2 mg/l (Danio rerio) EC50 | >10000 mg/l (BEL)

EC50/48h >100 mg/l (Daphnia magna)

ErC50/72h | 72 mg/l (Desmodesmus subspicatus)

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.
12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

(Contd. on page 9)



Page 9/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

#### Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 8)

· 12.6 Endocrine disrupting

properties .

The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

· General notes: Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

## **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

anow product to reach sewage system.				
· European	waste catalogue			
17 00 00	CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)			
17 09 00	other construction and demolition wastes			
17 09 03*	other construction and demolition wastes (including mixed wastes) containing hazardous substances			
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED			
15 01 00	packaging (including separately collected municipal packaging waste)			
15 01 01	paper and cardboard packaging			
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED			
15 01 00	packaging (including separately collected municipal packaging waste)			
15 01 02	plastic packaging			
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity			
HP13	Sensitising			

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

# SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

(Contd. on page 10)



Page 10/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

#### Trade name MC-Color Flair vision T - Komponente B

(Contd. of page 9)

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to

**IMO instruments** Not applicable.

· UN "Model Regulation": Void

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/ legislation specific for the

**substance or mixture** No further relevant information available.

· REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3, 74

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)



Page 11/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 38 (replaces version 37) Revision: 12.04.2025

#### Trade name MC-Color Flair vision T - Komponente B

		(Contd. of page 10)
· Relevant phrases	H302	Harmful if swallowed.
•	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H330	Fatal if inhaled.
	H331	Toxic if inhaled.
	H332	Harmful if inhaled.
	H334	May cause allergy or asthma symptoms or breathing
		difficulties if inhaled.
	H335	May cause respiratory irritation.
	H412	Harmful to aquatic life with long lasting effects.

Department issuing data

specification sheet:

Environment protection department. 13.10.2021

· Date of previous version:

· Version number of previous

version:

37

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

EUH204 Contains isocyanates. May produce an allergic reaction.

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 3

· \* Data compared to the previous version altered.