

Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 30 (replaces version 29) Revision: 10.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name MC-Color Flex pro

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance

/ the mixture Dispersion paint/ Latex paint

Surface protection

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

msds@mc-bauchemie.de

1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

GHS07

· Signal word Warning

Hazard-determining

components of labelling: 2-methyl-2H-isothiazol-3-one

(Contd. on page 2)



Page 2/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 30 (replaces version 29) Revision: 10.12.2024

Trade name MC-Color Flex pro

(Contd. of page 1)

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]

(3:1)

2-octyl-2H-isothiazol-3-one

4,5-dichloro-2-octyl-2H-isothiazol-3-one H317 May cause an allergic skin reaction.

• **Hazard statements** H317 May cause an allergic skin reaction.

• **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before

reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

· Additional information: EUH211 Warning! Hazardous respirable droplets may be formed

when sprayed. Do not breathe spray or mist.

Contains biocidal products: 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-octyl-2H-isothiazol-3-one, 4,5-

dichloro-2-octyl-2H-isothiazol-3-one

· 2.3 Other hazards

· Results of PBT and vPvB assessment · PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:			
CAS: 1317-65-3	Calcium carbonate	10-30%	
	substance with a Community workplace exposure limit		
	Titanium Dioxide	10-30%	
EINECS: 236-675-5	Carc. 2, H351		
		(Contd. on page 3)	

ΙΕ





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 30 (replaces version 29) Revision: 10.12.2024

Trade name MC-Color Flex pro

		(Contd. of page
CAS: 2634-33-5	1,2-benzisothiazol-3(2H)-one	≥0.025-<0.05%
EINECS: 236-671-3	Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	
	Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	
CAS: 2682-20-4	2-methyl-2H-isothiazol-3-one	≥0.0015-<0.025%
EINECS: 220-239-6	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	
CAS: 26530-20-1 EINECS: 247-761-7	2-octyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 ATE: LD50 oral: 125 mg/kg	≥0.00025-<0.0015%
CAS: 64359-81-5 EINECS: 264-843-8	4,5-dichloro-2-octyl-2H-isothiazol-3-one Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Acute Tox. 4, H302; Skin Sens. 1A, H317; STOT SE 3, H335 ATE: LD50 oral: 567 mg/kg LC50/4 h inhalative: 0.16 mg/l Specific concentration limits: Skin Irrit. 2; H315: C ≥ 0.025 % Eye Irrit. 2; H319: C ≥ 0.0015 %	≥0.00025-<0.0015%



Page 4/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 10.12.2024 Printing date 10.12.2024 Version number 30 (replaces version 29)

Trade name MC-Color Flex pro

(Contd. of page 3)

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information For all first aid measures: observe self-protection and consult a

doctor!

· After inhalation Take the person out into the fresh air. · After skin contact

Remove heavily soiled clothing.

Clean with plenty of water. Do not use thinner or similar.

· After eye contact Rinse for 10 minutes under running water with the eyelids open or

use eye rinsing solution. Always consult an ophthalmologist!

· After swallowing Do not induce vomiting.

Drink plenty of water in small sips.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

Not required. emergency procedures

· 6.2 Environmental

precautions: Dilute with much water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections No dangerous materials are released.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling No special measures required.

No special precautions necessary if used correctly.

(Contd. on page 5)



Page 5/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 30 (replaces version 29) Revision: 10.12.2024

Trade name MC-Color Flex pro

(Contd. of page 4)

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: Protect containers from frost!

Only store in the original container or in containers recommended

by the manufacturer.

After decanting, label containers as original containers.

Do not store in break rooms, recreation rooms or sanitary facilities as well as in stairwells, corridors, escape and rescue routes,

passages, passageways and confined spaces.

· Further information about

storage conditions: None.
Storage class 12

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 1317-65-3 Calcium carbonate

OEL (Ireland) Long-term value: 10* 4** mg/m³

*inhalable dust, **respirable dust

· DNELs

CAS: 1317-65-3 Calcium carbonate

Oral DNEL 6.1 mg/kg bw/Tag (ArL)

Inhalative DNEL 10 mg/m³ (ArL)

· PNECs

CAS: 1317-65-3 Calcium carbonate

PNEC 100 mg/l (Sewage Treatment Plant)

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures Do not store any foodstuffs or eat, drink, snuff or smoke in the

work area!

Avoid contact with eyes and skin!

Preventively apply skin protection ointment to facilitate skin

cleansing.

Remove product residues from the skin!

Clean hands thoroughly at the end of work and before cleaning! Remove product residues from the skin with a suitable cleaning

agent - never use solvents or thinners to clean the skin! Use skin care products after work (moisturising cream).

(Contd. on page 6)



Page 6/12

(Contd. of page 5)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 30 (replaces version 29) Revision: 10.12.2024

Trade name MC-Color Flex pro

· Breathing equipment:

For spraying processes:

Particle filter P2 (white)

• Hand protection Gloves made of: Natural latex, polychloroprene, nitrile rubber.

(Category 3 chemical protective gloves, recognisable by the CE

mark with four-digit test number).

When wearing protective gloves, cotton undergloves are

recommended.

· **Material of gloves** Natural latex, polychloroprene, nitrile rubber.

· Penetration time of glove

material The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

• Eye/face protection Frame glasses

· Body protection: Protective work clothing.

• Skin protection Use greasy skin protection ointment for all uncovered parts of the

body!

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: According to product specification

Smell: Characteristic
Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

beiling point of initial boiling point and

boiling range 100 °C

· Flash point: Not applicable

· pH at 20 °C

· Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.32500 mPas

Solubility

Water: Fully miscibleSteam pressure at 20 °C: 23 hPa

Density and/or relative density

• Density at 20 °C 1.42 g/cm³ • Relative density Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void

(Contd. on page 7)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 30 (replaces version 29) Revision: 10.12.2024 Printing date 10.12.2024

Trade name MC-Color Flex pro

(Contd. of page 6)

· Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

No dangerous reactions known reactions

· 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

No dangerous decomposition products known decomposition products:

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values that are relevant for classification:			
CAS: 131	CAS: 1317-65-3 Calcium carbonate			
Oral	LD50	>2000 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)		
CAS: 13463-67-7 Titanium Dioxide				
Oral	LD50	>5000 mg/kg (rat)		
Dermal	LD50	>10000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>6.8 mg/l (rat)		
		(Contd. on page 8		



Page 8/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 30 (replaces version 29) Revision: 10.12.2024

Trade name MC-Color Flex pro

		(Contd. of page
CAS: 263	4-33-5 1,2·	-benzisothiazol-3(2H)-one
Oral	LD50	1020 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
CAS: 268	CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one	
Oral	LD50	50-300 mg/kg (rat)
Inhalative	LC50/4 h	0.11 mg/l (rat)
CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-		
Oral	LD50	and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
		49.6-75 mg/kg (rat)
Dermal	LD50	87.12 mg/kg (rabbit)
		0.171 mg/l (rat)
CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one		
Oral	LD50	125 mg/kg (ATE)
		500 mg/kg (rat)
Dermal	LD50	311 mg/kg (ATE)
		>2000 mg/kg (rat)
Inhalative	LC50/4 h	0.27 mg/l (ATE)
		0.6 mg/l (rat)
CAS: 64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one		
Oral	LD50	567 mg/kg (ATE)
Inhalative	LC50/4 h	0.16 mg/l (ATE)
		•

Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met. • Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 9)



Page 9/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 30 (replaces version 29) Revision: 10.12.2024

Trade name MC-Color Flex pro

(Contd. of page 8)

SECTION 12: Ecological information · 12.1 Toxicity · Aquatic toxicity: CAS: 1317-65-3 Calcium carbonate EC50/72h >14 mg/l (Desmodesmus subspicatus) LC50/96h >10000 mg/l (Oncorhynchus mykiss) LC50/48h >1000 mg/l (Daphnia magna) EC50/48h >1000 mg/l (Daphnia magna) CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one EC50/72h | 0.067 mg/l (Pseudokirchneriella subcapitata) 0.11 mg/l (Selenastrum capricornutum) LC50/96h 1.6 mg/l (Oncorhynchus mykiss) EC50/48h 1.1 mg/l (Daphnia magna) CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one EC50/72h | 0.157 mg/l (Pseudokirchneriella subcapitata) LC50/96h 6 mg/l (Oncorhynchus mykiss) EC50/48h 1.68 mg/l (Daphnies) CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) LC50/24h | 0.19 mg/l (fish) EC50/72h | 0.027 mg/l (Pseudokirchneriella subcapitata) LC50/96h | 0.19 mg/l (Oncorhynchus mykiss) LC50/48h | 0.28 mg/l (fish) EC50/48h | 0.16 mg/l (Daphnia magna) NOEC 0.02 mg/l (Oncorhynchus mykiss) 0.00049 mg/l (Ske) 0.1 mg/l (Daphnia magna) CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one EC50/48h 0.42 mg/l (Daphnien)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.
12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

propertiesThe product does not contain substances with endocrine disrupting

properties.

(Contd. on page 10)



Page 10/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 30 (replaces version 29) Revision: 10.12.2024 Printing date 10.12.2024

Trade name MC-Color Flex pro

(Contd. of page 9)

· 12.7 Other adverse effects

· Additional ecological information:

· General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES,

SEALANTS AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

· Uncleaned packagings:

· Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· Recommended cleaning

Water, if necessary with cleaning agent. agent:

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
	(Contd. on page 1



Page 11/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 30 (replaces version 29) Revision: 10.12.2024

Trade name MC-Color Flex pro

(Contd. of page 10)

UN "Model Regulation":

Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
 H301 Toxic if swallowed.
 H302 Harmful if swallowed.

H310 Fatal in contact with skin.H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.H351 Suspected of causing cancer.

(Contd. on page 12)



Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 30 (replaces version 29) Revision: 10.12.2024

Trade name MC-Color Flex pro

(Contd. of page 11)

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Department issuing data

specification sheet: Environment protection department.

· Date of previous version: 19.10.2021

· Version number of previous

29

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity – Category 2 Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard -

Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 1

* * Data compared to the previous version altered.