

Page 1/13

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name MC-DUR 1204 R - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Epoxy impregnation

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400

E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG

Hagackerstr. 10

CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

#### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS07 GHS09

· Signal word Warning

(Contd. on page 2)





### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 10.12.2024 Printing date 10.12.2024 Version number 35 (replaces version 34)

#### Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 1)

Hazard-determining

components of labelling: epoxide derivates

Cyclohexanol, 4,4'-(1-Methylethyliden)-,Polymer mit 2-

(Chlormethyl)oxiran

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane

methyl toluene-4-sulphonate

Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4piperidinyl) ester and decanedioic acid,(1,2,2,6,6-pentamethyl-4-

piperidinyl) methyl ester

· Hazard statements H315 Causes skin irritation.

> H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Avoid breathing dust/fume/gas/mist/vapours/ · Precautionary statements P261

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/ P332+P313

attention.

If skin irritation or rash occurs: Get medical P333+P313

advice/attention.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture consisting of the following components.

| CAS: 1675-54-3                    | epoxide derivates   | 50-70% |
|-----------------------------------|---|--------|
| EINECS: 216-823-5                 | Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye<br>Irrit. 2, H319; Skin Sens. 1, H317, EUH205<br>Specific concentration limits:<br>Skin Irrit. 2; H315: C≥ 5 %<br>Eye Irrit. 2; H319: C ≥ 5 % |        |
| CAS: 30583-72-3<br>NLP: 500-070-7 | Cyclohexanol, 4,4'-(1-Methylethyliden)-,Polymer<br>mit 2-(Chlormethyl)oxiran<br>Skin Sens. 1, H317  | 10-30% |



Page 3/13

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

#### Trade name MC-DUR 1204 R - Komponente A

| CAS: 933999-84-9   | Reaction products of hexane-1,6-diol with 2-<br>(chloromethyl)oxirane (1:2)   | (Contd. of page<br>≥2.5-<10% |
|--|---|------------------------------|
|  | Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1,<br>H317; Aquatic Chronic 3, H412   |                              |
| CAS: 100-51-6  | Benzyl alcohol  | <5%                          |
|  | Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319  |                              |
| CAS: 80-48-8   | methyl toluene-4-sulphonate   | ≥0.1-<1%                     |
| EINECS: 201-283-5  | Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute<br>Tox. 4, H302; Skin Sens. 1, H317  |                              |
| EC number: 915-687-0<br>Reg.nr.: 01-2119491304-40-<br>XXXX | Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester and decanedioic acid,(1,2,2,6,6-pentamethyl-4-piperidinyl) methyl ester | ≥0.025-<0.1%                 |
|  | Repr. 2, H361; Aquatic Acute 1, H400; Aquatic<br>Chronic 1, H410; Skin Sens. 1A, H317   |                              |
| Additional information                                     | For the wording of the listed hazard phrases refer to   | section 16.                  |

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

• After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

• After skin contact In case of contact with skin, wash carefully with plenty of soap and

un case of contact with skin, wash carefully with plenty of soap ar water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

### **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

• 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

(Contd. on page 4)



Page 4/13

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 10.12.2024 Printing date 10.12.2024 Version number 35 (replaces version 34)

Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures

Not required.

6.2 Environmental

precautions: Inform respective authorities in case product reaches water or

sewage system.

· 6.3 Methods and material for

containment and cleaning up; Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe

handling Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy

resins.

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: Protect from heat and direct sunlight.

(Contd. on page 5)



Page 5/13

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 4)

· Storage class

10

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· DNELs

#### CAS: 100-51-6 Benzyl alcohol

| Oral | DNEL | 4 mg/kg bw/Tag (ArL)  |
|------|------|-----------------------|
|      |      | 20 mg/kg bw/Tag (Ark) |

Dermal DNEL 8 mg/kg bw/day (ArL)

Inhalative DNEL 22 mg/m³ (ArL)
110 mg/m³ (Ark)

PNECs

#### CAS: 100-51-6 Benzyl alcohol

PNEC | 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

· Additional information:

The lists that were valid during the compilation were used as basis.

8.2 Exposure controls
Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

**hygienic measures** Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

· Hand protection Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

· Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

(Contd. on page 6)



Page 6/13

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

#### Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 5)

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

Safe

Tight-fitting safety goggles Safety goggles.

· Body protection:

· Eye/face protection

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Yellow

Smell: CharacteristicMelting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range

>200 °C (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues

molecular weight < 700)

· Flash point: 151 °C · Auto-ignition temperature: 184 °C

(Contd. on page 7)



Page 7/13

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

#### Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 6)

· **pH** Not determined.

· Viscosity:

Kinematic viscositydynamic:Not determined.Not determined.

·Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: <0.1 hPa (CAS: 25068-38-6 Propyl -2,2-diphenyl-

4,4'dipropyloxirane polymers and homologues

molecular weight < 700)

· Density and/or relative density

Density at 20 °C 1.14 g/cm³

· 9.2 Other information

· Appearance:

Fluid

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void

Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which emit
flammable gases in contact with water
Oxidising liquids
Oxidising solids
Void

Organic peroxides
 Corrosive to metals
 Desensitised explosives

Void
Void

#### SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

(Contd. on page 8)



Page 8/13

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

#### Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 7)

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 values that are relevant for classification:                                    |                      |                      |  |
|---|----------------------|----------------------|--|
| CAS: 1675-54-3 epoxide derivates  |                      |                      |  |
| Dermal  | LD50                 | 23000 mg/kg (rabbit) |  |
| CAS: 30583-72-3 Cyclohexanol, 4,4'-(1-Methylethyliden)-,Polymer mit 2-(Chlormethyl)oxiran |                      |                      |  |
| Oral  | LD50                 | >5300 mg/kg (rat)    |  |
| Dermal  | LD50                 | >2000 mg/kg (rabbit) |  |
| CAS: 100-51-6 Benzyl alcohol  |                      |                      |  |
| Oral  | LD50                 | 1230 mg/kg (rat)     |  |
|   | NOAEL 2nd year study | 200 mg/kg (mouse)    |  |
|   |                      | 200 mg/kg (rat)      |  |
| Dermal  | LD50                 | 2000 mg/kg (rabbit)  |  |
| Inhalative  | LC50/4 h             | >4178 mg/l (rat)     |  |
| CAS: 80-48-8 methyl toluene-4-sulphonate  |                      |                      |  |
| Oral  | LD50                 | 341 mg/kg (rat)      |  |

Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin

**sensitisation** May cause an allergic skin reaction.

Carcinogenicity
Reproductive toxicity
STOT-repeated exposure
Aspiration hazard
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 9)



Page 9/13

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 8)

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 1675-54-3 epoxide derivates

IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (Oncorhynchus mykiss) EC50/48h 1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

CAS: 100-51-6 Benzyl alcohol

IC50/72h 700 mg/l (algae)

LC50/96h 460 mg/l (Pimephales promelas) 10 mg/l (Lepomis macrochirus)

· 12.2 Persistence and

**degradability** No further relevant information available.

12.3 Bioaccumulative

potential
No further relevant information available.
12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment
· PBT:
· vPvB:
Not applicable.
Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Remark: Toxic for fish

· Additional ecological information:

• General notes: Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

#### SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU)

OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES,

SEALANTS AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

(Contd. on page 10)





### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

### Trade name MC-DUR 1204 R - Komponente A

|           | (Contd. of page 9)  |
|-----------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |
| HP4       | Irritant - skin irritation and eye damage   |
| HP13      | Sensitising   |
| HP14      | Ecotoxic  |

· Uncleaned packagings: · Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

| 14.1 UN number or ID number<br>ADR, IMDG, IATA | UN3082   |
|--|--|
| · 14.2 UN proper shipping name                 |  |
| ADR, IATA                                      | ENVIRONMENTALLY HAZARDO  |
| ·IMDG  | SUBSTANCE, LIQUID, N.O.S. (epoxide derivate<br>ENVIRONMENTALLY HAZARDO |
| imbe   | SUBSTANCE, LIQUID, N.O.S. (epoxide deriva                              |
|  | Ethyl-4-[[(methylphenylamino)methylen]ami                              |
|  | benzoat), MARINE POLLUTANT   |
| · 14.3 Transport hazard class(es)              |  |
| ADR  |  |
| Class  | 9 (M6) Miscellaneous dangerous substances                              |
| · Label  | articles.<br>9   |
|  |  |
| · IMDG, IATA<br>· Class                        | 9 Miscellaneous dangerous substances a                                 |
| 0.000  | articles.  |
| Label  | 9  |
| · 14.4 Packing group                           |  |
| · ADR, IMDG, IATA                              | III  |
| 14.5 Environmental hazards:                    |  |
| Marine pollutant:                              | Yes  |
| · Special marking (ADR):                       | Symbol (fish and tree) Symbol (fish and tree)                          |
| Special marking (ADK). Special marking (IATA): | Symbol (fish and tree)   |
|  | , ,  |
| 14.6 Special precautions for user              | Warning: Miscellaneous dangerous substances articles.                  |
| Kemler Number:                                 | 90   |
| · EMS Number:                                  | F-A,S-F  |



Page 11/13

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

#### Trade name MC-DUR 1204 R - Komponente A

| 44.788  | (Contd. of page 1  |
|---|--|
| · 14.7 Maritime transport in bulk accord<br>IMO instruments       | Ing to Not applicable.   |
| Transport/Additional information:                                 |  |
| · ADR<br>· Limited quantities (LQ)<br>· Excepted quantities (EQ)  | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 100<br>ml |
| · Transport category<br>· Tunnel restriction code                 | <br>3<br>(-)   |
| · IMDG<br>· Limited quantities (LQ)<br>· Excepted quantities (EQ) | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 100<br>ml |
| UN "Model Regulation":  | UN 3082 ENVIRONMENTALLY HAZARDOU<br>SUBSTANCE, LIQUID, N.O.S. (EPOXID<br>DERIVATES), 9, III                              |

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

· REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 12)



Page 12/13

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

#### Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 11)

#### · Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

#### · Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

| D - I            | 11000 | 1 1 f . 1 !f         |
|------------------|-------|----------------------|
| Relevant phrases | H302  | Harmful if swallowed |

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· Department issuing data

specification sheet: Environment protection department.

Date of previous version: 19.10.2021

Version number of previous

rersion: 3

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 13)



Page 13/13

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024 Version number 35 (replaces version 34) Revision: 10.12.2024

#### Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 12)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Repr. 2: Reproductive toxicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 3

ΙE

<sup>\*</sup> Data compared to the previous version altered.