



BE SURE. BUILD SURE.

Page 1/14

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** MC-DUR 1800 - Komponente A

· **Article number:** 3154

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Epoxy coating

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360F May damage fertility.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure.  
Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

Trade name MC-DUR 1800 - Komponente A

(Contd. of page 1)

· **Hazard pictograms**



GHS07 GHS08 GHS09

· **Signal word**

Danger

· **Hazard-determining components of labelling:**

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane

Quartz sand

Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

4,4'-Methylenediphenyldiglycidyl ether

Maleic anhydride

Polymer with epoxy-functional groups

1,6-hexene-diglycidylether

Fatty acids, C14-18 and C16-18-unsatd., maleated

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360F May damage fertility.

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

· **Additional information:**

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Resin mixture with colouring agents.

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/14

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

**Trade name MC-DUR 1800 - Komponente A**

(Contd. of page 2)

Mixture consisting of the following components.

<b>· Dangerous components:</b>		
CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	30-60%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz sand STOT RE 1, H372	10-30%
CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥10-<25%
EC number: 953-811-5	Polymer with epoxy-functional groups Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥2.5-<5%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<5%
CAS: 16096-31-4 EINECS: 240-260-4	1,6-hexene-diglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH205	≥1-<2.5%
CAS: 68609-97-2 EINECS: 271-846-8	Oxirane, mono((C12-14-alkyloxy)methyl)derivatives Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.3-<1%
CAS: 85711-46-2	Fatty acids, C14-18 and C16-18-unsatd., maleated Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<0.5%
CAS: 108-31-6 EINECS: 203-571-6	Maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥0.001-<0.1%

**· Additional information**

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****· 4.1 Description of first aid measures**

- General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- After inhalation** Supply fresh air; seek medical advice if symptoms occur.  
If unconscious, place in recovery position and seek medical advice.
- After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- After eye contact** Rinse opened eye for several minutes under running water.  
Call a doctor immediately

(Contd. on page 4)

IE



BE SURE. BUILD SURE.

Page 4/14

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

Trade name MC-DUR 1800 - Komponente A

· **After swallowing**

Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

(Contd. of page 3)

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **For safety reasons unsuitable extinguishing agents**

Water with a full water jet.

· **5.2 Special hazards arising from the substance or mixture**

Can be released in case of fire  
Carbon monoxide (CO)

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained breathing apparatus.

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation

· **6.2 Environmental precautions:**

Prevent material from reaching sewage system, holes and cellars.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **6.4 Reference to other sections**

See Section 13 for information on disposal.

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Open and handle containers with care.  
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.  
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash

(Contd. on page 5)



BE SURE. BUILD SURE.

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

**Trade name MC-DUR 1800 - Komponente A**

(Contd. of page 4)

skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** Keep container tightly closed in a well-ventilated place.
- **Storage class** 6.1C

### SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

**CAS: 14808-60-7 Quartz sand**

OEL (Ireland)	Long-term value: 0.1 mg/m <sup>3</sup>
BOELV (European Union)	Long-term value: 0.1* mg/m <sup>3</sup> *respirable fraction

**CAS: 108-31-6 Maleic anhydride**

OEL (Ireland)	Long-term value: 0.01 ppm *Inhalable fraction and vapour, Sens
---------------	---

· **DNELs**

**CAS: 100-51-6 Benzyl alcohol**

Oral	DNEL	4 mg/kg bw/Tag (ArL)
		20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL)
		40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m <sup>3</sup> (ArL)
		110 mg/m <sup>3</sup> (Ark)

**CAS: 16096-31-4 1,6-hexene-diglycidylether**

Dermal	DNEL	2.8 mg/kg bw/day (ArL)
Inhalative	DNEL	4.9 mg/m <sup>3</sup> (ArL)

**CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives**

Dermal	DNEL	0.75 mg/kg bw/day (ArL)
Inhalative	DNEL	0.49 mg/m <sup>3</sup> (ArL)

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

Trade name MC-DUR 1800 - Komponente A

(Contd. of page 5)

**· PNECs**

**CAS: 100-51-6 Benzyl alcohol**

PNEC 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

**CAS: 16096-31-4 1,6-hexene-diglycidylether**

PNEC 0.0115 mg/l (Fresh water)

0.00115 mg/l (Mew)

PNEC 0.223 mg/kg dwt (Bod)

0.0283 mg/kg dwt (Sediment)

0.283 mg/kg dwt (Fresh water sediment)

**CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives**

PNEC 0.00072 mg/l (Mew)

0.0072 mg/l (Freshwater)

PNEC 80.12 mg/kg dwt (Bod)

6.677 mg/kg dwt (Sediment)

66.77 mg/kg dwt (Fresh water sediment)

**· Additional information:** The lists that were valid during the compilation were used as basis.

**· 8.2 Exposure controls**

**· Appropriate engineering controls**

No further data; see section 7.

**· Individual protection measures, such as personal protective equipment**

**· General protective and hygienic measures**

Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.

**· Breathing equipment:**

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

**· Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>  
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

**Trade name MC-DUR 1800 - Komponente A**

(Contd. of page 6)

- **Penetration time of glove material**  
 manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.  
 Nitrile rubber  
 Recommended material thickness:  $\geq 0.4$  mm  
 The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.  
 The following applies to all other gloves:  
 The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.  
 Nitrile rubber  
 Material thickness:  $\geq 0.40$  mm  
 Penetration time:  $\geq 480$  min  
 Butyl rubber:  
 Material thickness:  $\geq 0.5$  mm  
 Penetration time:  $\geq 480$  min
- **Eye/face protection**  
 Tight-fitting safety goggles.  
 Safety goggles.
- **Body protection:**  
 Protective clothing  
 Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** According to product specification
- **Smell:** Odourless
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range**  $> 320$  °C (CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether)
- **Flash point:** 61 °C
- **Auto-ignition temperature:** 455 °C (CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether)
- **pH** Not applicable.  
Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **dynamic at 20 °C:** 17400 mPas

(Contd. on page 8)



BE SURE. BUILD SURE.

Page 8/14

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

Trade name MC-DUR 1800 - Komponente A

(Contd. of page 7)

· <b>Solubility</b>	
· <b>Water:</b>	Not miscible or difficult to mix
· <b>Steam pressure at 20 °C:</b>	0 hPa (CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether)
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C</b>	2.07 g/cm <sup>3</sup>
· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	
· <b>Thermal decomposition / conditions to be avoided:</b>	No decomposition if used according to specifications.
· <b>10.3 Possibility of hazardous reactions</b>	No dangerous reactions known
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.

(Contd. on page 9)

IE





BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

**Trade name MC-DUR 1800 - Komponente A**

(Contd. of page 8)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

**CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane**

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

**CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether**

Oral	LD50	11400 mg/kg (rat)
Dermal	LD50	23000 mg/kg (rabbit) >2000 mg/kg (rat)

**CAS: 100-51-6 Benzyl alcohol**

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
	Dermal	LD50
Inhalative	LC50/4 h	>4178 mg/l (rat)

**CAS: 16096-31-4 1,6-hexene-diglycidylether**

Oral	LD50	>8500 mg/kg (rat)
Dermal	LD50	>4900 mg/kg (rat)

**CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives**

Oral	LD50	17100 mg/kg (rat)
------	------	-------------------

**CAS: 108-31-6 Maleic anhydride**

Oral	LD50	1090 mg/kg (rat)
Dermal	LD50	2620 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

(Contd. on page 10)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

**Trade name MC-DUR 1800 - Komponente A**

(Contd. of page 9)

- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 128-37-0	2,6-Di-tert-butyl-p-cresol	List II
CAS: 556-67-2	Octamethylcyclotetrasiloxane	List II
CAS: 556-67-2	octamethylcyclotetrasiloxane	List II

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane**

LC50/96h >100 mg/l (Daphnia magna)

EC50/96h >100 mg/l (Leucidus idus)

**CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether**

LC50/72h >11 mg/l (algae)

IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (Oncorhynchus mykiss)

1.3 mg/l (fish)

EC50/48h 2.1 mg/l (daphnia)

1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

**CAS: 100-51-6 Benzyl alcohol**

IC50/72h 700 mg/l (algae)

LC50/96h 460 mg/l (Pimephales promelas)

10 mg/l (Lepomis macrochirus)

**CAS: 16096-31-4 1,6-hexene-diglycidylether**

LC50/96h 30 mg/l (Leucidus idus)

EC50/48h 47 mg/l (Daphnia magna)

**CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives**

EbC50/72h 843 mg/l (Pseudokirchneriella subcapitata)

LC50/96h >5000 mg/l (Oncorhynchus mykiss)

1800 mg/l (Lepomis macrochirus)

EC50 >100 mg/l (BEL)

NOEC 500 mg/l (Pseudokirchneriella subcapitata)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

Trade name MC-DUR 1800 - Komponente A

(Contd. of page 10)

- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.

#### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP13	Sensitising
HP14	Ecotoxic

- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN3082
- **14.2 UN proper shipping name**
- **ADR, IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivatives)
- **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxide derivatives), MARINE POLLUTANT

(Contd. on page 12)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

Trade name MC-DUR 1800 - Komponente A

(Contd. of page 11)

· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR</b>	
· <b>Class</b>	9 (M6) Miscellaneous dangerous substances and articles.
· <b>Label</b>	9
-----	
· <b>IMDG, IATA</b>	
· <b>Class</b>	9 Miscellaneous dangerous substances and articles.
· <b>Label</b>	9
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	III
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	Yes
	Symbol (fish and tree)
· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>Special marking (IATA):</b>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	
	Warning: Miscellaneous dangerous substances and articles.
· <b>Kemler Number:</b>	90
· <b>EMS Number:</b>	F-A, S-F
· <b>Stowage Category</b>	A
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	
	Not applicable.
· <b>Transport/Additional information:</b>	
-----	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	(-)
-----	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/14

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

Trade name MC-DUR 1800 - Komponente A

(Contd. of page 12)

- **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H302 Harmful if swallowed.
  - H314 Causes severe skin burns and eye damage.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.

(Contd. on page 14)



BE SURE. BUILD SURE.

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025

Version number 63 (replaces version 62)

Revision: 15.04.2025

**Trade name MC-DUR 1800 - Komponente A**

(Contd. of page 13)

H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H360F May damage fertility.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.  
 EUH071 Corrosive to the respiratory tract.  
 EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

18.10.2021

· **Version number of previous version:**

62

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Resp. Sens. 1: Respiratory sensitisation – Category 1  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Skin Sens. 1A: Skin sensitisation – Category 1A  
 Repr. 1B: Reproductive toxicity – Category 1B  
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**