



BE SURE. BUILD SURE.

Page 1/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 1800 TX-AS - Komponente B**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy coating
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.
Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05 GHS07

(Contd. on page 2)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** Benzyl alcohol
Isophorone diamine
polymer amine terminated
Polyoxypropylenediamine
Tetraethylenepentamine
- **Hazard statements** H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements** P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

Dangerous components:

CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	30-60%
EC number: 949-140-2	polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥10-<25%

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 2)

CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine Skin Corr. 1B, H314; Aquatic Chronic 3, H412	≥5-<10%
CAS: 90640-66-7 EINECS: 292-587-7 Reg.nr.: 01-2119487290-37	Tetraethylenepentamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≥2.5-<5%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	≥3-<5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 3)

- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** None.
- **Storage class** 8A

IE

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require**

monitoring at the workplace: *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

· **DNELs**

CAS: 100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL) 110 mg/m ³ (Ark)

CAS: 2855-13-2 Isophorone diamine

Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m ³ (ArL)

CAS: 9046-10-0 Polyoxypropylenediamine

Oral	DNEL	0.04 mg/kg bw/Tag (ArL)
Dermal	DNEL	2.5 mg/kg bw/day (ArL)

CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Inhalative	DNEL	0.31 mg/m ³ (ArL)
------------	------	------------------------------

· **PNECs**

CAS: 100-51-6 Benzyl alcohol

PNEC	0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment)

CAS: 2855-13-2 Isophorone diamine

PNEC	0.006 mg/l (Mew) 0.06 mg/l (Freshwater)
PNEC	0.578 mg/kg dwt (Sediment) 5.784 mg/kg dwt (Fresh water sediment)

CAS: 9046-10-0 Polyoxypropylenediamine

PNEC	7.5 mg/l (Sewage Treatment Plant) 0.015 mg/l (Fresh water)
PNEC	0.0176 mg/kg dwt (Bod) 0.125 mg/kg dwt (Sediment)

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 5)

	0.132 mg/kg dwt (Fresh water sediment)
CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol	
PNEC	0.2 mg/l (Sewage Treatment Plant)
	0.0084 mg/l (Mew)
	0.084 mg/l (Freshwater)

- **Additional information:** *The lists that were valid during the compilation were used as basis.*
- **8.2 Exposure controls**
- **Appropriate engineering controls** *No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** *Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.*
- **Breathing equipment:** *If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.*
- **Hand protection** *Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves** *You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.
Nitrile rubber
Recommended material thickness: ≥ 0.4 mm*
- **Penetration time of glove material** *The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.
The following applies to all other gloves:
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.
Nitrile rubber
Material thickness: ≥ 0.40 mm
Penetration time: ≥ 480 min
Butyl rubber:
Material thickness: ≥ 0.5 mm*

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 6)

· **Eye/face protection**

Penetration time: ≥ 480 min

Tight-fitting safety goggles.

Safety goggles.

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Yellow

· **Smell:**

Amine-like

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

205.4 °C (CAS: 100-51-6 Benzyl alcohol)

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

1.3 Vol % (CAS: 100-51-6 Benzyl alcohol)

· **Upper:**

13 Vol % (CAS: 100-51-6 Benzyl alcohol)

· **Flash point:**

101 °C (CAS: 100-51-6 Benzyl alcohol)

· **Auto-ignition temperature:**

380 °C (CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

· **Decomposition temperature:**

Not determined.

· **pH**

Mixture reacts violently with water.

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic:**

Not determined.

· **Solubility**

· **Water:**

Fully miscible

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Steam pressure at 20 °C:**

0.1 hPa (CAS: 100-51-6 Benzyl alcohol)

· **Vapour pressure at 50 °C:**

0.7 hPa

· **Density and/or relative density**

· **Density at 20 °C**

1.03 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

(Contd. on page 8)

IE



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 7)

· 9.2 Other information

· Appearance:

· Form:

Viscous

· Important information on protection of health and environment, and on safety.

· Self-inflammability:

Product is not selfigniting.

· Explosive properties:

Product is not explosive.

· Change in condition

· Evaporation rate

Not determined.

· Information with regard to physical hazard classes

· Explosives

Void

· Flammable gases

Void

· Aerosols

Void

· Oxidising gases

Void

· Gases under pressure

Void

· Flammable liquids

Void

· Flammable solids

Void

· Self-reactive substances and mixtures

Void

· Pyrophoric liquids

Void

· Pyrophoric solids

Void

· Self-heating substances and mixtures

Void

· Substances and mixtures, which emit flammable gases in contact with water

Void

· Oxidising liquids

Void

· Oxidising solids

Void

· Organic peroxides

Void

· Corrosive to metals

Void

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity

No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

No dangerous reactions known

· 10.4 Conditions to avoid

No further relevant information available.

· 10.5 Incompatible materials:

No further relevant information available.

· 10.6 Hazardous decomposition products:

No dangerous decomposition products known

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 8)

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values that are relevant for classification:**

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

CAS: 2855-13-2 Isophorone diamine

Oral	LD50	1030 mg/kg (ATE) 1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit) >2000 mg/kg (rat)

CAS: 9046-10-0 Polyoxypropylenediamine

Oral	LD50	2855 mg/kg (Rat)
Dermal	LD50	2980 mg/kg (Kan)

CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Oral	LD50	mg/kg (rat)
	NOAEL	15 mg/kg (rat)

· **Skin corrosion/irritation** Causes severe skin burns and eye damage.

· **Serious eye damage/irritation** Causes serious eye damage.

· **Respiratory or skin sensitisation** May cause an allergic skin reaction.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 9)

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (<i>Pimephales promelas</i>) 10 mg/l (<i>Lepomis macrochirus</i>)

CAS: 2855-13-2 Isophorone diamine

LC50/96h	110 mg/l (<i>Leucidus idus</i>)
EC50	1120 mg/l (<i>Pseudomonas putida</i>)
EC50/48h	23 mg/l (<i>Daphnia magna</i>)
NOEC	1.5 mg/l (<i>Desmodesmus subspicatus</i>) 3 mg/l (<i>Daphnia magna</i>)
ErC50/72h	>50 mg/l (<i>Desmodesmus subspicatus</i>)

CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

EC50/72h	84 mg/l (<i>Desmodesmus subspicatus</i>)
LC50/96h	175 mg/l (<i>Cyp</i>) 718 mg/l (<i>Daphnia magna</i>)
NOEC	2 mg/l (BEL) 6.25 mg/l (<i>Desmodesmus subspicatus</i>)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 10)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

HP6	Acute Toxicity
HP8	Corrosive
HP13	Sensitising
HP14	Ecotoxic

· **Uncleaned packagings:**

· **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN2289

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA** ISOPHORONEDIAMINE solution

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class** 8 (C7) Corrosive substances.

· **Label** 8

· **IMDG, IATA**

· **Class** 8 Corrosive substances.

· **Label** 8

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Corrosive substances.

· **Kemler Number:** 80

· **EMS Number:** F-A, S-B

· **Stowage Category** A

· **Segregation Code** SG35 Stow "separated from" SGG1-acids

· **14.7 Maritime transport in bulk according to**

IMO instruments Not applicable.

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 11)

· Transport/Additional information:

· ADR

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category**

3

· **Tunnel restriction code**

E

· IMDG

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 2289 ISOPHORONEDIAMINE SOLUTION, 8, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **REGULATION (EC) No 1907/2006 ANNEX XVII**

Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

(Contd. of page 12)

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

16.10.2021

· **Version number of previous version:**

39

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. on page 14)



BE SURE. BUILD SURE.

Page 14/14

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 40 (replaces version 39)

Revision: 15.09.2024

Trade name MC-DUR 1800 TX-AS - Komponente B

· * **Data compared to the
previous version altered.**

(Contd. of page 13)

IE