



BE SURE. BUILD SURE.

Page 1/14

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** MC-DUR 1900 - Komponente A

· **Article number:** 182

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Coating
Epoxy coating

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360F May damage fertility.

STOT RE 2 H373 May cause damage to the lung through prolonged or repeated exposure.
Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

IE



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 1)

· **Hazard pictograms**



GHS07 GHS08 GHS09

· **Signal word**

Danger

· **Hazard-determining components of labelling:**

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane

Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

Quartz sand

4,4'-Methylenediphenyldiglycidyl ether

Polyol epoxy hybrid

Hydrocarbons, C9-unsaturated, polymerised

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

oxirane, 2-(chloromethyl)-, polymer with α -hydro- ω -hydroxypoly[oxy(methyl-1,2-ethanediyl)]

Polymer with epoxy-functional groups

1,6-hexene-diglycidylether

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360F May damage fertility.

H373 May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

· **Additional information:**

EUH205 Contains epoxy constituents. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/14

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

· vPvB:

Not applicable.

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description:

Resin mixture with colouring agents.

Mixture consisting of the following components.

· Dangerous components:

CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<25%
CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥10-<25%
	Polyol epoxy hybrid Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH205	≥10-<20%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz sand STOT RE 1, H372	<10%
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥2.5-<10%
CAS: 13463-67-7 EINECS: 236-675-5	Titanium dioxide Carc. 2, H351	≥1-<5%
CAS: 9072-62-2	oxirane, 2-(chloromethyl)-, polymer with α-hydro-ω-hydroxypoly[oxy(methyl-1,2-ethanediyl)] Eye Irrit. 2, H319; Skin Sens. 1B, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥2.5-<5%
CAS: 68609-97-2 EINECS: 271-846-8	Oxirane, mono((C12-14-alkyloxy)methyl)derivatives Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<2.5%
CAS: 71302-83-5	Hydrocarbons, C9-unsaturated, polymerised Asp. Tox. 1, H304; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	≥1-<1.5%
EC number: 953-811-5	Polymer with epoxy-functional groups Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%
CAS: 16096-31-4 EINECS: 240-260-4	1,6-hexene-diglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH205	≥0.1-<0.5%

(Contd. on page 4)

IE



BE SURE. BUILD SURE.

Page 4/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 3)

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 4)

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

· **Information about protection against explosions and fires:**

Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

No special requirements.

· **Further information about storage conditions:**

Keep container tightly closed in a well-ventilated place.

· **Storage class**

6.1C

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 14808-60-7 Quartz sand

OEL (Ireland)	Long-term value: 0.1 mg/m ³
BOELV (European Union)	Long-term value: 0.1* mg/m ³ *respirable fraction

· **DNELs**

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

Dermal	DNEL	0.75 mg/kg bw/day (ArL)
Inhalative	DNEL	0.49 mg/m ³ (ArL)

CAS: 16096-31-4 1,6-hexene-diglycidylether

Dermal	DNEL	2.8 mg/kg bw/day (ArL)
--------	------	------------------------

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 5)

Inhalative DNEL 4.9 mg/m³ (ArL)

· PNECs

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

PNEC	0.00072 mg/l (Mew)
	0.0072 mg/l (Freshwater)
PNEC	80.12 mg/kg dwt (Bod)
	6.677 mg/kg dwt (Sediment)
	66.77 mg/kg dwt (Fresh water sediment)

CAS: 16096-31-4 1,6-hexene-diglycidylether

PNEC	0.0115 mg/l (Fresh water)
	0.00115 mg/l (Mew)
PNEC	0.223 mg/kg dwt (Bod)
	0.0283 mg/kg dwt (Sediment)
	0.283 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· Breathing equipment:

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 6)

· **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· **Eye/face protection**

Tight-fitting safety goggles.

Safety goggles.

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

Pigmented

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

>200 °C (CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane)

· **Flash point:**

>93 °C

· **Auto-ignition temperature:**

184 °C

· **pH**

Not applicable.

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic at 20 °C:**

9000 mPas

(Contd. on page 8)

IE



BE SURE. BUILD SURE.

Page 8/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 7)

· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	<0.1 hPa (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight < 700)
· Density and/or relative density	
· Density at 20 °C	2.2 g/cm ³
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.

(Contd. on page 9)

IE



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 8)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

Oral	LD50	11400 mg/kg (rat)
------	------	-------------------

Dermal	LD50	23000 mg/kg (rabbit)
		>2000 mg/kg (rat)

Polyol epoxy hybrid

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

CAS: 13463-67-7 Titanium dioxide

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>10000 mg/kg (rabbit)
--------	------	-----------------------

Inhalative	LC50/4 h	>6.8 mg/l (rat)
------------	----------	-----------------

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

Oral	LD50	17100 mg/kg (rat)
------	------	-------------------

CAS: 16096-31-4 1,6-hexene-diglycidylether

Oral	LD50	>8500 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>4900 mg/kg (rat)
--------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/14

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 9)

11.2 Information on other hazards

Endocrine disrupting properties

CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II
CAS: 556-67-2	Octamethylcyclotetrasiloxane	List II
CAS: 556-67-2	octamethylcyclotetrasiloxane	List II

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl} oxirane

LC50/96h >100 mg/l (*Daphnia magna*)EC50/96h >100 mg/l (*Leucidus idus*)

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

LC50/72h >11 mg/l (algae)

IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (*Oncorhynchus mykiss*)

1.3 mg/l (fish)

EC50/48h 2.1 mg/l (*daphnia*)1.8 mg/l (*Daphnia magna*)ErC50/72h 11 mg/l (*Selenastrum capricornutum*)

Polyol epoxy hybrid

LC50/96h 67 mg/l (*Leucidus idus*)EC50/48h 90 mg/l (*Daphnia magna*)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

EbC50/72h 843 mg/l (*Pseudokirchneriella subcapitata*)LC50/96h >5000 mg/l (*Oncorhynchus mykiss*)1800 mg/l (*Lepomis macrochirus*)

EC50 >100 mg/l (BEL)

NOEC 500 mg/l (*Pseudokirchneriella subcapitata*)

CAS: 16096-31-4 1,6-hexene-diglycidylether

LC50/96h 30 mg/l (*Leucidus idus*)EC50/48h 47 mg/l (*Daphnia magna*)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

(Contd. on page 11)

IE



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 10)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP13	Sensitising
HP14	Ecotoxic

- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN3082
- **14.2 UN proper shipping name**
- **ADR, IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin)
- **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin), MARINE POLLUTANT

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 11)

· 14.3 Transport hazard class(es)	
· ADR	
· Class	9 (M6) Miscellaneous dangerous substances and articles.
· Label	9
· IMDG, IATA	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	
	Warning: Miscellaneous dangerous substances and articles.
· Kemler Number:	90
· EMS Number:	F-A, S-F
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	
	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 13)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 12)

· **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN), 9, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

(Contd. on page 14)



BE SURE. BUILD SURE.

Page 14/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 72 (replaces version 71)

Revision: 11.04.2025

Trade name MC-DUR 1900 - Komponente A

(Contd. of page 13)

H335 *May cause respiratory irritation.*
H351 *Suspected of causing cancer.*
H360F *May damage fertility.*
H372 *Causes damage to organs through prolonged or repeated exposure.*
H411 *Toxic to aquatic life with long lasting effects.*
H412 *Harmful to aquatic life with long lasting effects.*
EUH205 *Contains epoxy constituents. May produce an allergic reaction.*

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

13.10.2021

· **Version number of previous version:**

71

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

IE