



BE SURE. BUILD SURE.

Page 1/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** MC-DUR 2052 UVB - Komponente B

· **Article number:** 202

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Polyurethane resin  
Hardening agent/ Curing agent

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· **2.2 Label elements**

· **Labelling according to**

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS07

· **Signal word**

Warning

(Contd. on page 2)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

**Trade name MC-DUR 2052 UVB - Komponente B**

(Contd. of page 1)

- **Hazard-determining components of labelling:** Aliphatisches Polyisocyanat  
hexamethylene diisocyanate
- **Hazard statements** H332 Harmful if inhaled.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.
- **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
EUH204 Contains isocyanates. May produce an allergic reaction.
- **Additional information:**
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 28182-81-2	Aliphatisches Polyisocyanat Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	80-100%
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37-0000	hexamethylene diisocyanate Acute Tox. 2, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	<0.1%

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information** Remove soiled, soaked clothing immediately.
- **After inhalation** Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

Trade name **MC-DUR 2052 UVB - Komponente B**

(Contd. of page 2)

- **After swallowing** Do NOT induce vomiting. Rinse mouth with water. Medical attention required.
- **4.2 Most important symptoms and effects, both acute and delayed** Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.
- **4.3 Indication of any immediate medical attention and special treatment needed** Therapeutic measures: No information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** No special measures required.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** No dangerous materials are released.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application. For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored. At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people. For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling

(Contd. on page 4)



BE SURE. BUILD SURE.

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

**Trade name MC-DUR 2052 UVB - Komponente B**

(Contd. of page 3)

isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

**Information about protection against explosions and fires:**

Keep ignition sources away - do not smoke.

Protect from heat.

Do not store near heat sources.

**7.2 Conditions for safe storage, including any incompatibilities**

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

**Storage**

**Requirements to be met by storerooms and containers:**

Keep tightly closed in original packaging. Ventilate storage rooms well. Carefully close opened containers and store upright to prevent any leakage.

Storage temperature >5°C and <30°C

**Information about storage in one common storage facility:**

May be stored together with hazardous substances of other classes up to 200 kg.

**Further information about storage conditions:**

None.

**Storage class**

10

**7.3 Specific end use(s)**

No further relevant information available.

### SECTION 8: Exposure controls/personal protection

**8.1 Control parameters**

**Components with critical values that require monitoring at the workplace:**

**CAS: 822-06-0 hexamethylene diisocyanate**

OEL (Ireland) Long-term value: 0.005 ppm  
as -NCO, Sens

**DNELs**

**CAS: 28182-81-2 Aliphatisches Polyisocyanat**

Inhalative DNEL 0.5 mg/m<sup>3</sup> (Workers) (long term local)  
1 mg/m<sup>3</sup> (kei) (acute local eff)

**CAS: 822-06-0 hexamethylene diisocyanate**

Inhalative DNEL 0.5 mg/m<sup>3</sup> (ArL)

(Contd. on page 5)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

Trade name MC-DUR 2052 UVB - Komponente B

(Contd. of page 4)

<b>· PNECs</b>	
<b>CAS: 28182-81-2 Aliphatisches Polyisocyanat</b>	
PNEC aqua	12.7 µg/l ( <i>Daphnia magna</i> ) (marine)
PNEC	38.28 mg/l (kei) (STP)
<b>CAS: 822-06-0 hexamethylene diisocyanate</b>	
PNEC	100 mg/l (Sewage Treatment Plant) 0.0199 mg/l (Mew) 0.199 mg/l (Freshwater)
PNEC	8884 mg/kg dwt (Bod) 4455 mg/kg dwt (Marine water sediment) 44551 mg/kg dwt (Fresh water sediment)

- Additional information:** The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls**
- Appropriate engineering controls** No further data; see section 7.
- Individual protection measures, such as personal protective equipment**
- General protective and hygienic measures** Do not smoke, eat or drink while working. Have eye wash equipment ready.  
Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.  
Do not store food in the work area. Wash hands before breaks and at the end of work.
- Breathing equipment:** Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.  
If applicable, further recommendations for respiratory protection can be found in the appendix.  
In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.
- Hand protection** Suitable materials for protective gloves; EN 374:  
Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min.  
Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min.  
Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min.  
Recommendation: Dispose of contaminated gloves.
- Material of gloves** The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- Penetration time of glove material** Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min.  
Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min.  
Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min.
- Eye/face protection** Wear safety goggles/face protection.

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

Trade name MC-DUR 2052 UVB - Komponente B

(Contd. of page 5)

- **Body protection:** Wear suitable protective clothing when working.  
In case of hypersensitivity of the skin, handling of the product is not recommended.

#### SECTION 9: Physical and chemical properties

##### · 9.1 Information on basic physical and chemical properties

###### · General Information

- **Colour:** Yellowish
- **Smell:** Recognisable
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range:** Not determined
- **Flash point:** 158 °C
- **pH:** Not applicable.  
Not determined.
- **Viscosity:**
- **Kinematic viscosity:** Not determined.
- **dynamic at 20 °C:** 2500 mPas
- **Solubility:**
- **Water:** Not miscible or difficult to mix  
Fully miscible
- **Steam pressure at 20 °C:** 0.00000003 hPa
- **Density and/or relative density:**
- **Density at 20 °C:** 1.17 g/cm<sup>3</sup>

##### · 9.2 Other information

- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Explosive properties:** Product is not explosive.

##### · Information with regard to physical hazard classes

- **Explosives:** Void
- **Flammable gases:** Void
- **Aerosols:** Void
- **Oxidising gases:** Void
- **Gases under pressure:** Void
- **Flammable liquids:** Void
- **Flammable solids:** Void
- **Self-reactive substances and mixtures:** Void
- **Pyrophoric liquids:** Void
- **Pyrophoric solids:** Void
- **Self-heating substances and mixtures:** Void
- **Substances and mixtures, which emit flammable gases in contact with water:** Void

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

Trade name MC-DUR 2052 UVB - Komponente B

(Contd. of page 6)

- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

#### SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with amines
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

#### SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Harmful if inhaled.

· LD/LC50 values that are relevant for classification:

**CAS: 28182-81-2 Aliphatisches Polyisocyanat**

Oral LD50 >2500 mg/kg (rat) (OECD 423)

Dermal LD50 >2000 mg/kg (rat) (OECD 402)

**CAS: 822-06-0 hexamethylene diisocyanate**

Oral LD50 738 mg/kg (rat)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

**Trade name MC-DUR 2052 UVB - Komponente B**

(Contd. of page 7)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 28182-81-2 Aliphatisches Polyisocyanat**

ErC10/72h 370 mg/l (Desmodesmus subspicatus) (EU C.3)

ErC50/72h >1000 mg/l (Desmodesmus subspicatus) (EU C.3)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

**SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP13	Sensitising

(Contd. on page 9)





BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

**Trade name MC-DUR 2052 UVB - Komponente B**

(Contd. of page 8)

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

**SECTION 14: Transport information**

· **14.1 UN number or ID number**

· **ADR, ADN, IMDG, IATA**

Void

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA**

Void

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class**

Void

· **14.4 Packing group**

· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **UN "Model Regulation":**

Void

**SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**

No further relevant information available.

· **REGULATION (EC) No 1907/2006 ANNEX XVII**

Conditions of restriction: 3, 74

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

(Contd. on page 10)



BE SURE. BUILD SURE.

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

**Trade name MC-DUR 2052 UVB - Komponente B**

(Contd. of page 9)

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
EUH204 Contains isocyanates. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

13.10.2021

· **Version number of previous version:**

44

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Acute Tox. 2: Acute toxicity – Category 2  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Resp. Sens. 1: Respiratory sensitisation – Category 1

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/11

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Article 31**

Printing date 11.04.2025

Version number 45 (replaces version 44)

Revision: 11.04.2025

**Trade name MC-DUR 2052 UVB - Komponente B**

(Contd. of page 10)

*Skin Sens. 1: Skin sensitisation – Category 1*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

**· \* Data compared to the  
previous version altered.**

IE