

Page 1/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name MC-DUR 2496 CTP Tunnel - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Polyurethane lacquer

1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8

D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Warning

· Hazard-determining

components of labelling: tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester and decanedioic acid,(1,2,2,6,6-pentamethyl-4-

piperidinyl) methyl ester

(Contd. on page 2)



Page 2/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

#### Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 1)

· **Hazard statements** H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

• Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

· Additional information: EUH211 Warning! Hazardous respirable droplets may be formed

when sprayed. Do not breathe spray or mist.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· **Description:** Resin mixture.

Mixture consisting of the following components.

· Dangerous components:		
CAS: 136210-30-5 ELINCS: 429-270-1 Reg.nr.: 01-0000017556-64- xxxx	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl) bis-DL-aspartate Skin Sens. 1, H317; Aquatic Chronic 3, H412	30-60%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	10-30%
CAS: 1332-37-2 EINECS: 215-570-8	Iron oxide substance with a Community workplace exposure limit	<1.5%
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	≥0.25-<1.5%
CAS: 222417-26-7	Polyacrylate Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	≥0.25-<1%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40- XXXX	Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester and decanedioic acid,(1,2,2,6,6-pentamethyl-4-piperidinyl) methyl ester  Repr. 2, H361; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.1-<0.25%

(Contd. on page 3)



Page 3/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 29.06.2024 Printing date 29.06.2024 Version number 26 (replaces version 25)

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 2)

### SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information Remove soiled, soaked clothing immediately.

· After inhalation Remove person to fresh air, keep warm, allow to rest; if breathing

is difficult, seek medical attention.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at

least 10 minutes) with water that is as lukewarm as possible.

Consult an ophthalmologist.

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

· 4.3 Indication of any

immediate medical attention

and special treatment needed Therapeutic measures: No information available.

### SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: No special measures required.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections No dangerous materials are released.



Page 4/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 29.06.2024 Printing date 29.06.2024 Version number 26 (replaces version 25)

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 3)

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas.

Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being

exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing

immediately.

· Information about protection

against explosions and fires: Keep ignition sources away - do not smoke.

reasons can be found in our technical data sheet.

Protect from heat.

Do not store near heat sources.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the

storage conditions that must be observed for quality assurance

· Storage

Requirements to be met by storerooms and containers:

Keep tightly closed in original packaging. Ventilate storage rooms

well. Carefully close opened containers and store upright to

prevent any leakage.

Storage temperature >5°C and <30°C

· Information about storage in

one common storage facility: May be stored together with hazardous substances of other

classes up to 200 kg.

· Further information about

storage conditions: · Storage class

None. 12

· 7.3 Specific end use(s)

No further relevant information available.

(Contd. on page 5)



Page 5/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 4)

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 1332-37-2 Iron oxide

OEL (Ireland) Short-term value: 2 mg/m³

Long-term value: 1 mg/m3

as Fe

· DNELs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Dermal DNEL 4 mg/kg bw/day (ArL)
Inhalative DNEL 28 mg/m³ (ArL)
112 mg/m³ (Ark)

· PNECs

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

PNEC 31.1 mg/l (Kla)

0.000013 mg/l (Mew)

0.00013 mg/l (Freshwater)

PNEC 0.1 mg/kg dwt (Bod)

0.02 mg/kg dwt (Marine water sediment)

0.21 mg/kg dwt (Fresh water sediment)

• Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls
Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Do not smoke, eat or drink while working. Have eye wash

equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and

skin.

Do not store food in the work area. Wash hands before breaks and

at the end of work.

· Breathing equipment: Respiratory protection required at insufficiently ventilated

workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-

term work.

If applicable, further recommendations for respiratory protection

can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic

bronchitis), handling of the product is not recommended.

· Hand protection Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluororubber - FKM: thickness >0.4mm; breakthrough time

*≥*480min.

(Contd. on page 6)



Page 6/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 29.06.2024 Printing date 29.06.2024 Version number 26 (replaces version 25)

### Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 5)

Multi-layer glove - PE/EVAL/PE; Breakthrough time >480 min.

Recommendation: Dispose of contaminated gloves.

· Material of gloves The selection of the suitable gloves does not only depend on the

material, but also on further marks of quality and varies from

manufacturer to manufacturer.

Penetration time of glove

material Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min.

Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time

Multi-layer glove - PE/EVAL/PE; Breakthrough time ≥480 min.

· Eye/face protection Wear safety goggles/face protection.

· Body protection: Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not

recommended.

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: According to product specification

· Smell: Characteristic Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 185 °C (CAS: 136210-30-5 tetraethyl-N,N'-

(methylenedicyclohexane-4,1-diyl)bis-DL-

aspartate)

· Flash point: Not applicable

Auto-ignition temperature: 375 °C (CAS: 136210-30-5 tetraethyl-N,N'-

(methylenedicyclohexane-4,1-diyl)bis-DL-

aspartate) Not applicable.

Not determined.

· Viscosity:

· pH

· Kinematic viscosity Not determined. · dynamic: Not determined.

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0 hPa (CAS: 7727-43-7 barium sulphate, natural)

· Density and/or relative density

· Density at 20 °C 1.55 g/cm<sup>3</sup>

· 9.2 Other information

· Appearance:

Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting.

(Contd. on page 7)



Page 7/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

#### Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 6)

Explosive properties:	Product is not explosive.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

## **SECTION 10: Stability and reactivity**

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

## **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Oral LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.1)
Dermal LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.3)

(Contd. on page 8)



Page 8/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

### Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 7)

 Oral
 LD50
 >5000 mg/kg (rat)

 Dermal
 LD50
 >10000 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 >6.8 mg/l (rat)

CAS: 13463-67-7 titanium dioxide

• Skin corrosion/irritation Based on available data, the classification criteria are not met. • Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

**sensitisation** May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol List II

## **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

LC50/96h 66 mg/l (Danio rerio) (OECD 203)

EC50 3110 mg/l (BEL)

EC50/48h 88.6 mg/l (Daphnia magna) NOEC 0.01 mg/l (Daphnia magna)

ErC50/72h 113 mg/l (Scenedesmus subspicatus)

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow product to reach ground water, water bodies or

sewage system.

(Contd. on page 9)



Page 9/11

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 8)

Danger to drinking water if even small quantities leak into soil.

## **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

• **Recommendation**Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

	g	
· European	uropean waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
08 01 00	wastes from MFSU and removal of paint and varnish	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
HP13	Sensitising	
HP14	Ecotoxic	

· Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
	VOIG	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi IMO instruments	ing to Not applicable.	
UN "Model Regulation":	Void	

(Contd. on page 10)



Page 10/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 29.06.2024 Printing date 29.06.2024 Version number 26 (replaces version 25)

Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 9)

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture REGULATION (EC) No No further relevant information available.

1907/2006 ANNEX XVII

Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

A Chemical Safety Assessment has not been carried out. assessment:

#### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Flammable liquid and vapour. · Relevant phrases H226

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

Suspected of damaging fertility or the unborn child. H361

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. H412

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing data

specification sheet: Environment protection department.

(Contd. on page 11)



Page 11/11

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.06.2024 Version number 26 (replaces version 25) Revision: 29.06.2024

#### Trade name MC-DUR 2496 CTP Tunnel - Komponente A

(Contd. of page 10)

· Date of previous version: 18.10.2021

· Version number of previous

version:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity - Category 2 Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard -

Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 3

\* \* Data compared to the previous version altered.