



BE SURE. BUILD SURE.

Page 1/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 2496 CTP Tunnel - Komponente B**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Application of the substance / the mixture

Polyurethane resin
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word

Warning

(Contd. on page 2)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 1)

- **Hazard-determining components of labelling:** Aliphatisches Polyisocyanat
hexamethylene diisocyanate
- **Hazard statements** H226 Flammable liquid and vapour.
H332 Harmful if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
- **Precautionary statements**
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- **Additional information:** EUH401 To avoid risks to human health and the environment, comply with the instructions for use.
EUH204 Contains isocyanates. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Active substance with propellant.
Mixture consisting of the following components.

· **Dangerous components:**

CAS: 28182-81-2	Aliphatisches Polyisocyanat Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	60-80%
CAS: 123-86-4 EINECS: 204-658-1	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	≥10-<20%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥10-<20%

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 2)

CAS: 108-32-7 EINECS: 203-572-1	Propylene carbonate Eye Irrit. 2, H319	<2.5%
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37-0000	hexamethylene diisocyanate Acute Tox. 2, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	<0.1%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information**

Remove soiled, soaked clothing immediately.

· **After inhalation**

Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.

· **After skin contact**

In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

· **After eye contact**

Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.

· **After swallowing**

Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Therapeutic measures: No information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

· **5.2 Special hazards arising from the substance or mixture**

Can be released in case of fire
Carbon monoxide (CO)
Nitrogen oxides (NOx)
Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen cyanide (HCN)

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name **MC-DUR 2496 CTP Tunnel - Komponente B**

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** *Wear self-contained breathing apparatus.*

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Ensure adequate ventilation
Use breathing protection against the effects of fumes/dust/aerosol.*
- **6.2 Environmental precautions:** *Prevent material from reaching sewage system, holes and cellars.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.*
- **6.4 Reference to other sections** *See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Ensure sufficient air exchange and/or extraction in the work areas.
Air extraction is required for spray application.
For solid products: Avoid dust formation and dust deposits.
Air limit values mentioned in section 8 must be monitored.
At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.
For products containing solvents: Explosion protection required.
The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.
Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.*
- **Information about protection against explosions and fires:** *Keep ignition sources away - do not smoke.
Protect from heat.
Do not store near heat sources.*

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 4)

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

· Storage

· Requirements to be met by storerooms and containers:

Keep tightly closed in original packaging. Ventilate storage rooms well. Carefully close opened containers and store upright to prevent any leakage.

Storage temperature >5°C and <30°C

· Information about storage in one common storage facility:

May be stored together with hazardous substances of other classes up to 200 kg.

· Further information about storage conditions:

Keep container tightly closed in a well-ventilated place.

· Storage class

3

· 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 123-86-4 n-Butyl acetate

OEL (Ireland) Short-term value: 723 mg/m³, 150 ppm
Long-term value: 241 mg/m³, 50 ppm
IOELV

IOELV (European Union) Short-term value: 723 mg/m³, 150 ppm
Long-term value: 241 mg/m³, 50 ppm

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

OEL (Ireland) Short-term value: 550 mg/m³, 100 ppm
Long-term value: 275 mg/m³, 50 ppm
Skin, IOELV

IOELV (European Union) Short-term value: 550 mg/m³, 100 ppm
Long-term value: 275 mg/m³, 50 ppm
Skin

CAS: 822-06-0 hexamethylene diisocyanate

OEL (Ireland) Long-term value: 0.005 ppm
as -NCO, Sens

· DNELs

CAS: 28182-81-2 Aliphatisches Polyisocyanat

Inhalative	DNEL	0.5 mg/m ³ (Workers) (long term local) 1 mg/m ³ (kei) (acute local eff)
------------	------	--------------------------------------------------------------------------------------------------

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 5)

CAS: 123-86-4 n-Butyl acetate

Inhalative DNEL 480 mg/m³ (ArL)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Dermal DNEL 153.5 mg/kg bw/day (ArL)

Inhalative DNEL 275 mg/m³ (ArL)

CAS: 822-06-0 hexamethylene diisocyanate

Inhalative DNEL 0.5 mg/m³ (ArL)

· PNECs

CAS: 28182-81-2 Aliphatisches Polyisocyanat

PNEC aqua 12.7 µg/l (*Daphnia magna*) (marine)

PNEC 38.28 mg/l (kei) (STP)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

PNEC 0.635 mg/l (Fresh water)

100 mg/l (Kla)

0.0635 mg/l (Mew)

PNEC 0.29 mg/kg dwt (Bod)

0.329 mg/kg dwt (Marine water sediment)

3.29 mg/kg dwt (Fresh water sediment)

CAS: 822-06-0 hexamethylene diisocyanate

PNEC 100 mg/l (Sewage Treatment Plant)

0.0199 mg/l (Mew)

0.199 mg/l (Freshwater)

PNEC 8884 mg/kg dwt (Bod)

4455 mg/kg dwt (Marine water sediment)

44551 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Do not smoke, eat or drink while working. Have eye wash equipment ready.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Do not store food in the work area. Wash hands before breaks and at the end of work.

· Breathing equipment:

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.

If applicable, further recommendations for respiratory protection can be found in the appendix.

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 6)

· Hand protection

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

Suitable materials for protective gloves; EN 374:

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluororubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Multi-layer glove - PE/EVAL/PE ; Breakthrough time $\geq 480\text{ min}$.

Recommendation: Dispose of contaminated gloves.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluoro rubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Multi-layer glove - PE/EVAL/PE ; Breakthrough time $\geq 480\text{ min}$.

· Eye/face protection

Wear safety goggles/face protection.

· Body protection:

Wear suitable protective clothing when working.

In case of hypersensitivity of the skin, handling of the product is not recommended.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:

Dark brown

· Smell:

Characteristic

· Melting point/freezing point:

Not determined

· Boiling point or initial boiling point and boiling range

124-128 °C (CAS: 123-86-4 n-Butyl acetate)

· Lower and upper explosion limit

· Lower:

1.5 Vol % (CAS: 108-65-6 2-methoxy-1-methylethyl acetate)

· Upper:

10.4 Vol % (CAS: 123-86-4 n-Butyl acetate)

· Flash point:

27 °C

· Auto-ignition temperature:

315 °C (CAS: 108-65-6 2-methoxy-1-methylethyl acetate)

· pH

Not applicable.

Not determined.

· Viscosity:

· Kinematic viscosity

Not determined.

· dynamic:

Not determined.

· Solubility

· Water:

Hydrolized

· Steam pressure at 20 °C:

13 hPa (CAS: 123-86-4 n-Butyl acetate)

· Vapour pressure at 50 °C:

55 hPa

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 7)

· **Density and/or relative density**

· **Density at 20 °C** 1.12 g/cm³

· **9.2 Other information**

· **Appearance:**

· **Form:** Fluid

· **Important information on protection of health and environment, and on safety.**

· **Self-inflammability:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive.

· **Information with regard to physical hazard classes**

· **Explosives** Void

· **Flammable gases** Void

· **Aerosols** Void

· **Oxidising gases** Void

· **Gases under pressure** Void

· **Flammable liquids** Flammable liquid and vapour.

· **Flammable solids** Void

· **Self-reactive substances and mixtures** Void

· **Pyrophoric liquids** Void

· **Pyrophoric solids** Void

· **Self-heating substances and mixtures** Void

· **Substances and mixtures, which emit flammable gases in contact with water** Void

· **Oxidising liquids** Void

· **Oxidising solids** Void

· **Organic peroxides** Void

· **Corrosive to metals** Void

· **Desensitised explosives** Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** Reacts with amines

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 8)

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values that are relevant for classification:**

CAS: 28182-81-2 Aliphatisches Polyisocyanat

Oral	LD50	>2500 mg/kg (rat) (OECD 423)
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)

CAS: 123-86-4 n-Butyl acetate

Oral	LD50	10760 mg/kg (rat)
Dermal	LD50	>14112 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8500 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

CAS: 108-32-7 Propylene carbonate

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

CAS: 822-06-0 hexamethylene diisocyanate

Oral	LD50	738 mg/kg (rat)
------	------	-----------------

· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

· **Respiratory or skin sensitisation** May cause an allergic skin reaction.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** May cause respiratory irritation.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 28182-81-2 Aliphatisches Polyisocyanat

ErC10/72h	370 mg/l (Desmodesmus subspicatus) (EU C.3)
ErC50/72h	>1000 mg/l (Desmodesmus subspicatus) (EU C.3)

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 9)

CAS: 123-86-4 n-Butyl acetate

IC50	356 mg/l (Bak)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus)
LC50/96h	18 mg/l (Pimephales promelas)
EC50/48h	44 mg/l (Daphnia magna)
NOEC	200 mg/l (Desmodesmus subspicatus)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

LC50/96h	134 mg/l (Oncorhynchus mykiss) 161 mg/l (Pimephales promelas)
EC50	>1000 mg/l (BEL)
EC50/48h	>500 mg/l (Daphnia magna)
NOEC	47.5 mg/l (Ory)
EC50/3d	>1000 mg/l (Selenastrum capricornutum)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 10)

HP13 Sensitising

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1993

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA**

FLAMMABLE LIQUID, N.O.S. (BUTYL ACETATES, 2-methoxy-1-methylethyl acetate)

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class**

· **Label**

3 (F1) Flammable liquids.

3

· **IMDG, IATA**

· **Class**

· **Label**

3 Flammable liquids.

3

· **14.4 Packing group**

· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

· **Kemler Number:**

· **EMS Number:**

· **Stowage Category**

Warning: Flammable liquids.

30

F-E, S-E

A

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

· **Excepted quantities (EQ)**

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

· **Transport category**

· **Tunnel restriction code**

3

D/E

· **IMDG**

· **Limited quantities (LQ)**

· **Excepted quantities (EQ)**

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 11)

	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (BUTYL ACETATES, 2-METHOXY-1-METHYLETHYL ACETATE), 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H226 Flammable liquid and vapour.
H302 Harmful if swallowed.

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.09.2024

Version number 23 (replaces version 22)

Revision: 04.09.2024

Trade name MC-DUR 2496 CTP Tunnel - Komponente B

(Contd. of page 12)

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH204 Contains isocyanates. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

12.04.2024

· **Version number of previous version:**

22

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 2: Acute toxicity – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

IE