



BE SURE. BUILD SURE.

Page 1/13

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** MC-DUR 2500 - Komponente B

· **Article number:** 1432

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Polyurethane lacquer
Hardening agent/ Curing agent

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 1)

Hazard pictograms



GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

Diphenylmethane diisocyanate, isomers and homologues
diphenylmethane-4,4'-di-isocyanate
Diphenylmethane-2,4'-diisocyanate
diphenylmethane-2,2'-diisocyanate

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P284 [In case of inadequate ventilation] wear respiratory protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Additional information:

EUH401 To avoid risks to human health and the environment, comply with the instructions for use.
EUH204 Contains isocyanates. May produce an allergic reaction.
As from 24 August 2023 adequate training is required before industrial or professional use.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.1 Substances

CAS No. Designation: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/13

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name **MC-DUR 2500 - Komponente B**

(Contd. of page 2)

· **Identification number(s):**· **EC number:** 202-966-0· **Index number:** 615-005-01-6· **3.2 Mixtures**· **Description:** Active substance with propellant.
Mixture consisting of the following components.· **Dangerous components:**

CAS: 9016-87-9	Diphenylmethane diisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	60-80%
CAS: 101-68-8 EINECS: 202-966-0 Reg.nr.: 01-2119457014-47	diphenylmethane-4,4'-di-isocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	10-30%
CAS: 5873-54-1 EINECS: 227-534-9	Diphenylmethane-2,4'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	≥5-<10%
CAS: 2536-05-2 EINECS: 219-799-4	diphenylmethane-2,2'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	<0.1%

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 3)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **General information** Remove, decontaminate and dispose of soiled, soaked clothing and shoes immediately.
- **After inhalation** Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
- **After skin contact** In case of contact with skin, preferably wash with polyethylene glycol-based cleaner or clean with plenty of warm water and soap. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.
- **After swallowing** Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

· 4.2 Most important symptoms and effects, both acute and delayed

Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.

- **4.3 Indication of any immediate medical attention and special treatment needed** No information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet.
- **5.2 Special hazards arising from the substance or mixture**
 - Can be released in case of fire
 - Carbon monoxide (CO)
 - Nitrogen oxides (NO_x)
 - Hydrogen cyanide (HCN)
 - (Traces)
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.

(Contd. on page 5)

IE



BE SURE. BUILD SURE.

Page 5/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name **MC-DUR 2500 - Komponente B**

(Contd. of page 4)

- **6.2 Environmental precautions:** *Prevent material from reaching sewage system, holes and cellars.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.*
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling*
 - See Section 8 for information on personal protection equipment.*
 - See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application.*
 - For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.*
 - At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.*
 - For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.*
 - Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.*
- **7.2 Conditions for safe storage, including any incompatibilities**
 - Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.*
- **Storage**
- **Requirements to be met by storerooms and containers:** *Store only in the original container.*
- **Further information about storage conditions:** *None.*
- **Storage class** *10*
- **7.3 Specific end use(s)** *No further relevant information available.*

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 5)

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues

OEL (Ireland)	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ as -NCO; Sens.
---------------	---

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

OEL (Ireland)	Long-term value: 0.005 ppm as -NCO; Sens
---------------	---

CAS: 5873-54-1 Diphenylmethane-2,4'-diisocyanate

OEL (Ireland)	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ as -NCO; Sens.
---------------	---

CAS: 2536-05-2 diphenylmethane-2,2'-diisocyanate

OEL (Ireland)	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ as -NCO; Sens.
---------------	---

· **DNELs**

CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues

Inhalative	DNEL	0.05 mg/m ³ (ArL)
------------	------	------------------------------

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

Dermal	DNEL	50 mg/kg bw/day (Ark)
Inhalative	DNEL	0.05 mg/m ³ (ArL)

CAS: 5873-54-1 Diphenylmethane-2,4'-diisocyanate

Inhalative	DNEL	0.05 mg/m ³ (ArL)
------------	------	------------------------------

· **PNECs**

CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues

PNEC	1 mg/l (Sewage Treatment Plant)
	0.1 mg/l (Mew)
	1 mg/l (Freshwater)
PNEC	1 mg/kg dwt (Bod)

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

PNEC	1 mg/l (Sewage Treatment Plant)
	0.1 mg/l (Mew)
	1 mg/l (Freshwater)
PNEC	1 mg/kg dwt (Bod)

CAS: 5873-54-1 Diphenylmethane-2,4'-diisocyanate

PNEC	1 mg/l (Sewage Treatment Plant)
	0.1 mg/l (Mew)

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 6)

	1 mg/l (Freshwater)
PNEC	1 mg/kg dwt (Bod)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· **Breathing equipment:**

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.

If applicable, further recommendations for respiratory protection can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

· **Hand protection**

Suitable materials for protective gloves; EN 374:

Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).

Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC definition): butyl rubber.

In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes according to EN374).

The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multi-layer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide sufficient protection for short periods of wear.

For solvent-free products:

Example:

Polychloroprene - CR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0.35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluoro rubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 7)

- **Material of gloves**
 - ≥480min.
 - Recommendation: Dispose of contaminated gloves.
 - Polychloroprene - CR
 - Nitrile rubber - NBR
 - Butyl rubber - IIR
 - Fluoro rubber - FKM
- **Penetration time of glove material**
 - Polychloroprene - CR: thickness ≥0.5mm; breakthrough time ≥480min.
 - Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time ≥480min.
 - Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min.
 - Fluoro rubber - FKM: Thickness ≥0.4mm; Breakthrough time ≥480min.
- **Eye/face protection**
 - Safety goggles with side protection in accordance with EN 166.
- **Body protection:**
 - Use chemical-resistant protective clothing.
 - In case of hypersensitivity of the skin, handling the product is not recommended.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Dark brown
- **Smell:** Characteristic
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** 190 °C (CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues)
- **Flash point:** 228 °C
- **Auto-ignition temperature:** 400 °C
- **pH** Not applicable.
Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **dynamic at 20 °C:** 145 mPas
- **Solubility**
- **Water:** Not miscible or difficult to mix
- **Steam pressure at 25 °C:** 0 hPa (CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues)
- **Density and/or relative density**
- **Density at 20 °C** 1.24 g/cm³
- **9.2 Other information**
- **Appearance:**
- **Form:** Liquid

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 8)

· **Important information on protection of health and environment, and on safety.**

· **Explosive properties:** Product is not explosive.

· **Information with regard to physical hazard classes**

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with amines
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

Oral	LD50	>10000 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Kan)
Inhalative	LC50/4 h	~450 mg/l (Rat)

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 9)

CAS: 9016-87-9 Diphenylmethane diisocyanate, isomers and homologues

Oral	LD50	>10000 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Rab)
Inhalative	LC50/4 h	~450 mg/l (Rat)

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>9400 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

EC50/24h	>1000 mg/l (Daphnia magna)
LC50/96h	>1000 mg/l (Brachydanio rerio)
NOEC	>1000 mg/l (Eisenia foetida)
	>10 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 10)

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, ADN, IMDG, IATA**

Void

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA**

Void

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class**

Void

· **14.4 Packing group**

· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 11)

· **14.6 Special precautions for user** *Not applicable.*

· **14.7 Maritime transport in bulk according to IMO instruments** *Not applicable.*

· **UN "Model Regulation":** *Void*

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture** *No further relevant information available.*

· **REGULATION (EC) No 1907/2006 ANNEX XVII** *Conditions of restriction: 3, 56a, 56b, 56c, 74*

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**
None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**
None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**
None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
None of the ingredients is listed.

· **15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H315 Causes skin irritation.*
 - H317 May cause an allergic skin reaction.*
 - H319 Causes serious eye irritation.*
 - H332 Harmful if inhaled.*
 - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
 - H335 May cause respiratory irritation.*

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 32 (replaces version 31)

Revision: 13.04.2025

Trade name MC-DUR 2500 - Komponente B

(Contd. of page 12)

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

17.10.2021

· **Version number of previous version:**

31

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**

IE