



BE SURE. BUILD SURE.

Page 1/12

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **MC-DUR 3500 F - Komponente B**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### 1.3 Application of the substance / the mixture

Mineral coating  
Hardening agent/ Curing agent

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +48612864565

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



GHS02 GHS07

(Contd. on page 2)

IE



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

**Trade name MC-DUR 3500 F - Komponente B**

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** methyl methacrylate  
butyl acrylate  
N-Hydroxyethyl-N-methyl-p-toluidine
- **Hazard statements** H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.
- **Precautionary statements** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· **Determination of endocrine-disrupting properties**

128-37-0 Butylated hydroxytoluene

List II

**SECTION 3: Composition/information on ingredients**

· **3.2 Mixtures**

· **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-70%
CAS: 141-32-2 EINECS: 205-480-7	butyl acrylate Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥20-≤30%

(Contd. on page 3)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

**Trade name MC-DUR 3500 F - Komponente B**

(Contd. of page 2)

CAS: 2082-81-7 EINECS: 218-218-1	tetramethylene dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<5%
CAS: 2842-44-6 EINECS: 220-638-5	N-Hydroxyethyl-N-methyl-p-toluidine Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<2.5%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene Skin Irrit. 2, H315; Eye Irrit. 2, H319	<0.5%

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information** Instantly remove any clothing soiled by the product.
- **After inhalation** Supply fresh air and call for doctor for safety reasons.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Seek medical treatment.
- **After swallowing** Do not induce vomiting; instantly call for medical help.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture** Can be released in case of fire  
Nitrogen oxides (NOx)  
Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation

(Contd. on page 4)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

**Trade name MC-DUR 3500 F - Komponente B**

(Contd. of page 3)

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or water bodies.  
Prevent material from reaching sewage system, holes and cellars.  
Inform respective authorities in case product reaches water or sewage system.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

## SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
The product is not flammable  
Fumes can combine with air to form an explosive mixture.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

Store in cool location.  
Store only in the original container.

· **Information about storage in one common storage facility:**

Not required.

· **Further information about storage conditions:**

Keep container tightly sealed.  
Store in cool, dry conditions in well sealed containers.  
Protect from heat and direct sunlight.

· **Storage class**

12

· **7.3 Specific end use(s)**

No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

**80-62-6 methyl methacrylate**

OEL (Ireland)

Short-term value: 100 ppm  
Long-term value: 50 ppm  
IOELV, Sens

(Contd. on page 5)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

**Trade name MC-DUR 3500 F - Komponente B**

(Contd. of page 4)

IOELV (European Union)	Short-term value: 100 ppm Long-term value: 50 ppm
<b>141-32-2 butyl acrylate</b>	
OEL (Ireland)	Short-term value: 53 mg/m <sup>3</sup> , 10 ppm Long-term value: 11 mg/m <sup>3</sup> , 2 ppm IOELV, Sens
IOELV (European Union)	Short-term value: 53 mg/m <sup>3</sup> , 10 ppm Long-term value: 11 mg/m <sup>3</sup> , 2 ppm

· **DNELs**

**128-37-0 Butylated hydroxytoluene**

Dermal	DNEL	8.3 mg/kg bw/day (ArL)
Inhalative	DNEL	5.8 mg/m <sup>3</sup> (ArL)

· **PNECs**

**128-37-0 Butylated hydroxytoluene**

PNEC	0.4 µg/l (Mew)
	4 µg/l (Suw)
PNEC	100 mg/l (Sewage Treatment Plant)
PNEC	1.04 mg/kg dwt (Bod)
	1.29 mg/kg dwt (Sediment)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.  
Instantly remove any soiled and impregnated garments.  
Wash hands during breaks and at the end of the work.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

Use breathing protection in case of insufficient ventilation.  
Self-contained breathing apparatus.  
Filter AX.

· **Hand protection**

Protective gloves.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
After use of gloves apply skin-cleaning agents and skin cosmetics.

· **Material of gloves**

Nitrile rubber, NBR  
Butyl rubber, BR  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

Trade name MC-DUR 3500 F - Komponente B

(Contd. of page 5)

- **Penetration time of glove material**                      *The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.*
- **Eye/face protection**                      *Safety glasses  
Tightly sealed safety glasses.*
- **Body protection:**                      *Protective work clothing.*

#### SECTION 9: Physical and chemical properties

##### · 9.1 Information on basic physical and chemical properties

###### · General Information

- **Colour:**                      *Transparent*
- **Smell:**                      *Unpleasant*
- **Melting point/freezing point:**                      *-48 °C*
- **Boiling point or initial boiling point and boiling range**                      *101 °C (80-62-6 methyl methacrylate)*
- **Lower and upper explosion limit**
- **Lower:**                      *1.2 Vol % (141-32-2 butyl acrylate)*
- **Upper:**                      *12.5 Vol % (80-62-6 methyl methacrylate)*
- **Flash point:**                      *10 °C*
- **Auto-ignition temperature:**                      *275 °C (141-32-2 butyl acrylate)*
- **pH**                      *Not applicable.  
Not determined.*
- **Viscosity:**
- **Kinematic viscosity at 20 °C**                      *21 s (ISO 3 mm)*
- **dynamic:**                      *Not determined.*
- **Solubility**
- **Water:**                      *Not miscible or difficult to mix*
- **Steam pressure at 20 °C:**                      *47 hPa (80-62-6 methyl methacrylate)*
- **Density and/or relative density**
- **Density at 20 °C**                      *0.93 g/cm<sup>3</sup>*

##### · 9.2 Other information

- **Appearance:**                      *SAPT > 55°C*
- **Form:**                      *Fluid*
- **Important information on protection of health and environment, and on safety.**
- **Explosive properties:**                      *Product is not explosive. However, formation of explosive air/steam mixtures is possible.*

##### · Information with regard to physical hazard classes

- **Explosives**                      *Void*
- **Flammable gases**                      *Void*
- **Aerosols**                      *Void*
- **Oxidising gases**                      *Void*
- **Gases under pressure**                      *Void*
- **Flammable liquids**                      *Highly flammable liquid and vapour.*

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

Trade name MC-DUR 3500 F - Komponente B

(Contd. of page 6)

- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

#### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** self-accelerating polymerization temperature => 100°C
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

#### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

##### 80-62-6 methyl methacrylate

Oral	LD50	>6000 mg/kg (Rat)
Dermal	LD50	>7550 mg/kg (rabbit)

##### 141-32-2 butyl acrylate

Oral	LD50	900 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)

##### 128-37-0 Butylated hydroxytoluene

Oral	LD50	>2930 mg/kg (rat)
	NOAEL	100 mg/kg (rat)

(Contd. on page 8)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

**Trade name MC-DUR 3500 F - Komponente B**

(Contd. of page 7)

Dermal	LD50	>5000 mg/kg (rabbit) >2000 mg/kg (rat)
--------	------	---

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

128-37-0 Butylated hydroxytoluene

List II

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**80-62-6 methyl methacrylate**

EC50/24h 502 mg/l (*Daphnia magna*)

LC50/96h 130 mg/l (*Pimephales promelas*)

191 mg/l (*Lepomis macrochirus*)

EC50/48h 69 mg/l (*Daphnia magna*)

**128-37-0 Butylated hydroxytoluene**

EC50/72h 0.5 mg/l (*Desmodesmus subspicatus*)

EC50 >10000 mg/l (BEL)

LC50/48h 0.61 mg/l (*Daphnia magna*)

NOEC 0.07 mg/l (*Daphnia magna*)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

(Contd. on page 9)





BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

**Trade name MC-DUR 3500 F - Komponente B**

(Contd. of page 8)

- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.*

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **European waste catalogue**

17 00 00	CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)
17 09 00	other construction and demolition wastes
17 09 03*	other construction and demolition wastes (including mixed wastes) containing hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 01	paper and cardboard packaging
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 02	plastic packaging
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP6	Acute Toxicity
HP13	Sensitising

- **Uncleaned packagings:**
- **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

### SECTION 14: Transport information

· <b>14.1 UN number or ID number</b>	
· <b>ADR, IMDG, IATA</b>	UN1247
· <b>14.2 UN proper shipping name</b>	
· <b>ADR, IMDG, IATA</b>	METHYL METHACRYLATE MONOMER, STABILIZED

(Contd. on page 10)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

Trade name **MC-DUR 3500 F - Komponente B**

(Contd. of page 9)

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class** 3 (F1) Flammable liquids.

· **Label** 3

· **IMDG, IATA**

· **Class** 3 Flammable liquids.

· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

· **Marine pollutant:** no

No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Kemler Number:** 33

· **EMS Number:** F-E, S-D

· **Stowage Category** C

· **Stowage Code** SW1 Protected from sources of heat.

SW2 Clear of living quarters.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category** 2

· **Tunnel restriction code** D/E

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, 3, II

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

Trade name MC-DUR 3500 F - Komponente B

(Contd. of page 10)

#### SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
  - H225 Highly flammable liquid and vapour.
  - H226 Flammable liquid and vapour.
  - H302 Harmful if swallowed.
  - H312 Harmful in contact with skin.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H319 Causes serious eye irritation.
  - H335 May cause respiratory irritation.

· Department issuing data specification sheet: Environment protection department.

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2023

Version number 30 (replaces version 29)

Revision: 21.04.2023

**Trade name MC-DUR 3500 F - Komponente B**

(Contd. of page 11)

- **Date of previous version:** 17.10.2021
- **Version number of previous version:** 29
- **Abbreviations and acronyms:** *RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*  
*ICAO: International Civil Aviation Organisation*  
*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*  
*IMDG: International Maritime Code for Dangerous Goods*  
*IATA: International Air Transport Association*  
*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*  
*EINECS: European Inventory of Existing Commercial Chemical Substances*  
*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*DNEL: Derived No-Effect Level (REACH)*  
*PNEC: Predicted No-Effect Concentration (REACH)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*Flam. Liq. 2: Flammable liquids – Category 2*  
*Flam. Liq. 3: Flammable liquids – Category 3*  
*Acute Tox. 4: Acute toxicity – Category 4*  
*Skin Irrit. 2: Skin corrosion/irritation – Category 2*  
*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*  
*Skin Sens. 1: Skin sensitisation – Category 1*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

- **\* Data compared to the previous version altered.**

IE