

Page 1/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier		
· Trade name	MC-DUR GLW - Komponente A	
 Article number: 1.2 Relevant identified uses of the substance or mixture 	1202	
and uses advised against • Application of the substance	No further relevant information available.	
/ the mixture	Epoxy coating	
• 1.3 Details of the supplier of • Manufacturer/Supplier:	the safety data sheet MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10	
	CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533	
 Informing department: 1.4 Emergency telephone 	msds@mc-bauchemie.de	
number:	Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)	
SECTION 2: Hazards identification		
 2.1 Classification of the subs Classification according to R 		

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· 2.2 Label elements

- · Labelling according to
- **Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



Danger

Signal word

(Contd. on page 2)

IE



Page 2/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Trade name MC-DUR GLW - Komponente A

		(Contd. of page 1)
· Hazard-determining		
components of labelling:	Polymer Epoxidh	parz-Addukt
	crystalline silica	
	Aminpolymer	
		camethylenediamine
 Hazard statements 		rious eye damage.
		an allergic skin reaction.
		amage to the lung through prolonged or repeated Route of exposure: Inhalation.
· Precautionary statements	P260	Do not breathe dust/fume/gas/mist/vapours/
Frecautionaly statements	1 200	spray.
	P261	Avoid breathing dust/fume/gas/mist/vapours/
		spray.
	P305+P351+P33	38 IF IN EYES: Rinse cautiously with water for
		several minutes. Remove contact lenses, if
		present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.
	P321	Specific treatment (see on this label).
	P362+P364	Take off contaminated clothing and wash it
		before reuse.
2.3 Other hazards		
Results of PBT and vPvB as		
· PBT:	Not applicable.	
· vPvB:	Not applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description:

Resin mixture with colouring agents. Mixture consisting of the following components.

 Dangerous compor 	nents:	
CAS: 14808-60-7	crystalline silica	10-30%
	STOT RE 1, H372	
CAS: 260549-92-6	Polymer Epoxidharz-Addukt	≥3-<10%
	Eye Dam. 1, H318	
CAS: 180583-06-6	Aminpolymer	≥1-<2.5%
	Skin Sens. 1, H317	
CAS: 112-57-2	3,6,9-triazaundecamethylenediamine	≥0.1-<0.25%
EINECS: 203-986-2	Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	
· Additional informat	<i>tion</i> For the wording of the listed hazard phrases refer to	section 16.

(Contd. on page 3)



Page 3/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 2)

SECTION 4: First aid measures

General information	Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
· After inhalation	Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
· After skin contact	In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
· After eye contact	Rinse opened eye for several minutes under running water. Call a doctor immediately
· After swallowing	Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.
 4.2 Most important symptoms and effects, both acute and 	
delayed	Advice for the doctor: Elementary aid, decontamination,

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.

symptomatic treatment.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
 5.3 Advice for firefighters
- · Protective equipment:

No special measures required.

SECTION 6: Accidental release measures

Not required.
Prevent material from reaching sewage system, holes and cellars. Dilute with much water.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

(Contd. on page 4)



Page 4/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 3)

7.1 Precau	itions for safe	
handling		Open and handle containers with care.
		Ventilation measures are required in rooms without sufficient exchange (e.g. closed rooms),
		because the occupational exposure limit values (see chapte
		could be exceeded. This must be avoided.
		Wear suitable personal protective equipment (see section 8). A
		contact with eyes, skin and clothing. Change contaminated damaged gloves and contaminated clothing immediately and w skin immediately. Mix slowly, partially covering the mix container. Pour carefully and slowly when repotting. Observe BGBau technical data sheet and practical guide for handling ep resins.
Informatio	on about protec	tion
		ires: Ensure sufficient air exchange and/or extraction in the worl areas. Take precautionary measures to avoid electrost discharges.
7.2 Condit	tions for safe s	torage, including any incompatibilities
Storage		
· Requirements to be met by		
	ns and containe	
	formation abou	Protect from heat and direct sunlight.
storage co		-
storage co Storage cl		6.1D
		6.1D
Storage cl	lass	
Storage cl	lass	6.1D re controls/personal protection
Storage cl SECTIOI 8.1 Contro	lass N 8: Exposul ol parameters	re controls/personal protection
Storage cl SECTION 8.1 Contro Componen	lass N 8: Exposul ol parameters nts with critica	re controls/personal protection
Storage cl SECTION 8.1 Contro Componen	lass N 8: Exposul ol parameters	re controls/personal protection
Storage cl SECTION 8.1 Contro Componen	lass N 8: Exposul ol parameters nts with critica 08-60-7 crystall	re controls/personal protection
Storage cl SECTION 8.1 Contro Componen CAS: 1480 OEL (Irelar	lass N 8: Exposul of parameters nts with critica 08-60-7 crystall nd)	re controls/personal protection I values that require monitoring at the workplace: ine silica Long-term value: 0.1 mg/m ³ Long-term value: 0.1* mg/m ³
Storage cl SECTION 8.1 Contro Componen CAS: 1480 OEL (Irelar	lass N 8: Exposul of parameters nts with critica 08-60-7 crystall nd)	re controls/personal protection I values that require monitoring at the workplace: ine silica Long-term value: 0.1 mg/m ³
Storage cl SECTION 8.1 Contro Componen CAS: 1480 OEL (Irelar	lass N 8: Exposul of parameters nts with critica 08-60-7 crystall nd)	re controls/personal protection I values that require monitoring at the workplace: ine silica Long-term value: 0.1 mg/m ³ Long-term value: 0.1* mg/m ³
Storage cl SECTION 8.1 Contro Componen CAS: 1480 OEL (Irelar BOELV (Eu DNELS	lass N 8: Exposul of parameters nts with critica 08-60-7 crystall nd) uropean Union)	re controls/personal protection I values that require monitoring at the workplace: ine silica Long-term value: 0.1 mg/m ³ Long-term value: 0.1* mg/m ³
Storage cl SECTION 8.1 Contro Componen CAS: 1480 OEL (Irelar BOELV (Eu DNELS CAS: 112-:	lass N 8: Exposul of parameters nts with critica 08-60-7 crystall nd) uropean Union) 57-2 3,6,9-triaz	re controls/personal protection I values that require monitoring at the workplace: ine silica Long-term value: 0.1 mg/m ³ Long-term value: 0.1* mg/m ³ *respirable fraction
Storage cl SECTIOI 8.1 Contro Componen CAS: 1480 OEL (Irelar BOELV (Eu DNELS CAS: 112- Oral	lass N 8: Exposul of parameters nts with critica 08-60-7 crystall nd) uropean Union) 57-2 3,6,9-triaz DNEL 0.53 mg.	re controls/personal protection I values that require monitoring at the workplace: ine silica Long-term value: 0.1 mg/m ³ Long-term value: 0.1* mg/m ³ *respirable fraction
Storage cl SECTION 8.1 Contro Componen CAS: 1480 OEL (Irelar BOELV (Eu DNELS CAS: 112-4 Oral Dermal	lass N 8: Exposul of parameters nts with critica 08-60-7 crystall nd) uropean Union) 57-2 3,6,9-triaz DNEL 0.53 mg.	re controls/personal protection I values that require monitoring at the workplace: ine silica Long-term value: 0.1 mg/m ³ Long-term value: 0.1* mg/m ³ *respirable fraction aundecamethylenediamine /kg bw/Tag (ArL) /kg bw/day (ArL)

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

PNEC 9.73 mg/l (BEL)

(Contd. on page 5)

IE



Page 5/11

IE

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Trade name MC-DUR GLW - Komponente A

0.0068 mg/l (Fresh v	(Contd. of pag vater)
0.0068 mg/l (Mew)	
PNEC 0.343 mg/kg dwt (Se	diment)
3.43 mg/kg dwt (Fres	,
Additional information:	The lists that were valid during the compilation were used as bas
8.2 Exposure controls	
Appropriate engineering	No firstbar data, and contian 7
controls	No further data; see section 7. sures, such as personal protective equipment
General protective and	sures, such as personal protective equipment
hygienic measures	Keep away from food, drink and animal feed.
	Remove soiled, soaked clothing immediately.
	Wash hands before breaks and at the end of work.
	Avoid contact with eyes and skin.
Breathing equipment:	If workplace limit values cannot be complied with by ventilat
	measures or if rooms cannot be technically ventilated, respirat protection must be worn: Use combination filter A1-P2 (brow
	white) in rooms that cannot be ventilated. If oxygen deficiency
	expected, use self-contained breathing apparatus. Obse
	wearing time limits according to §9 (3) GefStoffV in conjunct
	with BGR 190.
Hand protection	Selection of the glove material on consideration of the penetrat times, rates of diffusion and the degradation
Material of gloves	You can find help with choosing gloves on the website http www.bgbau.de/fileadmin/Gisbau/Projekte.pdf
	For example, we recommend the Sol-vex 37-900 protective glo
	from Ansell GmbH. The breakthrough time of the protective glo
	can be found under point 8 "Penetration time of the glove materi The selection of a suitable glove depends not only on the mater
	but also on other quality features and varies from manufacture
	manufacturer. As the product
	is a preparation of several substances, the resistance of glo
	materials cannot be calculated in advance and must therefore
	checked before use.
	Nitrile rubber Recommended material thickness:≥ 0.4 mm
Penetration time of glove	1.000mmended material (moniess.= 0.4 mm
material	The breakthrough times of the Sol-vex 37-900 protective glo
	are around 8 hours.
	The following applies to all other gloves:
	The exact breakthrough time must be obtained from the protect
	glove manufacturer and adhered to.
	Nitrile rubber Material thickness: ≥ 0.40 mm
	Penetration time: ≥ 480 min
	Butyl rubber:
	Material thickness: $\geq 0.5 \text{ mm}$
	Penetration time: ≥ 480 min
	(Contd. on pag



Page 6/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Trade name MC-DUR GLW - Komponente A

	(Contd. of page 5)
 Eye/face protection 	Tight-fitting safety goggles.
	Safety goggles.
 Body protection: 	Protective clothing
	Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

9.1 Information on basic physical and che General Information	emical properties
Colour:	Grey
Smell:	Characteristic
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and	
boiling range	100 °C (CAS: 7732-18-5 water, distille
	conductivity or of similar purity)
Flash point:	Not applicable
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Fully miscible
Steam pressure at 20 °C:	23 hPa (CAS: 7732-18-5 water, distille
	conductivity or of similar purity)
Density and/or relative density	
Density at 20 °C	1.4 g/cm³
•	5
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of he	ealth
and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive.
Information with regard to physical has	zard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Page 7/11

Trade name MC-DUR GLW - Komponente A

		(Contd. of page 6)
· Flammable liquids	Void	
· Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity · 10.2 Chemical stability	No further relevant information available.
 Thermal decomposition / conditions to be avoided: 10.3 Possibility of hazardous 	No decomposition if used according to specifications.
reactions	No dangerous reactions known No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
 10.6 Hazardous decomposition products: 	No dangerous decomposition products known

SECTION 11: Toxicological information

 11.1 Information on hazard cl Acute toxicity 	asses as defined in Regulation (EC) No 1272/2008 Based on available data, the classification criteria are not met.			
· LD/LC50 values that are relevant for classification:				
CAS: 112-57-2 3,6,9-triazaundecamethylenediamine				
Oral LD50 2140 mg/kg (rat				
Dermal LD50 1260 mg/kg (rab	bbit)			
 Primary irritant effect: Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity Reproductive toxicity STOT-single exposure STOT-repeated exposure 	 Based on available data, the classification criteria are not met. Causes serious eye damage. May cause an allergic skin reaction. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. 			

IE



Page 8/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Trade name MC-DUR GLW - Komponente A

- (Contd. of page 7) • Aspiration hazard Based on available data, the classification criteria are not met. • 11.2 Information on other hazards
- · Endocrine disrupting properties
- None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

EC50/72h 2.1 mg/l (algae)

LC50/96h 420 mg/l (Gup)

EC50/48h 24.1 mg/l (Daphnia magna)

	• • •	
· 12.2 Persi		
degradabi	-	No further relevant information available.
• 12.3 Bioac	cumulative	
potential		No further relevant information available.
· 12.4 Mobil	lity in soil	No further relevant information available.
12.5 Results of PBT and vPvB assessment		
· PBT:		Not applicable.
· vPvB:		Not applicable.
[.] 12.6 Endo	crine disrupting	
properties	;	The product does not contain substances with endocrine disrupting
		properties.
· 12.7 Other	r adverse effects	
· Additional	l ecological informa	ation:
· General n	-	Do not allow product to reach ground water, water bodies or
		sewage system.
		Danger to drinking water if even small quantities leak into soil.
		- · · ·

SECTION 13: Disposal considerations

 • 13.1 Waste treatment methods

 • Recommendation
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

 • European waste catalogue
 08 00 00

 08 00 00
 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

 08 01 00
 wastes from MFSU and removal of paint and varnish

 08 01 11*
 waste paint and varnish containing organic solvents or other hazardous substances

 HP5
 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

pages

IF



Page 9/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 8)

- Uncleaned packagings: • Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.
 - Recommended cleaning agent:

Water, if necessary with cleaning agent.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, ADN, IMDG, IATA Void	
 14.2 UN proper shipping name ADR, ADN, IMDG, IATA Void 	
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class Void	
• 14.4 Packing group • ADR, IMDG, IATA Void	
• 14.5 Environmental hazards: • Marine pollutant: No	
• 14.6 Special precautions for user Not applicable.	
• 14.7 Maritime transport in bulk according to IMO instruments Not applicable.	
· UN "Model Regulation": Void	

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture No further relevant information available.
 REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II None of the ingredients is listed.
 REGULATION (EU) 2019/1148
 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
 None of the ingredients is listed.

(Contd. on page 10)



Page 10/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 9)

· Annex II - REPORTABLE	EXPLOSIVES PRECURSORS		
None of the ingredients is I	isted.		
· Regulation (EC) No 273/2	004 on drug precursors		
None of the ingredients is l	isted.		
 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors 			
None of the ingredients is l	isted.		
 15.2 Chemical safety assessment: 	A Chemical Safety Assessment has not been carried out.		

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relev	ant phrases	 H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
speci Date Versio versio		Environment protection department. 16.10.2021 32 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals ELINCS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) L50: Lethal concentration, 50 percent L50: Lethal concentration, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1



Page 11/11

IF

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 33 (replaces version 32)

Revision: 08.12.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 10) STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

 * Data compared to the previous version altered.