



BE SURE. BUILD SURE.

Page 1/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **MC-DUR GLW - Komponente B**

Article number: 1203

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Epoxy coating  
Hardening agent/ Curing agent

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



GHS07

(Contd. on page 2)

IE



BE SURE. BUILD SURE.

Page 2/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

**Trade name MC-DUR GLW - Komponente B**

(Contd. of page 1)

- **Signal word** Warning
- **Hazard-determining components of labelling:** epoxide derivates  
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] dioxirane
- **Hazard statements**  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves / eye protection / face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.
- **Additional information:** EUH205 Contains epoxy constituents. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Binding agent with colouring agents.  
Mixture consisting of the following components.

(Contd. on page 3)

IE



BE SURE. BUILD SURE.

Page 3/12

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

Trade name **MC-DUR GLW - Komponente B**

(Contd. of page 2)

**· Dangerous components:**

|  |   |          |
|--|---|----------|
| CAS: 1675-54-3<br>EINECS: 216-823-5                                  | epoxide derivates<br>Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205<br>Specific concentration limits:<br>Skin Irrit. 2; H315: C ≥ 5%<br>Eye Irrit. 2; H319: C ≥ 5 %   | ≥10-<25% |
| CAS: 9003-36-5<br>EC number: 701-263-0                               | Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane<br>Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317 | ≥2.5-<5% |
| CAS: 100-51-6  | Benzyl alcohol<br>Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319  | <3%      |
| CAS: 107-98-2<br>EINECS: 203-539-1<br>Reg.nr.: 01-2119457435-35-XXXX | 1-methoxypropan-2-ol<br>Flam. Liq. 3, H226; STOT SE 3, H336   | <1.5%    |

**· Additional information**

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****· 4.1 Description of first aid measures****· General information**

Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.

**· After inhalation**

Supply fresh air; seek medical advice if symptoms occur.

**· After skin contact**

If unconscious, place in recovery position and seek medical advice. In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

**· After eye contact**

Rinse opened eye for several minutes under running water.

**· After swallowing**

Call a doctor immediately

Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

**· 4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

Trade name MC-DUR GLW - Komponente B

(Contd. of page 3)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Void
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Open and handle containers with care.  
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.  
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.

(Contd. on page 5)

IE



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

Trade name **MC-DUR GLW - Komponente B**

(Contd. of page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** Keep container tightly closed in a well-ventilated place.
- **Storage class** 10

## SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

#### · Components with critical values that require monitoring at the workplace:

##### CAS: 107-98-2 1-methoxypropan-2-ol

|                        |  |
|------------------------|--|
| OEL (Ireland)          | Short-term value: 568 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 375 mg/m <sup>3</sup> , 100 ppm<br>IOELV |
| IOELV (European Union) | Short-term value: 568 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 375 mg/m <sup>3</sup> , 100 ppm<br>Skin  |

#### · DNELs

##### CAS: 100-51-6 Benzyl alcohol

|            |      |   |
|------------|------|---|
| Oral       | DNEL | 4 mg/kg bw/Tag (ArL)<br>20 mg/kg bw/Tag (Ark)             |
| Dermal     | DNEL | 8 mg/kg bw/day (ArL)<br>40 mg/kg bw/day (Ark)             |
| Inhalative | DNEL | 22 mg/m <sup>3</sup> (ArL)<br>110 mg/m <sup>3</sup> (Ark) |

##### CAS: 107-98-2 1-methoxypropan-2-ol

|            |      |                             |
|------------|------|-----------------------------|
| Oral       | DNEL | 3.3 mg/kg bw/Tag (ArL)      |
| Dermal     | DNEL | 50.6 mg/kg bw/day (ArL)     |
| Inhalative | DNEL | 369 mg/m <sup>3</sup> (ArL) |

#### · PNECs

##### CAS: 100-51-6 Benzyl alcohol

|      |   |
|------|---|
| PNEC | 0.527 mg/l (Marine water sediment)<br>0.1 mg/l (Mew)<br>1 mg/l (Fresh water sediment) |
| PNEC | 0.456 mg/kg dwt (Bod)<br>5.27 mg/kg dwt (Fresh water sediment)                        |

· **Additional information:** The lists that were valid during the compilation were used as basis.

(Contd. on page 6)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

**Trade name MC-DUR GLW - Komponente B**

(Contd. of page 5)

- **8.2 Exposure controls**
- **Appropriate engineering controls**  
*No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**  
*Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.*
- **Breathing equipment:**  
*If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.*
- **Hand protection**  
*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves**  
*You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>  
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material".  
The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.  
Nitrile rubber  
Recommended material thickness:  $\geq 0.4$  mm*
- **Penetration time of glove material**  
*The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.  
The following applies to all other gloves:  
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.  
Nitrile rubber  
Material thickness:  $\geq 0.40$  mm  
Penetration time:  $\geq 480$  min  
Butyl rubber:  
Material thickness:  $\geq 0.5$  mm  
Penetration time:  $\geq 480$  min*
- **Eye/face protection**  
*Tight-fitting safety goggles.  
Safety goggles.*
- **Body protection:**  
*Protective clothing  
Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on*

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

Trade name MC-DUR GLW - Komponente B

(Contd. of page 6)

the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

#### SECTION 9: Physical and chemical properties

##### 9.1 Information on basic physical and chemical properties

###### General Information

|   |  |
|---|--|
| · <b>Colour:</b>  | Yellow   |
| · <b>Smell:</b>   | Characteristic   |
| · <b>Melting point/freezing point:</b>                            | Not determined   |
| · <b>Boiling point or initial boiling point and boiling range</b> | 100 °C (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)                                      |
| · <b>Flash point:</b>   | >94 °C   |
| · <b>Auto-ignition temperature:</b>                               | 184 °C (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight < 700) |
| · <b>pH</b>   | Not determined.  |
| · <b>Viscosity:</b>   |  |
| · <b>Kinematic viscosity</b>                                      | Not determined.  |
| · <b>dynamic:</b>   | Not determined.  |
| · <b>Solubility</b>   |  |
| · <b>Water:</b>   | Fully miscible   |
| · <b>Steam pressure at 20 °C:</b>                                 | 23 hPa (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)                                      |
| · <b>Density and/or relative density</b>                          |  |
| · <b>Density at 20 °C</b>   | 1.03 g/cm <sup>3</sup>   |

##### 9.2 Other information

|  |                              |
|--|------------------------------|
| · <b>Appearance:</b>   |                              |
| · <b>Form:</b>   | Fluid                        |
| · <b>Important information on protection of health and environment, and on safety.</b> |                              |
| · <b>Self-inflammability:</b>  | Product is not selfigniting. |
| · <b>Explosive properties:</b>   | Product is not explosive.    |

##### Information with regard to physical hazard classes

|  |      |
|--|------|
| · <b>Explosives</b>                            | Void |
| · <b>Flammable gases</b>                       | Void |
| · <b>Aerosols</b>                              | Void |
| · <b>Oxidising gases</b>                       | Void |
| · <b>Gases under pressure</b>                  | Void |
| · <b>Flammable liquids</b>                     | Void |
| · <b>Flammable solids</b>                      | Void |
| · <b>Self-reactive substances and mixtures</b> | Void |
| · <b>Pyrophoric liquids</b>                    | Void |

(Contd. on page 8)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

**Trade name MC-DUR GLW - Komponente B**

(Contd. of page 7)

- |  |      |
|--|------|
| · <b>Pyrophoric solids</b>   | Void |
| · <b>Self-heating substances and mixtures</b>                                      | Void |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b> | Void |
| · <b>Oxidising liquids</b>   | Void |
| · <b>Oxidising solids</b>  | Void |
| · <b>Organic peroxides</b>   | Void |
| · <b>Corrosive to metals</b>   | Void |
| · <b>Desensitised explosives</b>   | Void |

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**CAS: 1675-54-3 epoxide derivates**

|        |      |                      |
|--------|------|----------------------|
| Dermal | LD50 | 23000 mg/kg (rabbit) |
|--------|------|----------------------|

**CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | >2000 mg/kg (rat)    |
| Dermal | LD50 | >2000 mg/kg (rabbit) |

**CAS: 100-51-6 Benzyl alcohol**

|            |                      |                     |
|------------|----------------------|---------------------|
| Oral       | LD50                 | 1230 mg/kg (rat)    |
|            | NOAEL 2nd year study | 200 mg/kg (mouse)   |
|            |                      | 200 mg/kg (rat)     |
| Dermal     | LD50                 | 2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h             | >4178 mg/l (rat)    |

(Contd. on page 9)





BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

**Trade name MC-DUR GLW - Komponente B**

(Contd. of page 8)

**CAS: 107-98-2 1-methoxypropan-2-ol**

|            |          |                      |
|------------|----------|----------------------|
| Oral       | LD50     | 4016 mg/kg (rat)     |
| Dermal     | LD50     | 13000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 54.6 mg/l (rat)      |

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 1675-54-3 epoxide derivates**

|           |                                     |
|-----------|-------------------------------------|
| IC50      | >42.6 mg/l (Bak)                    |
| LC50/96h  | 2 mg/l (Oncorhynchus mykiss)        |
| EC50/48h  | 1.8 mg/l (Daphnia magna)            |
| ErC50/72h | 11 mg/l (Selenastrum capricornutum) |

**CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane**

|          |                           |
|----------|---------------------------|
| LC50/96h | >100 mg/l (Daphnia magna) |
| EC50/96h | >100 mg/l (Leucidus idus) |

**CAS: 100-51-6 Benzyl alcohol**

|          |   |
|----------|---|
| IC50/72h | 700 mg/l (algae)  |
| LC50/96h | 460 mg/l (Pimephales promelas)<br>10 mg/l (Lepomis macrochirus) |

**CAS: 107-98-2 1-methoxypropan-2-ol**

|          |                            |
|----------|----------------------------|
| IC50     | 1000 mg/l (BEL)            |
| LC50/96h | 6812 mg/l (Leucidus idus)  |
| LC50/48h | 23300 mg/l (Daphnia magna) |
| EC50/48h | 23300 mg/l (Daphnia magna) |

(Contd. on page 10)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

**Trade name MC-DUR GLW - Komponente B**

(Contd. of page 9)

- **12.2 Persistence and degradability** *No further relevant information available.*
- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Endocrine disrupting properties** *The product does not contain substances with endocrine disrupting properties.*
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.*

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **European waste catalogue**

|           |   |
|-----------|---|
| 08 00 00  | WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS |
| 08 01 00  | wastes from MFSU and removal of paint and varnish   |
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances   |
| HP4       | Irritant - skin irritation and eye damage   |
| HP13      | Sensitising   |
| HP14      | Ecotoxic  |

- **Uncleaned packagings:**
- **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*
- **Recommended cleaning agent:** *Water, if necessary with cleaning agent.*

### SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, ADN, IMDG, IATA** *Void*
- **14.2 UN proper shipping name**
- **ADR, ADN, IMDG, IATA** *Void*

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

Trade name MC-DUR GLW - Komponente B

(Contd. of page 10)

- **14.3 Transport hazard class(es)**
- **ADR, ADN, IMDG, IATA**
- **Class** Void
- **14.4 Packing group**
- **ADR, IMDG, IATA** Void
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Not applicable.
- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.
- **UN "Model Regulation":** Void

#### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture** No further relevant information available.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.09.2024

Version number 38 (replaces version 37)

Revision: 15.09.2024

**Trade name MC-DUR GLW - Komponente B**

(Contd. of page 11)

- **Relevant phrases**
  - H226 *Flammable liquid and vapour.*
  - H302 *Harmful if swallowed.*
  - H315 *Causes skin irritation.*
  - H317 *May cause an allergic skin reaction.*
  - H319 *Causes serious eye irritation.*
  - H332 *Harmful if inhaled.*
  - H336 *May cause drowsiness or dizziness.*
  - H411 *Toxic to aquatic life with long lasting effects.*
  - EUH205 *Contains epoxy constituents. May produce an allergic reaction.*
  
- **Department issuing data specification sheet:** *Environment protection department.*
- **Date of previous version:** *16.10.2021*
- **Version number of previous version:** *37*
- **Abbreviations and acronyms:**
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
  - ICAO: International Civil Aviation Organisation*
  - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
  - IMDG: International Maritime Code for Dangerous Goods*
  - IATA: International Air Transport Association*
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals*
  - EINECS: European Inventory of Existing Commercial Chemical Substances*
  - ELINCS: European List of Notified Chemical Substances*
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)*
  - DNEL: Derived No-Effect Level (REACH)*
  - PNEC: Predicted No-Effect Concentration (REACH)*
  - LC50: Lethal concentration, 50 percent*
  - LD50: Lethal dose, 50 percent*
  - PBT: Persistent, Bioaccumulative and Toxic*
  - vPvB: very Persistent and very Bioaccumulative*
  - Flam. Liq. 3: Flammable liquids – Category 3*
  - Acute Tox. 4: Acute toxicity – Category 4*
  - Skin Irrit. 2: Skin corrosion/irritation – Category 2*
  - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*
  - Skin Sens. 1: Skin sensitisation – Category 1*
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*
  - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*
  - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*
  
- **\* Data compared to the previous version altered.**

IE