

Page 1/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name MC-Estripox protect - Komponente A

· Article number: 1443

 1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Epoxy coating

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1A H360F May damage fertility.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure.

Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

n. (Contd. on page 2)

-*)* - IF



Page 2/14

(Contd. of page 1)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 11.07.2025 Printing date 11.07.2025 Version number 45 (replaces version 44)

Trade name MC-Estripox protect - Komponente A

· Hazard pictograms





· Signal word Danger

· Hazard-determining components of labelling:

4,4'-Methylenediphenyldiglycidyl ether 1,6-bis(2,3-epoxypropoxy)hexane

Quartz sand

Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

Maleic anhydride

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] bis(oxirane) and 2.2'-[methylenebis(4.1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}

methyl)oxirane

Fatty acids, C14-18 and C16-18-unsatd., maleated

· Hazard statements

H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H360F May damage fertility.

H372 Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation. H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/

P261 Avoid breathing dust/fume/gas/mist/vapours/

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

EUH211 Warning! Hazardous respirable droplets may be formed

when sprayed. Do not breathe spray or mist.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Resin mixture with colouring agents.

(Contd. on page 3)



Page 3/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

	Mixture consisting of the following components.	(Contd. of page
Dangerous compor		
CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	30-60%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz sand STOT RE 1, H372	10-30%
CAS: 13463-67-7 EINECS: 236-675-5	Titanium dioxide Carc. 2, H351	≥1-<5%
CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	<i>≥</i> 2.5-<5%
CAS: 933999-84-9	1,6-bis(2,3-epoxypropoxy)hexane Repr. 1A, H360F; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<5%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<2.5%
CAS: 68609-97-2 EINECS: 271-846-8	Oxirane, mono((C12-14-alkyloxy)methyl)derivatives Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<1.5%
CAS: 85711-46-2	Fatty acids, C14-18 and C16-18-unsatd., maleated Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<0.5%
CAS: 108-31-6 EINECS: 203-571-6	Maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥0.001-<0.19

SECTION 4: First aid measures

Additional information

· 1 1	Description	of firet aid	maacurac
4. 1	Describitor	ı vı ılısı alu	IIIeasures

General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

• After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

For the wording of the listed hazard phrases refer to section 16.

• After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

(Contd. on page 4)



Page 4/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 11.07.2025 Printing date 11.07.2025 Version number 45 (replaces version 44)

Trade name MC-Estripox protect - Komponente A

(Contd. of page 3)

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or

No further relevant information available. mixture

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

(Contd. on page 5)



Page 5/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

(Contd. of page 4)

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

0.1 mg/l (Mew)

PNEC 0.456 mg/kg dwt (Bod)

1 mg/l (Fresh water sediment)

5.27 mg/kg dwt (Fresh water sediment)

storage conditions: None. Storage class 6.1C

SECTION 8: Exposure controls/personal protection

CAS: 148	08-60-7	Quartz :	sand	
OEL (Irela	nd)		Long-term value: 0.1 mg/m³	
,		n Union)	Long-term value: 0.1* mg/m³ *respirable fraction	
CAS: 108	-31-6 M	laleic anl	nydride	
OEL (Ireland)			Long-term value: 0.01 ppm *Inhalable fraction and vapour, Sens	
DNELs				
CAS: 100	-51-6 B	enzyl ald	ohol	
Oral	DNEL	4 mg/kg	4 mg/kg bw/Tag (ArL)	
		20 mg/k	g bw/Tag (Ark)	
Dermal	DNEL	8 mg/kg	bw/day (ArL)	
		40 mg/k	g bw/day (Ark)	
Inhalative	DNEL	22 mg/m	³ (ArL)	
		110 mg/	m³ (Ark)	
CAS: 686	09-97-2	Oxirane	, mono((C12-14-alkyloxy)methyl)derivatives	
Dermal	DNEL	0.75 mg/kg bw/day (ArL)		
Inhalative DNEL 0.49 mg/m³ (ArL)				
PNECs				

(Contd. on page 6)



Page 6/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

(Contd. of page 5)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

PNEC 0.00072 mg/l (Mew)

0.0072 mg/l (Freshwater)

PNEC 80.12 mg/kg dwt (Bod)

6.677 mg/kg dwt (Sediment)

66.77 mg/kg dwt (Fresh water sediment)

• Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

· Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

· Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

• Hand protection Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

Penetration time of glove

material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

(Contd. on page 7)



Page 7/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

(Contd. of page 6)

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min

• Eye/face protection Tight-fitting safety goggles.

Safety goggles.

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.

Not determined.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: According to product specification

· Smell: Characteristic
· Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 200 °C
• Flash point: 151 °C
• Auto-ignition temperature: 184 °C

ρΗ

· Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.16800 mPas

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0.1 hPa

· Density and/or relative density

Density at 20 °C 1.56 g/cm³

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void

(Contd. on page 8)



Page 8/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

(Contd. of page 7)

Gases under pressure	Void
· Flammable liquids	Void
Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.
 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values that are relevant for classification:		
CAS: 167	CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether		
Oral	LD50	11400 mg/kg (rat)	
Dermal	LD50	23000 mg/kg (rabbit)	
		>2000 mg/kg (rat)	
CAS: 134	CAS: 13463-67-7 Titanium dioxide		
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>10000 mg/kg (rabbit)	

(Contd. on page 9)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

1	1.050/4.5	(Contd. of page 8
Inhalative		>6.8 mg/l (rat)
CAS: 900	bis(oxirane)	as of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
CAS: 100	-51-6 Benzyl alcohol	
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year stud	y 200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
CAS: 686	09-97-2 Oxirane, mon	o((C12-14-alkyloxy)methyl)derivatives
Oral	LD50	17100 mg/kg (rat)
CAS: 108	-31-6 Maleic anhydrid	e
Oral	LD50	1090 mg/kg (rat)
Dermal	LD50	2620 mg/kg (rat)
	rritant effect:	
		Causes skin irritation.
		Causes serious eye irritation.
Respirato sensitisa		May cause an allergic skin reaction.
		Based on available data, the classification criteria are not met.
Carcinog	0 ,	Based on available data, the classification criteria are not met.
Reproductive toxicity M		May damage fertility.
		Based on available data, the classification criteria are not met.
- 5101-rep		Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
· Aspiratio		Based on available data, the classification criteria are not met.
	mation on other haza	

SECTION 12: Ecological information

CAS: 556-67-2 octamethylcyclotetrasiloxane

· Endocrine disrupting properties

· 12.1 Toxicity

· Aquatic toxicity:			
CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether			
LC50/72h	>11 mg/l (algae)		
IC50	>42.6 mg/l (Bak)		
LC50/96h	2 mg/l (Oncorhynchus mykiss)		
	(Contd. on nogo 10)		

(Contd. on page 10)

List II



Page 10/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

(Contd. of page 9)

1.3 mg/l (fish)

EC50/48h 2.1 mg/l (daphnia)

1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)

oxirane

LC50/96h >100 mg/l (Daphnia magna) EC50/96h >100 mg/l (Leucidus idus)

CAS: 100-51-6 Benzyl alcohol

IC50/72h 700 mg/l (algae)

LC50/96h 460 mg/l (Pimephales promelas)

10 mg/l (Lepomis macrochirus)

CAS: 68609-97-2 Oxirane, mono((C12-14-alkyloxy)methyl)derivatives

EbC50/72h 843 mg/l (Pseudokirchneriella subcapitata)

LC50/96h >5000 mg/l (Oncorhynchus mykiss)

1800 mg/l (Lepomis macrochirus)

EC50 >100 mg/l (BEL)

NOEC 500 mg/l (Pseudokirchneriella subcapitata)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
 No further relevant information available.
 12.4 Mobility in soil
 No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Additional ecological information:

General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

(Contd. on page 11)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

	(Contd. of page 10)
· European	waste catalogue
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP10	Toxic for reproduction
HP13	Sensitising
HP14	Ecotoxic

- · Uncleaned packagings:
- · Recommendation: Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name · ADR, IATA	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (Epoxide resin)
· IMDG	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (Epoxide resin MARINE POLLUTANT
· 14.3 Transport hazard class(es)	
· ADR	
Class	9 (M6) Miscellaneous dangerous substances ar articles.
· Label	9
· IMDG, IATA	
Class	 Miscellaneous dangerous substances ar articles.
· Label	9
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

	(Contd. of page 1
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accordi	ing to
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
Transport category	3
Tunnel restriction code	(-)
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN
	9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 13)



Page 13/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

(Contd. of page 12)

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H351 Suspected of causing cancer.

H360F May damage fertility.

H372 Causes damage to organs through prolonged or repeated

exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Department issuing data

specification sheet: Environment protection department.

Date of previous version: 17.10.2021

Version number of previous

version:

44

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 14)



Page 14/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.07.2025 Version number 45 (replaces version 44) Revision: 11.07.2025

Trade name MC-Estripox protect - Komponente A

(Contd. of page 13)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity - Category 2

Repr. 1A: Reproductive toxicity – Category 1A
Repr. 1B: Reproductive toxicity – Category 1B
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 2

* * Data compared to the previous version altered.