

Page 1/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 43 (replaces version 42) Revision: 11.04.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name Muraplast FK 63.30

162 · Article number:

· 1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Concrete/Mortar admixtures

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP

regulation.

· Hazard pictograms



· Signal word Warning

· Hazard-determining

components of labelling: 2-Octyl-2H-isothiazol-3-on 1,2-benzisothiazol-3(2H)-one

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-

isothiazol-3-one (3:1)

(Contd. on page 2)



Page 2/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 43 (replaces version 42) Revision: 11.04.2025

Trade name Muraplast FK 63.30

(Contd. of page 1)

· **Hazard statements** H317 May cause an allergic skin reaction.

· Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before

reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

· Additional information: Contains biocidal products: 1,2-benzisothiazol-3(2H)-one, 2-Octyl-

2H-isothiazol-3-on, Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-

one and 2-methyl-2H-isothiazol-3-one (3:1)

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Mixture consisting of the following components.

٠,	Dan	ger	ous	con	про	nent	s:
----	-----	-----	-----	-----	-----	------	----

CAS: 2634-33-5	1,2-benzisothiazol-3(2H)-one	<i>≥</i> 0.025-<0.05%
EINECS: 220-120-9	Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥0.05 %	

(Contd. on page 3)

Ε-



Page 3/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 43 (replaces version 42) Revision: 11.04.2025

Trade name Muraplast FK 63.30

		(Contd. of page
CAS: 26530-20-1 EINECS: 247-761-7	2-Octyl-2H-isothiazol-3-on Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l Specific concentration limit: Skin Sens. 1A; H317: C≥ 0.0015 %	≥0.0015-<0.0025%
CAS: 55965-84-9 EC number: 911-418-6	Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314: $C \ge 0.6$ % Skin Irrit. 2; H315: 0.06 % ≤ $C < 0.6$ % Eye Dam. 1; H318: $C \ge 0.6$ % Eye Irrit. 2; H319: 0.06 % ≤ $C < 0.6$ % Skin Sens. 1A; H317: $C \ge 0.0015$ %	≥0.00025-<0.0015%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information For all first aid measures: observe self-protection and consult a

doctor!

• After inhalation Take the person out into the fresh air.

• After skin contact Remove contaminated clothing immediately.

Hold affected areas under cold running water for at least 15

minutes.

· After eye contact Rinse for 10 minutes under running water with the eyelids open or

use eye rinsing solution. Always consult an ophthalmologist!

· After swallowing Drink plenty of water in small sips.

Do not induce vomiting.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

(Contd. on page 4)



Page 4/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 43 (replaces version 42) Revision: 11.04.2025

Trade name Muraplast FK 63.30

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: Dilute with much water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections No dangerous materials are released.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Avoid splashing.

Avoid dust development with powder products.

Limit the storage quantity at the workplace to one shift

requirement.

Do not leave containers open.

Provide washing facilities in the work area. Provide an eye shower or eyewash bottle.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: Avoid splashing.

Avoid dust development with powder products.

Limit the storage quantity at the workplace to one shift

requirement.

Do not leave containers open.

Provide washing facilities in the work area. Provide an eye shower or eyewash bottle.

· Information about storage in

one common storage facility: Combined storage bans apply from a total storage quantity of 200

ka.

Do not store together with substances of the following LGK: 1;

5.1A; 5.2; 6.2; 7

Storage with substances of the following LGK is only possible under the conditions specified in TRGS 510: 4.1A; 4.2; 4.3; 5.1C

· Further information about

storage conditions: None.

(Contd. on page 5)



Page 5/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 11.04.2025 Printing date 11.04.2025 Version number 43 (replaces version 42)

Trade name Muraplast FK 63.30

(Contd. of page 4)

· Storage class

12

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters · Components with critical values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls Appropriate engineering

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

Do not store any foodstuffs or eat, drink, snuff or smoke in the hygienic measures

work area!

Avoid contact with eyes, skin and clothing!

Clean hands thoroughly after work and before cleaning! Use skin care products after work (moisturising cream).

Change wet/uncleaned clothing immediately, place in water and

only use again after cleaning!

Breathing equipment: If the limit value is exceeded:

Combination filter A-P2 (brown/white).

Gloves made of: Natural latex, polychloroprene, nitrile rubber. · Hand protection

(Category 3 chemical protective gloves, recognisable by the CE

mark with four-digit test number).

When wearing protective gloves, cotton undergloves are

recommended.

· Material of gloves

see "Hand protection"

· Penetration time of glove

The exact breakthrough time must be obtained from the protective material

glove manufacturer and must be observed.

· Eye/face protection

Gauze goggles

Alkali-resistant protective clothing · Body protection:

Use greasy skin protection ointment for all uncovered parts of the · Skin protection

body!

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Brown

· Smell: Characteristic

<0 °C Melting point/freezing point:

(Contd. on page 6)



Page 6/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 11.04.2025 Printing date 11.04.2025 Version number 43 (replaces version 42)

Trade name Muraplast FK 63.30

(Contd. of page 5)

Boiling point or initial boiling point and

boiling range 100 °C (CAS: 7732-18-5 Water)

· Flash point: Not applicable

· pH at 20 °C

· Viscosity:

· Kinematic viscosity Not determined. · dynamic at 20 °C: 750 mPas

· Solubility

· Water: Fully miscible

· Steam pressure at 20 °C: 23 hPa (CAS: 7732-18-5 Water)

Density and/or relative density

Density at 20 °C 1.06 g/cm3

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes · Explosives · Aerosols

Void · Flammable gases Void Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void Flammable solids Void

· Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pyrophoric solids Self-heating substances and mixtures Void

· Substances and mixtures, which emit

Void flammable gases in contact with water · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

No further relevant information available. · 10.1 Reactivity

10.2 Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)



Page 7/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 11.04.2025 Printing date 11.04.2025 Version number 43 (replaces version 42)

Trade name Muraplast FK 63.30

(Contd. of page 6)

· 10.3 Possibility of hazardous

No dangerous reactions known reactions

· 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

No dangerous decomposition products known decomposition products:

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC	50 values tl	hat are relevant for classification:
CAS: 2	634-33-5 1,	2-benzisothiazol-3(2H)-one
Oral	LD50	1020 mg/kg (rat)

Orai	LDSU	1020 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

CAS: 26530-20-1 2-Octyl-2H-isothiazol-3-on LDEO 405 mm m/lon /ATC

Orai	LD50	125 mg/kg (ATE)
		500 mg/kg (rat)
Dermal	LD50	311 mg/kg (ATE)

>2000 mg/kg (rat)

Inhalative LC50/4 h 0.27 mg/l (ATE) 0.6 mg/l (rat)

CAS: 55965-84-9 Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2Hisothiazol-3-one (3:1)

Oral	LD50	49.6-75 mg/kg (rat)
	LD50	87.12 mg/kg (rabbit)
Inhalative	LC50/4 h	0.171 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met. · Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

May cause an allergic skin reaction. sensitisation

Germ cell mutagenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · Carcinogenicity Reproductive toxicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure · Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.



Page 8/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 43 (replaces version 42) Revision: 11.04.2025

Trade name Muraplast FK 63.30

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

EC50/72h | 0.067 mg/l (Pseudokirchneriella subcapitata)

0.11 mg/l (Selenastrum capricornutum)

LC50/96h 1.6 mg/l (Oncorhynchus mykiss)

EC50/48h 1.1 mg/l (Daphnia magna)

CAS: 26530-20-1 2-Octyl-2H-isothiazol-3-on

EC50/48h | 0.42 mg/l (Daphnien)

CAS: 55965-84-9 Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

LC50/24h | 0.19 mg/l (fish)

EC50/72h 0.027 mg/l (Pseudokirchneriella subcapitata)

LC50/96h | 0.19 mg/l (Oncorhynchus mykiss)

LC50/48h | 0.28 mg/l (fish)

EC50/48h | 0.16 mg/l (Daphnia magna)

NOEC 0.02 mg/l (Oncorhynchus mykiss)

0.00049 mg/l (Ske)

0.1 mg/l (Daphnia magna)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

Additional ecological information:

General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

(Contd. on page 9)



Page 9/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 43 (replaces version 42) Revision: 11.04.2025

Trade name Muraplast FK 63.30

	(Contd. of page 8)	1
· Europear	n waste catalogue	
17 00 00	CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)	
17 09 00	other construction and demolition wastes	
17 09 03*	other construction and demolition wastes (including mixed wastes) containing hazardous substances	
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED	
15 01 00	packaging (including separately collected municipal packaging waste)	
15 01 01	paper and cardboard packaging	
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED	
15 01 00	packaging (including separately collected municipal packaging waste)	
15 01 02	plastic packaging	

· Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number	
ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	Not dangerous according to the abov specifications.



Page 10/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 43 (replaces version 42) Revision: 11.04.2025

Trade name Muraplast FK 63.30

(Contd. of page 9)

UN "Model Regulation":

Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
 H301 Toxic if swallowed.
 H302 Harmful if swallowed.

H310 Fatal in contact with skin. H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 11)



Page 11/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.04.2025 Version number 43 (replaces version 42) Revision: 11.04.2025

Trade name Muraplast FK 63.30

(Contd. of page 10)

EUH071 Corrosive to the respiratory tract.

· Department issuing data

specification sheet: Environment protection department.

· Date of previous version: 13.10.2021

· Version number of previous

version: 4

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values
Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 3: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1 Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard -

Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 1

* Data compared to the previous version altered.

- IE