



BE SURE. BUILD SURE.

Page 1/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name Mycoflex 4100 TS - Komponente A

· Article number: 966

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Primer/ Subcoating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· Informing department: msds@mc-bauchemie.de

· 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07 GHS08

Signal word

Warning

Hazard-determining components of labelling:

Reaction mass of ethylbenzene and xylene
4,4'-Methylenediphenyldiglycidyl ether
1-Methoxy-2-propanol

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

H412 Harmful to aquatic life with long lasting effects.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components.

Dangerous components:

EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	30-60%
---	--	--------

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 2)

CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-XXXX	1-Methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	30-60%
CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥10-<25%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318	≥1-<1.5%
CAS: 1589-47-5 EINECS: 216-455-5	2-methoxypropanol Flam. Liq. 3, H226; Repr. 1B, H360D; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	<0.3%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **For safety reasons unsuitable extinguishing agents** Water with a full water jet.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** Keep container tightly closed in a well-ventilated place.

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

· **Storage class**

3

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 107-98-2 1-Methoxy-2-propanol

OEL (Ireland)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm IOELV
IOELV (European Union)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Skin

· **DNELs**

Reaction mass of ethylbenzene and xylene

Oral	DNEL	1.6 mg/kg bw/Tag (ArL) mg/kg bw/Tag (Workers)
Dermal	DNEL	180 mg/kg bw/day (ArL)
Inhalative	DNEL	211 mg/m ³ (ArL)

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	DNEL	3.3 mg/kg bw/Tag (ArL)
Dermal	DNEL	50.6 mg/kg bw/day (ArL)
Inhalative	DNEL	369 mg/m ³ (ArL)

· **CAS No. Designation of material % Type Value Unit**

· **Additional Occupational Exposure Limit Values for possible hazards during processing:**

CAS: 1330-20-7 xylene

OEL (Ireland)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin, IOELV
IOELV (European Union)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

CAS: 100-41-4 ethylbenzene

OEL (Ireland)	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin, IOELV
IOELV (European Union)	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin

· **Additional information:**

The lists that were valid during the compilation were used as basis.

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 5)

- **8.2 Exposure controls**
- **Appropriate engineering controls**
No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
*Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.*
- **Breathing equipment:**
If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.
- **Hand protection**
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
*You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material".
The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.
Nitrile rubber
Recommended material thickness: ≥ 0.4 mm*
- **Penetration time of glove material**
*The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.
The following applies to all other gloves:
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.
Nitrile rubber
Material thickness: ≥ 0.40 mm
Penetration time: ≥ 480 min
Butyl rubber:
Material thickness: ≥ 0.5 mm
Penetration time: ≥ 480 min*
- **Eye/face protection**
*Tight-fitting safety goggles.
Safety goggles.*
- **Body protection:**
*Protective clothing
Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on*

(Contd. on page 7)

IE



BE SURE. BUILD SURE.

Page 7/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 6)

the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:	Yellow
· Smell:	Characteristic
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	120.3 °C (CAS: 107-98-2 1-Methoxy-2-propanol)
· Lower and upper explosion limit	
· Lower:	1 Vol % (Reaction mass of ethylbenzene and xylene)
· Upper:	13.7 Vol % (CAS: 107-98-2 1-Methoxy-2-propanol)
· Flash point:	25 °C
· Auto-ignition temperature:	184 °C (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight < 700)
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity at 20 °C	22 s (DIN 53211/4)
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	13 hPa (CAS: 107-98-2 1-Methoxy-2-propanol)
· Vapour pressure at 50 °C:	45 hPa
· Density and/or relative density	
· Density at 20 °C	0.94 g/cm ³

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 7)

· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

Reaction mass of ethylbenzene and xylene

Oral	LD50	3523-4000 mg/kg (rat)
Dermal	LD50	1100 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (rat)

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	LD50	4016 mg/kg (rat)
Dermal	LD50	13000 mg/kg (rabbit)
Inhalative	LC50/4 h	54.6 mg/l (rat)

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

Oral	LD50	11400 mg/kg (rat)
------	------	-------------------

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 8)

Dermal	LD50	23000 mg/kg (rabbit) >2000 mg/kg (rat)
CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
Oral	LD50	8030 mg/kg (rat)
Dermal	LD50	4248 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· Endocrine disrupting properties		
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II
CAS: 556-67-2	octamethylcyclotetrasiloxane	List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

Reaction mass of ethylbenzene and xylene		
EC50/72h	2.2 mg/l (Selenastrum capricornutum)	
LC50/96h	2.6 mg/l (Oncorhynchus mykiss)	
NOEC	16 mg/l (BEL)	
CAS: 107-98-2 1-Methoxy-2-propanol		
IC50	1000 mg/l (BEL)	
LC50/96h	6812 mg/l (Leucidus idus)	
LC50/48h	23300 mg/l (Daphnia magna)	
EC50/48h	23300 mg/l (Daphnia magna)	
CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether		
LC50/72h	>11 mg/l (algae)	
IC50	>42.6 mg/l (Bak)	
LC50/96h	2 mg/l (Oncorhynchus mykiss)	
	1.3 mg/l (fish)	

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 9)

EC50/48h	2.1 mg/l (daphnia) 1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)
CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane	
LC50/96h	55 mg/l (Cyp)
EC50/48h	473 mg/l (Daphnia magna)
ErC50/72h	255 mg/l (Scenedesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP6	Acute Toxicity
HP13	Sensitising
HP14	Ecotoxic

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 10)

- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1866
· 14.2 UN proper shipping name · ADR, IMDG, IATA	RESIN SOLUTION
· 14.3 Transport hazard class(es) · ADR · Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA · Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, S-E A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code · Remarks:	3 D/E Begrenzte Mengen (LQ)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 11)

· Remarks:	ml Begrenzte Mengen
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation.
---------------------------	---

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 46 (replaces version 45)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 12)

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360D May damage the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

09.03.2024

· **Version number of previous version:**

45

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

IE