



BE SURE. BUILD SURE.

Page 1/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name **Mycoflex 4100 TS - Komponente B**

· Article number: 967

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Primer/ Subcoating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· Informing department: msds@mc-bauchemie.de

· 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



BE SURE. BUILD SURE.

Page 2/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

· **Signal word**

Danger

· **Hazard-determining components of labelling:**

2-Methylpropan-1-ol
xylene
3-aminopropyltriethoxysilane
2-Methylpentamethylenediamine

· **Hazard statements**

H226 *Flammable liquid and vapour.*
H315 *Causes skin irritation.*
H318 *Causes serious eye damage.*
H317 *May cause an allergic skin reaction.*
H335-H336 *May cause respiratory irritation. May cause drowsiness or dizziness.*
H373 *May cause damage to the hearing organs through prolonged or repeated exposure.*

· **Precautionary statements**

P260 *Do not breathe dust/fume/gas/mist/vapours/spray.*
P303+P361+P353 *IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].*
P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P310 *Immediately call a POISON CENTER/doctor.*
P321 *Specific treatment (see on this label).*
P362+P364 *Take off contaminated clothing and wash it before reuse.*
P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*
· **vPvB:** *Not applicable.*

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** *Mixture consisting of the following components.*

(Contd. on page 3)

IE



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 2)

· Dangerous components:

CAS: 78-83-1 EINECS: 201-148-0	2-Methylpropan-1-ol Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥20-≤30%
CAS: 1330-20-7	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥10-<20%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-Methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	<10%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	<5%
CAS: 15520-10-2 EINECS: 239-556-6	2-Methylpentamethylenediamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥1-<3%
CAS: 919-30-2 EINECS: 213-048-4	3-aminopropyltriethoxysilane Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317	≥1-<1.5%

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.

· After inhalation

Supply fresh air; seek medical advice if symptoms occur.

· After skin contact

If unconscious, place in recovery position and seek medical advice. In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

· After eye contact

Rinse opened eye for several minutes under running water. Call a doctor immediately

· After swallowing

Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

(Contd. on page 5)

IE



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 4)

- **Information about protection against explosions and fires:** *Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Further information about storage conditions:** *Keep container tightly closed in a well-ventilated place.*
- **Storage class** *3*

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 78-83-1 2-Methylpropan-1-ol

OEL (Ireland) *Long-term value: 700 mg/m³, 150 ppm*

CAS: 1330-20-7 xylene

OEL (Ireland) *Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin, IOELV*

IOELV (European Union) *Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin*

CAS: 107-98-2 1-Methoxy-2-propanol

OEL (Ireland) *Short-term value: 568 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
IOELV*

IOELV (European Union) *Short-term value: 568 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
Skin*

CAS: 100-41-4 ethylbenzene

OEL (Ireland) *Short-term value: 884 mg/m³, 200 ppm
Long-term value: 442 mg/m³, 100 ppm
Skin, IOELV*

IOELV (European Union) *Short-term value: 884 mg/m³, 200 ppm
Long-term value: 442 mg/m³, 100 ppm
Skin*

· **DNELs**

CAS: 78-83-1 2-Methylpropan-1-ol

Oral DNEL *25 mg/kg bw/Tag (ArL)*

Inhalative DNEL *310 mg/m³ (ArL)*

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 5)

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	DNEL	3.3 mg/kg bw/Tag (ArL)
Dermal	DNEL	50.6 mg/kg bw/day (ArL)
Inhalative	DNEL	369 mg/m ³ (ArL)

CAS: 15520-10-2 2-Methylpentamethylenediamine

Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m ³ (ArL) 0.5 mg/m ³ (Ark)

· PNECs

CAS: 78-83-1 2-Methylpropan-1-ol

PNEC	0.4 mg/l (Fresh water)
	0.04 mg/l (Mew)
PNEC	0.0699 mg/kg dwt (Bod)
	0.125 mg/kg dwt (Sediment)
	1.52 mg/kg dwt (Fresh water sediment)

CAS: 15520-10-2 2-Methylpentamethylenediamine

PNEC	0.042 mg/l (Mew)
	0.42 mg/l (Freshwater)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· Breathing equipment:

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 6)

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· **Penetration time of glove material**

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· **Eye/face protection**

Tight-fitting safety goggles.

Safety goggles.

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

Light yellow

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

>100 °C (CAS: 260549-92-6 Polymer Epoxidharz-Addukt)

· **Lower and upper explosion limit**

· **Lower:**

1 Vol % (Reaction mass of ethylbenzene and xylene)

· **Upper:**

12 Vol % (CAS: 78-83-1 butanol)

· **Flash point:**

28 °C

· **Auto-ignition temperature:**

270 °C

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 7)

· dynamic at 20 °C:	3300 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	4-40 hPa (CAS: 78-83-1 butanol)
· Vapour pressure at 50 °C:	45 hPa
· Density and/or relative density	
· Density at 20 °C	0.99 g/cm ³
9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 8)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 78-83-1 2-Methylpropan-1-ol

Oral	LD50	2460 mg/kg (rat)
Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50/4 h	19.2 mg/l (rat)

CAS: 1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (rat)

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	LD50	4016 mg/kg (rat)
Dermal	LD50	13000 mg/kg (rabbit)
Inhalative	LC50/4 h	54.6 mg/l (rat)

CAS: 100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (rat)

CAS: 15520-10-2 2-Methylpentamethylenediamine

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

CAS: 919-30-2 3-aminopropyltriethoxysilane

Oral	LD50	1780 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 9)

- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 78-83-1 2-Methylpropan-1-ol

LC50/96h	1430 mg/l (Pimephales promelas)
EC50/48h	1250 mg/l (Desmodesmus subspicatus)
	1030 mg/l (Daphnia magna)

CAS: 107-98-2 1-Methoxy-2-propanol

IC50	1000 mg/l (BEL)
LC50/96h	6812 mg/l (Leucidus idus)
LC50/48h	23300 mg/l (Daphnia magna)
EC50/48h	23300 mg/l (Daphnia magna)

CAS: 100-41-4 ethylbenzene

LC50/96h	4.2 mg/l (Oncorhynchus mykiss)
EC50/48h	2.97 mg/l (Daphnia magna)

CAS: 15520-10-2 2-Methylpentamethylenediamine

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

CAS: 919-30-2 3-aminopropyltriethoxysilane

LC0/96h	934 mg/l (Brachydanio rerio)
EC50/72h	603 mg/l (Scenedesmus subspicatus)
EC50/48h	331 mg/l (Daphnia magna)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 10)

- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.*

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

- **Uncleaned packagings:**
- **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** *UN1866*
- **14.2 UN proper shipping name**
- **ADR, IMDG, IATA** *RESIN SOLUTION*
- **14.3 Transport hazard class(es)**
- **ADR**
- **Class** *3 (F1) Flammable liquids.*
- **Label** *3*
- **IMDG, IATA**
- **Class** *3 Flammable liquids.*
- **Label** *3*
- **14.4 Packing group**
- **ADR, IMDG, IATA** *II*
- **14.5 Environmental hazards:**
- **Marine pollutant:** *No*

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 11)

· 14.6 Special precautions for user	Warning: <i>Flammable liquids.</i>
· Kemler Number:	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	

· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· Remarks:	Begrenzte Mengen (LQ)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Remarks:	Begrenzte Mengen
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 13)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 12)

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

CAS: 108-88-3 toluene

3

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

CAS: 108-88-3 toluene

3

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing data specification sheet:**

Environment protection department.

· **Date of previous version:**

09.03.2024

· **Version number of previous version:**

38

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

(Contd. on page 14)



BE SURE. BUILD SURE.

Page 14/14

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.04.2025

Version number 39 (replaces version 38)

Revision: 13.04.2025

Trade name Mycoflex 4100 TS - Komponente B

(Contd. of page 13)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

*** Data compared to the
previous version altered.**

IE