

Page 1/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 28 (replaces version 27) Revision: 15.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name Nafufill KM 110 HS

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Fixing mortar /Compo

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number: Te

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP

regulation.

· Hazard pictograms



GHS05 GHS07

· Signal word Danger

· Hazard-determining

components of labelling: Portland cement (low chromate)

Flue dust, portland cement

(Contd. on page 2)



Page 2/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 28 (replaces version 27) Revision: 15.04.2025

Trade name Nafufill KM 110 HS

(Contd. of page 1)

· **Hazard statements** H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

• Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/

spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P310 Immediately call a POISON CENTER, P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it

before reuse.

P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous compor	· Dangerous components:	
CAS: 14808-60-7 EINECS: 238-878-4	Quartz sand substance with a Community workplace exposure limit	30-60%
CAS: 65997-15-1 EINECS: 266-043-4	Portland cement (low chromate) Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	30-60%
CAS: 1317-65-3 EINECS: 207-439-9	Calcium carbonate substance with a Community workplace exposure limit	<3%
CAS: 68475-76-3 EINECS: 270-659-9	Flue dust, portland cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥1-<2.5%

• Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information For all first aid measures: observe self-protection and consult a

doctor!

· After inhalation Remove people from the dusty area.

After skin contact Remove heavily soiled clothing. Clean with plenty of soap and

water.

· After eye contact Rinse for 10 minutes under running water with the eyelids open.

Always consult an ophthalmologist!

(Contd. on page 3)



Page 3/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 28 (replaces version 27) Revision: 15.04.2025

Trade name Nafufill KM 110 HS

(Contd. of page 2)

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

· 5.3 Advice for firefighters

• Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: No special measures required.

· 6.3 Methods and material for

containment and cleaning up: Collect mechanically.

· 6.4 Reference to other

sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Avoid dust formation! Avoid spraying the ready-to-use cementitious

product! Avoid contact with eyes and skin! Clean hands thoroughly at the end of work and before every break! Use skin care products! Change heavily soiled clothing! Change clothes at the end of work! Apply greasy skin protection ointment before starting work and

after each break. Observe work restrictions!

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: Store bags tightly closed; protect from moisture and water!

Store containers tightly closed in a well-ventilated and well-lit room.

Access only for specialised personnel.

Do not store in break rooms, recreation rooms or sanitary facilities or in stairwells, corridors, escape and rescue routes, passages,

passageways and confined spaces.

(Contd. on page 4)



Page 4/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 28 (replaces version 27) Revision: 15.04.2025

Trade name Nafufill KM 110 HS

(Contd. of page 3)

· Information about storage in

one common storage facility: Combined storage bans apply from a total storage quantity of 200

kg.

Do not store together with substances of the following LGK: 1; 6.2;

7

Storage with substances of the following LGK is only possible

under the conditions specified in TRGS 510: 4.1A; 5.1C

· Further information about

storage conditions:

Store in a dry and frost-free place.

· Storage class 13

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical	I values that require monitoring at the workplace:
CAS: 14808-60-7 Quartz	sand
OFL (Iroland)	Lang tarm value: 0.1 mg/m3

OEL (Ireland) Long-term value: 0.1 mg/m³
BOELV (European Union) Long-term value: 0.1* mg/m³

*respirable fraction

CAS: 65997-15-1 Portland cement (low chromate)

OEL (Ireland) Long-term value: 1 mg/m³

respirable fraction

CAS: 1317-65-3 Calcium carbonate

OEL (Ireland)

Long-term value: 10* 4** mg/m³

*inhalable dust, **respirable dust

· DNELs

CAS: 65997-15-1 Portland cement (low chromate)

Inhalative DNEL 1 mg/m³ (ArL)

CAS: 1317-65-3 Calcium carbonate

Oral DNEL 6.1 mg/kg bw/Tag (ArL)

Inhalative DNEL 10 mg/m³ (ArL)

· PNECs

CAS: 1317-65-3 Calcium carbonate

PNEC 100 mg/l (Sewage Treatment Plant)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Do not store food, eat, drink, sniff or smoke in the work area!

Avoid contact with eyes and skin!

Clean hands thoroughly at the end of work and before breaks!

Use skin care products after work (moisturising cream).

(Contd. on page 5)



Page 5/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 28 (replaces version 27) Revision: 15.04.2025

Trade name Nafufill KM 110 HS

(Contd. of page 4)

Change and clean heavily soiled clothing!

Change clothes at the end of work!

Apply greasy skin protection ointment before starting work and

after every break.

• Breathing equipment: For work with higher dust loads particle filter class P2

· Hand protection Check protective gloves prior to each use for their proper condition.

• Material of gloves Nitrile impregnated cotton gloves.

· Penetration time of glove

material The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

• Eye/face protection Safety glasses

· Body protection: Protective work clothing.

Skin protection Use greasy skin protection ointment for all uncovered parts of the

body!

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Grey · Smell: neutral

· Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 2230 °C (CAS: 14808-60-7 Quartz sand)

· Flash point: Not applicable · pH Not applicable.

· Viscosity:

Kinematic viscositydynamic:Not applicable.Not applicable.

Solubility

· Water: Unsoluble

· Steam pressure at 1732 °C: 13.5 hPa (CAS: 14808-60-7 Quartz sand)

Density and/or relative density

• Density at 20 °C 2.72 g/cm³ • Particle characteristics See section 3.

· 9.2 Other information

· Appearance:

· Form: Powder

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void

(Contd. on page 6)



Page 6/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 28 (replaces version 27) Revision: 15.04.2025

Trade name Nafufill KM 110 HS

(Contd. of page 5)

· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:			
CAS: 659	CAS: 65997-15-1 Portland cement (low chromate)		
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	5 mg/l (rat)	
CAS: 131	CAS: 1317-65-3 Calcium carbonate		
Oral	LD50	>2000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	

· Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye damage.

(Contd. on page 7)



Page 7/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 28 (replaces version 27) Revision: 15.04.2025

Trade name Nafufill KM 110 HS

(Contd. of page 6)

Respiratory or skin
sensitisation
Based on available data, the classification criteria are not met.
Germ cell mutagenicity
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.
Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

• STOT-repeated exposure
• Aspiration hazard

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 | 2,6-Di-tert-butyl-p-cresol | List II

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity:

CAS: 1317-65-3 Calcium carbonate

EC50/72h >14 mg/l (Desmodesmus subspicatus)
LC50/96h >10000 mg/l (Oncorhynchus mykiss)

LC50/48h >1000 mg/l (Daphnia magna) EC50/48h >1000 mg/l (Daphnia magna)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

European waste catalogue

17 00 00 CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL

FROM CONTAMINATED SITES)

(Contd. on page 8)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 28 (replaces version 27) Revision: 15.04.2025

Trade name Nafufill KM 110 HS

	(Contd. of page 7)
17 01 00	concrete, bricks, tiles and ceramics
17 01 01	concrete
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk accordi IMO instruments	ng to Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 9)



Page 9/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 28 (replaces version 27) Revision: 15.04.2025

Trade name Nafufill KM 110 HS

(Contd. of page 8)

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

· Department issuing data

specification sheet: Environment protection department.

· Date of previous version: 17.10.2021

· Version number of previous

version: 2

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.