

Page 1/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 52 (replaces version 51) Revision: 12.04.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name Nafufill KM 250 HS

· Article number: 794

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Concrete surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS05 GHS07

· Signal word Danger

(Contd. on page 2)



Page 2/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 52 (replaces version 51) Revision: 12.04.2025

#### Trade name Nafufill KM 250 HS

(Contd. of page 1)

Hazard-determining

**components of labelling:** Portland cement (low chromate)

Burnt oil shale

Flue dust, portland cement

Hazard statements H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

• Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/

spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it

before reuse.

P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4	Quartz sand substance with a Community workplace exposure limit	50-70%
CAS: 65997-15-1 EINECS: 266-043-4	Portland cement (low chromate) Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥20-≤30%
CAS: 93685-99-5 Reg.nr.: 01-2119703178-42- 0000	Burnt oil shale STOT RE 2, H373; Eye Dam. 1, H318; STOT SE 3, H335	≥3-<10%
CAS: 68475-76-3 EINECS: 270-659-9	Flue dust, portland cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥1-<1.5%
· Additional information	For the wording of the listed hazard phrases refer to se	ction 16.

(Contd. on page 3)

- IF



Page 3/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 52 (replaces version 51) Revision: 12.04.2025

Trade name Nafufill KM 250 HS

(Contd. of page 2)

### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

• General information For all first aid measures: observe self-protection and consult a

doctor!

· After inhalation Remove people from the dusty area.

· After skin contact Remove heavily soiled clothing. Clean with plenty of soap and

water

· After eye contact Rinse for 10 minutes under running water with the eyelids open.

Always consult an ophthalmologist!

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media

· Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with

water jet or alcohol-resistant foam.

· 5.2 Special hazards arising

from the substance or

mixture No further relevant information available.

5.3 Advice for firefighters

• **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: No special measures required.

· 6.3 Methods and material for

containment and cleaning up: Collect mechanically.

· 6.4 Reference to other

sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Avoid dust formation! Avoid spraying the ready-to-use cementitious

product! Avoid contact with eyes and skin! Clean hands thoroughly at the end of work and before every break! Use skin care products! Change heavily soiled clothing! Change clothes at the end of work! Apply greasy skin protection ointment before starting work and

after each break. Observe work restrictions!

(Contd. on page 4)



Page 4/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 52 (replaces version 51) Revision: 12.04.2025

#### Trade name Nafufill KM 250 HS

(Contd. of page 3)

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: Store bags tightly closed; protect from moisture and water!

Store containers tightly closed in a well-ventilated and well-lit room.

Access only for specialised personnel.

Do not store in break rooms, recreation rooms or sanitary facilities or in stairwells, corridors, escape and rescue routes, passages,

passageways and confined spaces.

· Information about storage in

one common storage facility: Combined storage bans apply from a total storage quantity of 200

kg.

Do not store together with substances of the following LGK: 1; 6.2;

7

Storage with substances of the following LGK is only possible

under the conditions specified in TRGS 510: 4.1A; 5.1C

· Further information about

storage conditions:

Store in a dry and frost-free place.

Storage class 13

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:		
CAS: 14808-60-7 Quartz	sand	
OEL (Ireland)	Long-term value: 0.1 mg/m³	
BOELV (European Union)	Long-term value: 0.1* mg/m³ *respirable fraction	
CAS: 65997-15-1 Portlan	d cement (low chromate)	
OEL (Ireland)	Long-term value: 1 mg/m³ respirable fraction	

· DNELs

CAS: 65997-15-1 Portland cement (low chromate)

Inhalative DNEL 1 mg/m³ (ArL)

CAS: 93685-99-5 Burnt oil shale

Inhalative DNEL 0.233 mg/m³ (ArL)

· PNECs

CAS: 93685-99-5 Burnt oil shale

PNEC | 100 mg/l (BEL) 0.002 mg/l (Mew) 0.02 mg/l (Freshwater)

• Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 5)



Page 5/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 52 (replaces version 51) Revision: 12.04.2025

#### Trade name Nafufill KM 250 HS

(Contd. of page 4)

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Do not store food, eat, drink, sniff or smoke in the work area!

Avoid contact with eyes and skin!

Clean hands thoroughly at the end of work and before breaks!

Use skin care products after work (moisturising cream).

Change and clean heavily soiled clothing! Change clothes at the end of work!

Apply greasy skin protection ointment before starting work and

after every break.

• Breathing equipment: For work with higher dust loads particle filter class P2

• Hand protection Check protective gloves prior to each use for their proper condition.

· Material of gloves Nitrile impregnated cotton gloves.

· Penetration time of glove

material The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

· Eye/face protection Safety glasses

· Body protection: Protective work clothing.

• Skin protection Use greasy skin protection ointment for all uncovered parts of the

body!

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Whitish
 Smell: Odourless
 Melting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range 2230 °C (CAS: 14808-60-7 Quartz sand)

· Flash point: Not applicable

· pH at 20 °C 11

· Viscosity:

· Kinematic viscosity
· dynamic:

Not applicable.

Not applicable.

Solubility

· Water: Unsoluble

• Steam pressure at 1732 °C: 13.5 hPa (CAS: 14808-60-7 Quartz sand)

Density and/or relative density

• Density at 20 °C 2.74 g/cm³ • Particle characteristics See section 3.

(Contd. on page 6)



Page 6/10

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 12.04.2025 Printing date 12.04.2025 Version number 52 (replaces version 51)

#### Trade name Nafufill KM 250 HS

(Contd. of page 5)

· 9.2 Other information

· Appearance:

· Form: Powder

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void Flammable gases Void Void · Aerosols

· Oxidising gases Void · Gases under pressure Void Flammable liquids Void · Flammable solids Void

· Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Void

· Self-heating substances and mixtures

· Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void Void · Organic peroxides Void · Corrosive to metals

### SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability Thermal decomposition /

· Desensitised explosives

conditions to be avoided: No decomposition if used according to specifications.

Void

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

· 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

(Contd. on page 7)



Page 7/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 52 (replaces version 51) Revision: 12.04.2025

Trade name Nafufill KM 250 HS

(Contd. of page 6)

### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

 LD/LC50 values that are relevant for classification:

 CAS: 65997-15-1 Portland cement (low chromate)

 Dermal
 LD50
 2000 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 5 mg/l (rat)

 CAS: 93685-99-5 Burnt oil shale

 Oral
 LD50
 >2000 mg/kg (rat)

 Inhalative
 LOAEL
 0.000699 mg/l (ArL)

Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin

Sensitisation
 Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

**STOT-single exposure** May cause respiratory irritation.

• STOT-repeated exposure
• Aspiration hazard

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

## **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 93685-99-5 Burnt oil shale

EC50/72h 82.7 mg/l (Selenastrum capricornutum)

LC50/96h >100 mg/l (fish)

EC50/48h >100 mg/l (Daphnia magna)

NOEC >100 mg/l (fish)

· 12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

• 12.5 Results of PBT and vPvB assessment
• PBT:
• vPvB:
Not applicable.
Not applicable.

(Contd. on page 8)

List II



Page 8/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 52 (replaces version 51) Revision: 12.04.2025

#### Trade name Nafufill KM 250 HS

(Contd. of page 7)

· 12.6 Endocrine disrupting

properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- **Recommendation**Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Europea	n waste catalogue
17 00 00	CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)
17 01 00	concrete, bricks, tiles and ceramics
17 01 01	concrete
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

· Uncleaned packagings:

• Recommendation: Non contaminated packagings can be used for recycling.

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.

(Contd. on page 9)



Page 9/10

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 12.04.2025 Printing date 12.04.2025 Version number 52 (replaces version 51)

Trade name Nafufill KM 250 HS

(Contd. of page 8)

UN "Model Regulation":

Void

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H315 Causes skin irritation.

> H318 Causes serious eye damage. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated

exposure.

· Department issuing data

specification sheet: Environment protection department.

Date of previous version: 15.10.2021

Version number of previous

51 version:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

(Contd. on page 10)



Page 10/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2025 Version number 52 (replaces version 51) Revision: 12.04.2025

#### Trade name Nafufill KM 250 HS

(Contd. of page 9)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

\* Data compared to the previous version altered.

· IE