

Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 45 (replaces version 44) Revision: 15.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name <u>Nafuflex Easy Tech 1</u>

· Article number: 0033118 000 1

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Bitumen high build coating

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

011007

GHS07

· Signal word Warning

· Hazard-determining

components of labelling: 2-Methyl-2H-isothiazol-3-one 2-Octyl-2H-isothiazol-3-on

(Contd. on page 2)



Page 2/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 15.04.2025 Printing date 15.04.2025 Version number 45 (replaces version 44)

Trade name Nafuflex Easy Tech 1

(Contd. of page 1)

1,2-benzisothiazol-3(2H)-one

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-

isothiazol-3-one (3:1)

· Hazard statements H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

> P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

· Additional information: Contains biocidal products: 1,2-benzisothiazol-3(2H)-one, 2-

> Methyl-2H-isothiazol-3-one, 2-Octyl-2H-isothiazol-3-on, Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-

3-one (3:1)

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Mixture consisting of the following components. · Description:

CAC, 00E0 40 4		
EINECS: 232-490-9 su	itumen ubstance with a Community workplace xposure limit	30-60%
	inc oxide quatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<0.5%
Reg.nr.: 01-2119487014-41 (ui	I-C16-18 (even numbered) and C18 unsaturated) alkylpropane-1,3-diamine	<0.025%
Ac	TOT RE 1, H372; Skin Corr. 1B, H314; Aquatic cute 1, H400 (M=10); Aquatic Chronic 1, H410 M=1); Acute Tox. 4, H302	



Page 3/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 45 (replaces version 44) Revision: 15.04.2025

Trade name Nafuflex Easy Tech 1

		(Contd. of page
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317:C ≥ 0.05 %	<0.025%
CAS: 2682-20-4 EINECS: 220-239-6	2-Methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A;H317: C ≥ 0.0015 %	<i>≥</i> 0.0015-<0.025%
CAS: 26530-20-1 EINECS: 247-761-7	2-Octyl-2H-isothiazol-3-on Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l Specific concentration limit: Skin Sens. 1A;H317: C ≥ 0.0015 %	≥0.0015-<0.0025%
CAS: 55965-84-9 EC number: 911-418-6	Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C;H314: $C \ge 0.6\%$ Skin Irrit. 2; H315: $0.06\% \le C < 0.6\%$ Eye Dam. 1; H318: $C \ge 0.6\%$ Skin Sens. 1A; H317: $C \ge 0.0015\%$	<0.00025%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information For all first aid measures: observe self-protection and consult a

doctor!

• After inhalation Take the person out into the fresh air.

(Contd. on page 4)



Page 4/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 45 (replaces version 44) Revision: 15.04.2025

Trade name Nafuflex Easy Tech 1

(Contd. of page 3)

· After skin contact Remove heavily soiled clothing.

Clean with plenty of water. Do not use thinner or similar.

· After eye contact Rinse for 10 minutes under running water with the eyelids open or

use eye rinsing solution. Always consult an ophthalmologist!

• After swallowing Do not induce vomiting, do not give anything to drink.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

• Protective equipment: No special measures required.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

6.2 Environmental

precautions: Do not allow product to reach sewage system or water bodies.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections No dangerous materials are released.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Open and handle container with care.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: Store frost-free.

Protect powder products from moisture and water.

Only store in the original container or in containers recommended

by the manufacturer.

After decanting, label containers as original containers.

Store containers tightly closed in a well-ventilated and well-lit room.

Access only for specialised personnel.

Do not store in break rooms, recreation rooms or sanitary facilities as well as in stairwells, corridors, escape and rescue routes,

passages, passageways and confined spaces.

(Contd. on page 5)



Page 5/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 45 (replaces version 44) Revision: 15.04.2025

Trade name Nafuflex Easy Tech 1

(Contd. of page 4)

· Further information about

storage conditions: None.
Storage class 12

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 8052-42-4 Bitumen

OEL (Ireland) Long-term value: 0.5 mg/m³

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Do not store food, eat, drink, sniff or smoke in the work area!

Avoid contact with eyes, skin and clothing!

Apply skin protection ointment as a preventive measure to facilitate

skin cleansing.

Remove product residues from the skin!

Only remove dried bitumen from the skin with a suitable cleanser (special skin cleansers, margarine or vegetable oil are also

suitable).

Never use solvents or diesel to clean the skin. Clean hands thoroughly after work and before breaks! Use skin care products after work (moisturising cream).

Wear closed work clothing during work. Change clothes at the end of work!

Breathing equipment: Particle filters P2 are recommended when using the spraying

method (with strong aerosol formation).

Hand protection Gloves made of: Nitrile rubber.

(Category 3 chemical protective gloves, recognisable by the CE

mark with four-digit test number).

Cotton undergloves are recommended when wearing protective

gloves.

Can be used as splash protection: Nitrile-soaked cotton gloves.

Suitable glove brands have been identified for work with bitumen

emulsions: Best: Nitri-Solve 730 KCL: Camatril Velours 730

· Material of gloves

· Penetration time of glove

material

The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

Eye/face protection If there is a risk of splashing: frame goggles.

• Body protection: For spraying processes: Disposable protective suit.

Nitrile rubber, NBR

(Contd. on page 6)



Page 6/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 15.04.2025 Printing date 15.04.2025 Version number 45 (replaces version 44)

Trade name Nafuflex Easy Tech 1

(Contd. of page 5)

Use fat-free or low-fat (oil-in-water emulsion) skin protection · Skin protection

ointment for all uncovered parts of the body!

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Dark brown · Smell: Fish-like • Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 100 °C (CAS: 7732-18-5 Water)

· Flash point: Not applicable

· pH at 20 °C 8.5-9

· Viscosity:

· Kinematic viscosity Not determined. · dynamic at 20 °C: 50000 mPas

· Solubility

· Water: Fully miscible

· Steam pressure at 20 °C: 23 hPa (CAS: 7732-18-5 Water)

· Density and/or relative density

0.85 g/cm3 · Density at 20 °C

· 9.2 Other information

· Appearance:

· Form: Viscous

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void Void · Aerosols Void · Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures

· Substances and mixtures, which emit

flammable gases in contact with water Void Void · Oxidising liquids · Oxidising solids Void

(Contd. on page 7)



Page 7/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 45 (replaces version 44) Revision: 15.04.2025

Trade name Nafuflex Easy Tech 1

(Contd. of page 6)

· Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

· 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous


decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity		Based on available data, the classification criteria are not met.
· LD/LC50	values tha	at are relevant for classification:
CAS: 805	2-42-4 Bit	umen
Dermal	LD50	>2000 mg/kg (rabbit)
	NOAEL	2000 mg/kg (rabbit)
Inhalative	NOAEL	103.9 mg/l (rat)
CAS: 121	9010-04-4	N-C16-18 (even numbered) and C18 (unsaturated) alkylpropane-1,3-
		diamine
Oral	LD50	500 mg/kg (rat)
	NOAEL	0.4 mg/kg (rat)
CAS: 263	4-33-5 1,2	-benzisothiazol-3(2H)-one
Oral	LD50	1020 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
CAS: 268	2-20-4 2-N	lethyl-2H-isothiazol-3-one
Oral	LD50	50-300 mg/kg (rat)
Inhalative	LC50/4 h	0.11 mg/l (rat)
CAS: 265	30-20-1 2-	Octyl-2H-isothiazol-3-on
Oral	LD50	125 mg/kg (ATE)
		500 mg/kg (rat)
Dermal	LD50	311 mg/kg (ATE)
		>2000 mg/kg (rat)
		(Contd. on page 8

(Contd. on page 8)



Page 8/12

Version number 45 (replaces version 44) Revision: 15.04.2025 Printing date 15.04.2025

Trade name Nafuflex Easy Tech 1

BE SURE. BUILD SURE

		(Contd. of page 7)		
Inhalative	LC50/4 h	0.27 mg/l (ATE)		
		0.6 mg/l (rat)		
CAS: 55965-84-9 Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-				
isothiazol-3-one (3:1)				
Oral	LD50	49.6-75 mg/kg (rat)		
Dermal	LD50	87.12 mg/kg (rabbit)		
Inhalative	LC50/4 h	0.171 mg/l (rat)		

Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met. · Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxid	· 12.1 Toxicity			
· Aquatic to	· Aquatic toxicity:			
CAS: 8052	CAS: 8052-42-4 Bitumen			
EC50/72h	>1000 mg/l (algae)			
LC50/96h	0.002 mg/l (Coregonus clupeaformis)			
	>1000 mg/l (fish)			
EC50	0.062 mg/l (Gammarus pseudolimnaeus)			
LC50/48h	>1000 mg/l (Daphnien)			
NOEC	>1000 mg/l (Daphnien)			
CAS: 1219	CAS: 1219010-04-4 N-C16-18 (even numbered) and C18 (unsaturated) alkylpropane-1,3-			
	diamine			
LC50/24h	0.148 mg/l (fish)			
EC50	0.29 mg/l (Daphnia magna)			
NOEC	>0.01 mg/l (algae)			
CAS: 2634	4-33-5 1,2-benzisothiazol-3(2H)-one			
EC50/72h	0.067 mg/l (Pseudokirchneriella subcapitata)			
	0.11 mg/l (Selenastrum capricornutum)			

(Contd. on page 9)



Page 9/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 45 (replaces version 44) Revision: 15.04.2025

Trade name Nafuflex Easy Tech 1

(Contd. of page 8)

LC50/96h | 1.6 mg/l (Oncorhynchus mykiss)

EC50/48h | 1.1 mg/l (Daphnia magna)

CAS: 2682-20-4 2-Methyl-2H-isothiazol-3-one

EC50/72h | 0.157 mg/l (Pseudokirchneriella subcapitata)

LC50/96h | 6 mg/l (Oncorhynchus mykiss)

EC50/48h 1.68 mg/l (Daphnies)

CAS: 26530-20-1 2-Octyl-2H-isothiazol-3-on

EC50/48h | 0.42 mg/l (Daphnien)

CAS: 55965-84-9 Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

LC50/24h | 0.19 mg/l (fish)

EC50/72h 0.027 mg/l (Pseudokirchneriella subcapitata)

LC50/96h 0.19 mg/l (Oncorhynchus mykiss)

LC50/48h | 0.28 mg/l (fish)

EC50/48h 0.16 mg/l (Daphnia magna)

NOEC 0.02 mg/l (Oncorhynchus mykiss)

0.00049 mg/l (Ske)

0.1 mg/l (Daphnia magna)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

Das ausgehärtete Produkt ist wie Bitumen im allgemeinen nicht

wassergefährdend (WGK -)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

(Contd. on page 10)



Page 10/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 45 (replaces version 44) Revision: 15.04.2025

Trade name Nafuflex Easy Tech 1

(Contd. of page 9)

•	n waste catalogue
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 14	aqueous sludges containing adhesives or sealants other than those mentioned in 08 04 13
HP14	Ecotoxic

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according IMO instruments	to Not applicable.
· Transport/Additional information:	Not dangerous according to the abov specifications.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture

No further relevant information available.

(Contd. on page 11)



Page 11/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 45 (replaces version 44) Revision: 15.04.2025

Trade name Nafuflex Easy Tech 1

(Contd. of page 10)

· REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases	H301	Toxic if swallowed.
	11000	

H302 Harmful if swallowed.H310 Fatal in contact with skin.H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H372 Causes damage to organs through prolonged or repeated

exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Department issuing data

specification sheet: Environment protection department.

Date of previous version: 18.10.2021

Version number of previous

version: 44

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

(Contd. on page 12)



Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.04.2025 Version number 45 (replaces version 44) Revision: 15.04.2025

Trade name Nafuflex Easy Tech 1

(Contd. of page 11)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity - Category 2 Skin Corr. 1: Skin corrosion/irritation - Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard -

Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 3

^{* *} Data compared to the previous version altered.