

PRODUCT PROPERTIES

- Cost effective powder concentrate
- Soluble in water up to 1 : 20
- Short soaking time

AREAS OF APPLICATION

- Removal of mortar and concrete splashes on:
 - construction machines
 - construction equipment
- Cleaning of
 - precast concrete elements
 - washed out concrete slabs
 - clinker
 - ceramic facings
 - efflorescence
- Removal of cement streaks and residues

APPLICATION ADVICE

Before using Donnital 3 X please read the warnings and safety notes on the packaging. The cleaning agent affects mucous membranes. Contact with the eyes must be avoided (use protective goggles)!

Preparation Depending on the application, dilute Donnital 3 X with water at a mixing ratio of between 1 : 4 and 1 : 20. The optimal mixing ratio should be determined by prior test runs.

Application The mixed solution is applied with scrubbing brush, broom or paintbrush onto the thoroughly wetted substrate. After a short treatment time, the cleaning process is supported by mechanical action. For especially persistent contamination apply Donnital 3 X repeatedly until the contaminant has been sufficiently removed.

The treated area must be thoroughly washed with water after each cleaning process, to remove unused residues of Donnital 3 X. This is especially important when working with metal substrates.

Mixing trucks, construction equipment and other metal parts should be preserved with a suitable preservation agent (e. g. Intaktin UWV) after cleaning.

Further Information Application equipment should not contain metals, especially iron, as Donnital 3 X causes corrosion if exposed for longer periods.

Discoloration may occur on mineral substrates.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Application conditions	°C	≥ 5	
Consumption (flat)	g/m ²	250 - 300	
All technical values are laboratory results determined at 21°C ±2°C and 50% relative humidity.			
Equipment cleaning agent	Clean with water immediately after use		
Delivery form	12 kg tub(s)		
Self-monitoring	EN ISO 9001		
Hazardous substance according to the Ordinance on Hazardous Substances	Ensure compliance with the DIN Safety Data Sheet!		
Storage	Can be stored in cool and dry conditions for at least 12 months in original unopened packs.		
Packaging disposal	Make sure single-use containers are completely empty.		

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets. GISCODE : BZM10

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2400020633]