

MC-Cleaner G

Anti graffiti-cleaner



PRODUCT PROPERTIES

- Solvent containing
- Ready-for-use, easy application
- Application by paint-brush and brush
- Gel-like consistency, drip-free application

AREAS OF APPLICATION

- Removal of graffiti on MC-Color Proof vision and MC-Color Flair vision
- Only to be used in combination with these products
- REACH-assessed exposure scenarios: periodical inhalation, application

APPLICATION ADVICE

Product Description: MC-Cleaner G is especially developed to remove graffiti. It is ready-for-use and therefore offers a rapid, easy and thorough removal of graffiti, coloured pencils, markers and lacquers.

Graffiti Removal: MC-Cleaner G is applied onto the stained areas using a soft brush and spread in circles (without interruption). Mechanical cleaning has a big influence on the result. On rough substrates MC-Cleaner G must be applied by brush. After a short waiting time of approx. 5 - 8 minutes (max. 10 min.) the paint can be removed from the substrate using a rubber squeegee, disposed properly with paper towels and washed off with a moist sponge. Tenside-containing water increases the cleaning intensity. The etched paint must not dry during cleaning. Therefore high wind velocities and direct sunlight must be avoided.

Safety Measures: Protective gloves and goggles must be worn when working with MC-Cleaner G. Recommended are the protective groves Ultranitrl 492 and / or Ultranitrl 381 from MAPA. DIN-safety data sheets must be observed!

General Information: Please request or technical advice in advance.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Density	kg/dm ³	0.98	
Application conditions	°C	≥ 5 ≤ 30	Temperatura del aire, soporte y material
	%	< 80	rel. humidity
	K	3	above dew point
Consumption ¹⁾	g/m ²	approx. 150 - 200	
Exposure time	minutes	≥ 2	minimum
		5	maximum

All technical values are laboratory results determined at 21°C ±2°C and 50% relative humidity.

1) Depending on the type of surface and the graffiti paint used, the consumption can also be noticeably higher.

Colour	transparent
Delivery form	5 kg buckets
Storage	Can be stored in cool and dry conditions for at least 24 months in original unopened packs.
Packaging disposal	Make sure single-use containers are completely empty.

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2400020484]