

# MC-Cleaner eco

Tool and equipment cleaner



## PRODUCT PROPERTIES

- VOC-reduced universal cleaner based on renewable raw materials
- Significantly reduced exposure of the work environment to harmful vapors
- Extremely good cleaning effect at low consumption

## AREAS OF APPLICATION

- Cleaner for tools and equipment when working with reactive resins or sealants

## APPLICATION ADVICE

To achieve a good cleaning effect, it is sufficient to apply MC-Cleaner Eco in a thin layer to the part to be cleaned. After a short exposure time, the loosened dirt is wiped off with an absorbent cloth. Larger quantities of tools can also be immersed in a cleaner bath. However, cleaning with a paintbrush or brush before removal is necessary, same as wiping with an absorbent cloth. Processing machines (e.g. injection pumps or dispenser guns for sealants) can be rinsed with MC-Cleaner Eco. Existing hoses and gaskets are less attacked compared to cleaning with conventional solvents. After the cleaning process has been completed, residues of the cleaning solution must be removed from the processing equipment in order not to damage gaskets etc.

The used cleaner can be collected in suitable containers and after the suspended matter has settled it can be used again by carefully pouring off the clean parts of the liquid.

## TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Density	g/cm <sup>3</sup>	approx. 0.9	
All technical values are laboratory results determined at 21°C ±2°C and 50% relative humidity.			
Form		liquid	
Colour		transparent	
Delivery form		Can with 5 kg content	
Storage		Can be stored in original sealed packages at temperatures between 5°C and 20°C in dry conditions for at least 24 months.	
Packaging disposal		Make sure single-use containers are completely empty.	

### Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

**Note:** The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2400020665]